

# AXIS M4206-LV Network Camera

## Varifocal mini dome with IR and HDMI

AXIS M4206-LV Network Camera delivers clear, sharp video surveillance in any light conditions whether you need hawk-eye overviews or detailed close-ups. The ultra-compact and dust-resistant casing is designed to blend seamlessly into any indoor environment. AXIS M4206-LV only requires two screws to mount on ceiling or wall, and the camera features a varifocal lens that can be adjusted from a remote location. With over 40% recycled plastics, AXIS M4206-LV is designed for flexible, cost-effective and environment-friendly installations.

- > **3 MP/HDTV 1080p**
- > **Varifocal lens with remote zoom and focus**
- > **Optimized IR and WDR for any light conditions**
- > **Zipstream with H.264 and H.265**
- > **HDMI output for public monitors**



# AXIS M4206–LV Network Camera

<b>Camera</b>		<b>Built-in installation aids</b>	Remote zoom, remote focus, pixel counter OptimizedIR with adjustable IR illumination intensity
<b>Image sensor</b>	1/2.5" progressive scan RGB CMOS	<b>General</b>	
<b>Lens</b>	Varifocal, 3–6 mm, F2.0 Horizontal field of view: 100°–45° Vertical field of view: 72°–34° Remote focus and zoom, fixed iris	<b>Casing</b>	IP42 water- and dust-resistant, IK08 impact-resistant, polycarbonate and aluminum casing with hard-coated dome (to comply with IP42, follow Installation Guide) Encapsulated electronics Color: white NCS S 1002-B For repainting instructions of casing and impact on warranty, contact your Axis partner.
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>Sustainability</b>	PVC free, 43% recycled plastics
<b>Minimum illumination</b>	Color: 0.26 lux at 50 IRE F2.0 B/W: 0.05 lux at 50 IRE F2.0, 0 lux when IR illumination is on	<b>Memory</b>	512 MB RAM, 512 MB Flash
<b>Shutter time</b>	1/10000 s to 1/5 s	<b>Power</b>	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 4.6 W, max 8.1 W
<b>Camera angle adjustment</b>	Pan ±180°, tilt -40 to +65°, rotation ±105° Can be directed in any direction and see the wall/ceiling	<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX PoE HDMI type D
<b>Video</b>		<b>IR illumination</b>	OptimizedIR with power-efficient, long-life 850 nm IR LEDs Range of reach 15 m (50 ft) or more depending on the scene
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main and High Profiles Motion JPEG	<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
<b>Resolution</b>	2048x1536 to 320x240	<b>Operating conditions</b>	0 °C to 45 °C (32 °F to 113 °F) Humidity 10–85% RH (non-condensing)
<b>Frame rate</b>	25/30 fps with power line frequency 50/60 Hz	<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Video streaming</b>	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/MBR H.264/H.265 HDMI	<b>Approvals</b>	EMC EN 55032 Class A, EN 50121-4, EN 55024, EN 61000-6-1, EN 61000-6-2, IEC 62236-4, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A Safety IEC/EN/UL 62368-1 IEC 62471 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-6, IEC/EN 60529 IP42, IEC/EN 62262 IK08 Network NIST SP500-267
<b>Multi-view streaming</b>	Up to 2 individually cropped out view areas in full frame rate streaming	<b>Dimensions</b>	Height: 71 mm (2 3/4 in) ø 121 mm (4 3/4 in)
<b>HDMI output</b>	HDMI 1080p (16:9) @25/30 fps (50/60 Hz) HDMI 720p (16:9) @50/60 fps (50/60 Hz)	<b>Weight</b>	370 g (0.82 lb)
<b>Image settings</b>	Compression, color, brightness, sharpness, contrast, white balance, exposure control, WDR: up to 110 dB depending on scene, text and image overlay, mirroring of images, privacy mask Rotation: 0°, 90°, 180°, 270°, including Corridor Format	<b>Included accessories</b>	Installation guide, Windows® decoder 1-user license
<b>Pan/Tilt/Zoom</b>	Digital PTZ	<b>Optional accessories</b>	AXIS T94C01L Recessed Mount AXIS T94C01U Universal Mount AXIS T94C01M J-Box/Gang Box Plate AXIS M42 Casing A Black 4P AXIS M42 Smoked Dome A 4P AXIS T91A33 Lighting Track Mount AXIS T91A23 Tile Grid Ceiling Mount AXIS TM3101 Pendant Wall Mount AXIS Surveillance Cards For more accessories, see <a href="http://axis.com">axis.com</a>
<b>Network</b>		<b>Video management software</b>	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware	<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Japanese, Korean, Portuguese, Simplified Chinese, Traditional Chinese
<b>Supported protocols</b>	IPv4, IPv6 USGv6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, Bonjour, UPnP <sup>®</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, DHCP, SOCKS, SSH, HDMI 1.4b, LLDP	<b>Warranty</b>	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://axis.com/warranty">axis.com/warranty</a>
<b>System integration</b>		a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ( <a href="http://openssl.org">openssl.org</a> ), and cryptographic software written by Eric Young ( <a href="mailto:ey@cryptsoft.com">ey@cryptsoft.com</a> ).	
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> AXIS Guardian with One-Click Connection ONVIF <sup>®</sup> Profile G and ONVIF <sup>®</sup> Profile S, specification at <a href="http://onvif.org">onvif.org</a>	Environmental responsibility: <a href="http://axis.com/environmental-responsibility">axis.com/environmental-responsibility</a>	
<b>Analytics</b>	<b>Included</b> AXIS Video Motion Detection <b>Supported</b> AXIS Fence Guard, AXIS Motion Guard, AXIS Loitering Guard, AXIS People Counter, AXIS Occupancy Estimator, AXIS Direction Detector, AXIS Tailgating Detector, AXIS Random Selector, AXIS Queue Monitor Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>		
<b>Event triggers</b>	Analytics, edge storage events, virtual inputs through API		
<b>Event actions</b>	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap Overlay text		
<b>Data streaming</b>	Event data		