

# PDU Power Cord, C13 to P-Lock C14 - North America and Europe Rated, 10A, 250V, 18 AWG, 3 ft. (0.9 m), Black

MODEL NUMBER: P004-E03



Connects a computer, server or switch to a PDU with a P-Lock C13 or C39 power connector and extends your existing power connection by 3 ft.

## Features

### Locking C13-to-C14 Power Cable Connects Computers and Servers to a PDU

The P004-E03 power extension cord can be used to power a computer, server, switch or other device commonly found in a small data center, office workstation or other lower-amp application. The three-foot (0.9-meter) length helps reduce cable clutter by providing a tailor-made fit between the device and the PDU in a crowded rack enclosure. It complies with UL and VDE standards for international application use.

### Forms a Special Locking Connection with a P-Lock Outlet

The P-Lock C14 connector forms a secure connection with a PDU with a P-Lock outlet, including Eaton G4 and newer PDUs with C13 and C39 outlets. The P-Lock connection helps reduce costly downtime caused by accidental cable disconnections in a crowded rack or PDU space. The P004-E03 lets you replace a non-locking C14/C13 cable or upgrade an entire PDU application by pairing with an Eaton PDU or other PDU with P-Lock outlets.

## Highlights

- Recommended for powering computers, servers and other network devices
- P-Lock C14 connector eliminates accidental cable disconnections in a crowded PDU
- 3 ft. length allows flexibility in mounting devices within a rack while avoiding cable clutter
- PDU-style cord replaces or upgrades non-locking power cable provided by manufacturer
- Complies with UL and VDE standards for use in international applications

## Package Includes

P004-E03 PDU Power Cord, C13 to P-Lock C14, 3 ft. (0.9 m), Black

# Specifications

| OVERVIEW             |                                                   |
|----------------------|---------------------------------------------------|
| UPC Code             | 037332292933                                      |
| Product Type         | PDU Power Cord                                    |
| Device Compatibility | Computer; Monitor/HDTV; Printer; Server; UPS; PDU |
| Country/Region       | Global                                            |
| INPUT                |                                                   |
| Maximum Input Amps   | 10                                                |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                              |
|--------------------------------------|------------------------------|
| Voltage Compatibility (VAC)          | 100-250                      |
| <b>CONNECTIONS</b>                   |                              |
| Side A - Connector 1                 | IEC-320-C14                  |
| Side B - Connector 1                 | IEC-320-C13                  |
| <b>PHYSICAL</b>                      |                              |
| Plug Color                           | Black                        |
| Cable Jacket Color                   | Black                        |
| Connector Color                      | Black                        |
| Cable Jacket Material                | PVC                          |
| Cable Jacket Rating                  | H05VV-F; SJT; VW-1           |
| Power Cord Jacket Type               | SJT + H05VV-F                |
| Cable Outer Diameter (OD)            | 7.0mm                        |
| Number of Conductors                 | 3                            |
| Wire Gauge (AWG)                     | 18                           |
| Wire Gauge (OD - mm <sup>2</sup> )   | 1.0                          |
| Cable Length (ft.)                   | 3                            |
| Cable Length (m)                     | 0.91                         |
| Shipping Dimensions (hwd / in.)      | 10.00 x 7.99 x 0.50          |
| Shipping Weight (lbs.)               | 0.82                         |
| Shipping Weight (kg)                 | 0.37                         |
| Unit Dimensions (hwd / in.)          | 10.000 x 7.990 x 0.500       |
| <b>ENVIRONMENTAL</b>                 |                              |
| Operating Temperature Range          | 23° to 158°F (-5° to 70°C)   |
| Storage Temperature Range            | 14° to 140°F (-10° to 60°C)  |
| Relative Humidity                    | 35 TO 85% RH, Non-Condensing |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                              |
| Antibacterial                        | No                           |
| Angled Plug                          | No                           |
| High Voltage                         | Yes                          |
| Locking Plug                         | Yes                          |
| Coiled Power Cord                    | No                           |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                              |
| Product Certifications               | cUL Listed; UL Listed        |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| Product Compliance                  | CE (Europe); REACH; RoHS3; UKCA; WEEE |
| WARRANTY & SUPPORT                  |                                       |
| Product Warranty Period (Worldwide) | Lifetime limited warranty             |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.