Product data sheet

Specifications





Rack PDU 2G, Switched, ZeroU, 15A, 100-120V, (8) 5-15

AP8931

Overview

Presentation

APC Switched Rack Power Distribution Units (PDUs) enable advanced, usercustomizable power control and active monitoring. Remote outlet level controls allow
power on/off functionality for power recycling to remotely reboot equipment and
restrict unauthorized use of individual outlets. Power sequencing delays allow users
to define the order in which to power up or down attached equipment. Avoid circuit
overload during power recovery and extend uptime of critical equipment by
prioritizing the load shedding. Current metering provides real-time remote monitoring
of connected loads. Switched Rack PDUs include real power monitoring, a
temperature/humidity sensor port and low profile circuit breakers. User-defined
alarms warn of potential circuit overloads before critical IT failures occur. Users can
access, configure, and control Switched Rack PDUs through secure Web, SNMP, or
Telnet Interfaces and is complimented by APC Centralized Management platforms
using InfraStruxure Central, Capacity Manager and Change Manager.

Lead time Usually in Stock

Main

Color	Black
Product or Component Type	PDU
PDU Type	Switched
Cord length	10 ft (3.05 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets Serial configuration cable Safety guide

Complementary

Input Voltage	100 V 120 V
Height	38.9 in (98.8 cm)
Width	2.2 in (5.5 cm)
Output Voltage	100 V 120 V
Depth	1.8 in (4.6 cm)
Net Weight	9.17 lb(US) (4.16 kg)
Mounting Location	Side
Mounting preference	No preference
Input Plug Type	NEMA 5-15P
Mounting Mode	Not rack-mountable
Rack units	0U

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Mounting position	Vertical
Line Rated Current	12 A
Acceptable Input Voltage	100120 V
Input current limits	15 A
Load Capacity	1440 VA
Input Frequency	50/60 Hz
Outlet type and quantity	8 NEMA 5-15R

Environment

Product Certifications	cUL Listed PSE UL Listed
Standards	FCC Part 15 class A ICES-003 UL 60950-1
Ambient Air Temperature for Operation	23140 °F (-560 °C)
Relative Humidity	595 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	595 %
Storage altitude	050000 ft (0.000000000015240.0000000000 m)

Ordering and shipping details

GTIN 731304307525

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	44.5 in (113.1 cm)
Package 1 Width	4.26 in (10.83 cm)
Package 1 Length	6.3 in (16 cm)
Package 1 Weight	11.07 lb(US) (5.02 kg)

Contractual warranty

Warranty 2 years repair or replace



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >









Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Lead Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation

Eu Rohs Directive

Compliant with Exemptions

Environmental Disclosure

Product Environmental Profile

Circularity Profile

End of Life Information

WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov