



PM-81

COMPACT PANEL MOUNT KEYBOARD

The PM-81 is a small-footprint keyboard that offers an alternative solution when space is at a premium. It has 12 function keys and standard keycap sizing. iKey's rugged panel mount keyboards allow for easy integration into workstations or other industrial environments. The PM-81 is designed to meet NEMA 4X specifications, which enables it to withstand the roughest of conditions. Features: Stainless Steel Bezel USB, PS/2 and AT Configurations Available

Product Code PM-81

CERTIFICATIONS	NEMA 4X, CE UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet (3 meters) DESIGN: PS/2, AT or Single-Cable USB
KEY SWITCH	MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 6.35 oz. +/- 1.06 oz. (180g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2: 50mA@5V (from Keyboard port) USB: 50mA@5V (from CPU port)
COMPATIBILITY	PS/2 KEYBOARD: All Windows Operating Systems USB KEYBOARD: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
WEIGHT	3.50 lbs +/- 0.10 lbs (1.59 kg +/- 0.05 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100% (when properly installed)
DIMENSIONS	14.05" x 7.81" x 1.58" (w-h-d) 356.9mm x 198.4mm x 40.1mm CUTPIT: 12.75" x 6.50" (w-h) 323.9mm x 165.1 mm
MODEL NUMBERS	PM-81-PS2: With PS/2 cable PM-81-USB: With USB cable PM-81-STD: With AT cable