

# Product data sheet

Specifications



## APC Performance SurgeArrest 11 Outlet with Phone (Splitter) and Coax Protection, 120V

P11VT3

⚠ Discontinued on: Feb 14, 2024

⚠ To be end-of-service on: Sep 30, 2024

⚠ To be discontinued

### Overview

Lead time Usually in Stock

### Main

|                       |   |
|-----------------------|---|
| Main Input Voltage    | 120 V   |
| Input Connection Type | NEMA 5-15P                                      |
| Cable length          | 8 ft (2.4 m)                                    |
| Number of cables      | 1   |
| Provided equipment    | Coaxial cable<br>Telephone Cable<br>User Manual |

### Physical

|                     |                       |
|---------------------|-----------------------|
| Color               | Black                 |
| Height              | 1.6 in (4 cm)         |
| Width               | 4.7 in (11.9 cm)      |
| Depth               | 11.9 in (30.2 cm)     |
| Net Weight          | 2.34 lb(US) (1.06 kg) |
| Mounting preference | No preference         |
| Mounting Mode       | Not rack-mountable    |

### Input

|                            |          |
|----------------------------|----------|
| Input Frequency            | 50/60 Hz |
| Switching current capacity | 15 A     |

### Output

|                                |            |
|--------------------------------|------------|
| Number of power socket outlets | 11         |
| Outlet standard                | NEMA 5-15R |

### Conformance

|                        |                                  |
|------------------------|----------------------------------|
| UL 1449 TVSS Rating    | L-N: 400<br>L-G: 500<br>N-G: 500 |
| Product Certifications | CSA                              |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

|                             |                     |
|-----------------------------|---------------------|
| Standards                   | UL 1363<br>UL 1449  |
| Equipment protection policy | Lifetime : \$100000 |

## Environmental

|                                       |  |
|---------------------------------------|--|
| Ambient Air Temperature for Operation | 5...113 °F (-15...45 °C)                         |
| Relative Humidity                     | 0...95 %   |
| Operating altitude                    | 0...10000 ft                                     |
| Ambient Air Temperature for Storage   | 5...113 °F (-15...45 °C)                         |
| Storage Relative Humidity             | 0...95 %   |
| Storage altitude                      | 0...50000 ft (0.0000000000...15240.0000000000 m) |

## Surge Protection and Filtering

|   |                  |
|---|------------------|
| Data Lines Protected<br>(multi-line only) | 1-4              |
| NM Surge Response Time (ns)               | 1 ns common mode |
| Common mode rejection                     | 70 dB            |
| Surge energy rating                       | 3020 J           |

## Ordering and shipping details

|      |              |
|------|--------------|
| GTIN | 731304249030 |
|------|--------------|

## Packing Units

|                              |                           |
|------------------------------|---------------------------|
| Unit Type of Package 1       | PCE                       |
| Number of Units in Package 1 | 1                         |
| Package 1 Height             | 2.4 in (6 cm)             |
| Package 1 Width              | 13.6 in (34.5 cm)         |
| Package 1 Length             | 7.6 in (19.2 cm)          |
| Package 1 Weight             | 2.98 lb(US) (1.35 kg)     |
| Number of Units in Package 2 | 6                         |
| Package 2 Height             | 15 in (381.0000000000 mm) |
| Package 2 Width              | 8 in (203.2 mm)           |
| Package 2 Length             | 15 in (381.0000000000 mm) |
| Package 2 Weight             | 19.58 lb(US) (8.88 kg)    |
| SCC14                        | 10731304249037            |

## Contractual warranty

|          |                  |
|----------|------------------|
| Warranty | Limited Lifetime |
|----------|------------------|

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



RoHS/REACH

## Well-being performance

Reach Free Of Svhc

---

Mercury Free

---

Rohs Exemption Information Yes

---

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

---

Eu Rohs Directive Compliant with Exemptions

---

Circularity Profile [End of Life Information](#)

---