

Product datasheet

Specifications



APC Rack PDU 9000 Switched, ZeroU, 11.0kW, 230V, (21) C13 & (3) C19

APDU9981EU3

Overview

Lead time Usually in Stock

Main

| | |
|---------------------------|--|
| Colour | Black |
| Product or component type | PDU |
| PDU type | Switched |
| Cord length | 1.8 m |
| Number of cables | 1 |
| Provided equipment | Installation guide Rack mounting brackets Safety guide |

Complementary

| | |
|-----------------------------|----------------------------|
| Input Voltage | 400 V 3 phases |
| Height | 179.2 cm |
| Width | 5.5 cm |
| Output Voltage | 230 V |
| Depth | 4.6 cm |
| Net weight | 7 kg |
| Mounting location | Side |
| Mounting preference | No preference |
| Input Plug Type | IEC 60309 16 A 3P + N + PE |
| Mounting mode | Not rack-mountable |
| Rack units | 0U |
| USB compatible | No |
| Mounting position | Vertical |
| Communication port protocol | SNMP Redfish |
| [In] rated current | 16 A |
| Max line current | 16 A |
| Input current limits | 16 A |
| Load capacity | 11000 VA |
| Network frequency | 50/60 Hz |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-----------------------------------|-------------------------------------|
| Outlet type and quantity | 21 IEC 60320 C13 3 IEC 60320 C19 |
| Communication network type | 10/100/1000BASE-T |

Environment

| | |
|--|--|
| Product certifications | cUL listed FCC part 15 class A UL listed VDE |
| Standards | EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 ICES-003 |
| Ambient air temperature for operation | -5...60 °C |
| Relative humidity | 5...95 % |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -25...65 °C |
| Storage Relative Humidity | 5...95 % |
| Storage altitude | 0.0000000000...15240.0000000000 m |

Packing Units

| | |
|-------------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 200.2 cm |
| Package 1 Width | 11.4 cm |
| Package 1 Length | 16.5 cm |
| Package 1 Weight | 8.95 kg |

Contractual warranty

| | |
|-----------------|---------------------------|
| Warranty | 3 years repair or replace |
|-----------------|---------------------------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

RoHS Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu RoHS Directive Compliant with Exemptions

China RoHS Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)