

# Product data sheet

Specifications



## Rack PDU 2G, Switched, ZeroU, 20A/208V, 16A/230V, (7) C13 & (1) C19

AP8958

### Overview

**Presentation** APC Switched Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and active monitoring. Remote outlet level controls allow power on/off functionality for power recycling to remotely reboot equipment and restrict unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and low profile circuit breakers. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched Rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.

**Lead time** Usually in Stock

### Main

<b>Color</b>	Black
<b>Product or Component Type</b>	PDU
<b>PDU Type</b>	Switched
<b>Provided Equipment</b>	Installation guide Rack Mounting brackets Serial configuration cable Safety guide

### Complementary

<b>Input Voltage</b>	200 V 208 V 230 V
<b>Height</b>	38.9 in (98.8 cm)
<b>Width</b>	2.2 in (5.6 cm)
<b>Output Voltage</b>	100 V 200 V 208 V 230 V
<b>Depth</b>	1.8 in (4.6 cm)
<b>Net Weight</b>	7.12 lb(US) (3.23 kg)
<b>Mounting Location</b>	Side
<b>Mounting preference</b>	No preference
<b>Input Plug Type</b>	IEC 60320 C20
<b>Mounting Mode</b>	Not rack-mountable
<b>Rack units</b>	0U

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Mounting position	Vertical
Line Rated Current	16 A
Acceptable Input Voltage	100...240 V
Input current limits	20 A
Load Capacity	3300 VA
Input Frequency	50/60 Hz
Outlet type and quantity	7 IEC 60320 C13 1 IEC 60320 C19

## Environment

Product Certifications	cUL Listed PSE UL Listed VCCI Class A VDE
Standards	EN 55022 Class A EN 55024 EN 61000-3-2 EN 61000-3-3 FCC Part 15 class A ICES-003
Ambient Air Temperature for Operation	23.0000000000...140.0000000000 °F (-5...60 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13.0000000000...149.0000000000 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

## Ordering and shipping details

GTIN	731304277101
Country of origin	IN

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	44.3 in (112.5 cm)
Package 1 Width	6.5 in (16.5 cm)
Package 1 Length	4.5 in (11.4 cm)
Package 1 Weight	10.49 lb(US) (4.76 kg)

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH


## Resource performance


 Energy Efficient Product

 Take-Back Program Available

## Well-being performance

 Lead Free

 Mercury Free

 Rohs Exemption Information [Yes](#)

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)