

## Planar PLL2210MW - White

22" LCD Monitor

The Planar® PLL2210MW-WH 22" widescreen LED backlit LCD monitor is a great value for home or office. This slim, space-saving monitor delivers superb performance at a great price point.



| SPECIFICATION            | DETAIL   |
|--------------------------|--|
| Product Name             | PLL2210MW-WH   |
| Planar Part Number       | 997-6404-00  |
| Viewable Size            | 21.5" diagonal (18.77" horizontal x 10.56" vertical)     |
| Aspect Ratio             | 16:9   |
| Contrast Ratio (typ)     | 1000:1   |
| Viewing Angle (typ)      | 170° Horizontal and 160° Vertical (Specified at CR>10:1) |
| Response Time (typ)      | 5 ms   |
| Brightness (Typical)     | 250 cd/m²  |
| Display Type             | Edge-Lit LED LCD   |
| Display Resolution       | 1920 x 1080, full HD                                     |
| Tilt Range               | -0° to +20°  |
| Palette                  | 16.7 million colors                                      |
| Pixel Pitch              | 0.24825  |
| Refresh Rate             | 56~75 Hz (60 Hz recommended)                             |
| Dimensions (W x H x D)   | 19.94" x 15.35" x 7.0" (506.5 mm x 389.9 mm x 177.8 mm)  |
| Dimensions without Stand | 19.94" x 12.64" x 1.91" (506.5 mm x 321.1 mm x 48.5 mm)  |
| Panel Depth              | 1.91" (48.5 mm)  |
| Display Weight           | 7 lb (3.2 kg)  |
| Shipping weight          | 9 lb (4.1 kg)  |
| Video Inputs             | Analog and Digital (DVI-D w/HDCP)                        |

| HDCP                     | Yes  |
|--------------------------|--|
| External Connections     | 1 - DVI 24-pin connector; 1 - VGA D-sub 15-pin video connector; 1 - 1/8 inch audio jack  |
| Audio Output             | Integrated TrueMedia™ speakers, 1W/channel, Headset jack   |
| Compatibility            | PC and Mac® (adapter may be required for Mac)  |
| Power Supply             | External (DC power)  |
| Power Consumption (max)  | 25W Typical, (0.5W standby)  |
| Power Requirements       | AC 100/240 VAC   |
| Operating Temperature    | 0° to +40°C (32° to 104°F)   |
| Humidity                 | 10 - 90% RH (non-condensing)   |
| VESA Compatible/Location | Built-in 100mm VESA, monitor back  |
| Product Approvals        | UL/cUL, CE, FCC-B, RoHS  |
| Recommended Usage        | Up to 16 hours per day   |
| Service and Support      | 3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only). Please see warranty document for more details and for replacement procedures outside the US. |
| Options / Features       | Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot   |
| Blue Light Reduction     | Yes  |
| In the Box               | PLL2210MW 22" LCD Monitor, 12V DC AC Adaptor, Power Cord, VGA Cable, DVI Cable, Audio Cable, User's Guide  |
| UPC                      | 8 10689 06404 6  |