



Overview

| | |
|----------------------|--|
| Model Name | APC Home Office SurgeArrest 8 Outlet with Phone (Splitter) and Coax Protection, 120V |
| Includes | Coaxial cable , Cord management straps , Telephone Cable , User Manual |
| Standard Lead Time | Usually in Stock |
| Product Distribution | Canada , United States |

Output

| | |
|-------------------|------------|
| Number of Outlets | 8 |
| Receptacle Style | NEMA 5-15R |

Input

| | |
|--------------------------------|-------------|
| Nominal Input Voltage | 120V |
| Input Power | 0 W |
| Input Frequency | 50/60 Hz |
| Input Connections | NEMA 5-15P |
| Maximum Line Current per phase | 0.0 A |
| Cord Length | 1.83 meters |
| Maximum Input Current | 0 A |

Surge Protection and Filtering

| | |
|---|--|
| Surge energy rating | 2770 joules |
| EP Joule Rating | 2525 joules |
| EMI/RFI Noise rejection (100 kHz to 10 MHz) | 70.0 dB |
| Peak Current Common Mode | 0.0 kA |
| NM Surge Response Time (ns) | 0.0 ns |
| Data Line Protection | Cable modem / Video protection , RJ-11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines) |

| | |
|---------------------------------------|-----|
| Data Lines Protected(multi-line only) | 1-4 |
| Let Through Voltage Rating | 400 |

Physical

| | |
|--|--------------------|
| Net Weight | 0.92 kg |
| Maximum Height | 32.0 mm |
| Maximum Width | 89.0 mm |
| Maximum Depth | 330.0 mm |
| Shipping Weight | 1.11 kg |
| Shipping Height | 60.0 mm |
| Shipping Width | 142.0 mm |
| Shipping Depth | 360.0 mm |
| Master Carton Units | 6.0 |
| Master Carton Dimensions (Length x Width x Height) | 15 x 8 x 12 inches |
| Master Carton Weight | 7.5 kg |
| SCC Codes | 1073130424904 4 |
| Color | Black |
| Units per Pallet | 0.0 |

Environmental

| | |
|-----------------------------|----------------|
| Operating Environment | 0 - 45 °C |
| Operating Relative Humidity | 0 - 95 % |
| Operating Elevation | 0-3000 meters |
| Storage Temperature | -15 - 45 °C |
| Storage Relative Humidity | 0 - 95 % |
| Storage Elevation | 0-15000 meters |

Conformance

| | |
|-----------------------------|-------------------------|
| Approvals | CSA , UL 1363 , UL 1449 |
| Standard warranty | Lifetime |
| Equipment protection policy | Lifetime : \$150000 |