

Product datasheet

Specifications



APC Smart-UPS On-Line,
2200VA, Tower, 230V, 8x C13+2x
C19 IEC outlets, SmartSlot,
Extended runtime, W/O rail kit

SRT2200XLI

Overview


| | |
|--------------|---|
| Presentation | High density, double-conversion on-line power protection with scalable runtime. |
| Lead time | Usually in Stock |

Main

| | |
|---------------------------|--|
| Main Input Voltage | 230 V |
| Product or component type | Uninterruptible power supply (UPS) |
| Other Input Voltage | 220 V 240 V |
| Main Output Voltage | 230 V |
| Other Output Voltage | 220 V 240 V |
| Rated power in W | 1980 W |
| Rated power in VA | 2200 VA |
| Input Connection Type | BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P |
| output connection type | 8 IEC 60320 C13 2 IEC Jumpers 2 IEC 60320 C19 |
| Cable length | 2.4 m |
| Number of cables | 1 |
| Provided equipment | CD with software Country-specific detachable power cord Documentation CD Installation guide Removable support feet USB cable Warranty card |
| Range of product | Smart-UPS On-Line |

Batteries & Runtime

| | |
|--------------------------------|---------------------------------------|
| Run Time | View Runtime Graph |
| Efficiency | View Efficiency Graph |
| Battery type | Lead-acid battery |
| Number of battery filled slots | 1 |
| Number of battery free slots | 0 |
| Battery recharge time | 3 h |

| | |
|--|---|
| Number of battery replacement quantity | 1 |
| Battery voltage | 72 V |
| Battery charger power | 122 W rated |
| Battery life | 3...5 year(s) |
| Replacement battery | APCRBC141  |
| Extended runtime | 1 |

General

| | |
|-------------------------------------|--------------------------|
| UPS type | Double conversion online |
| product web sub-family | High density |
| Number of power module | 1400 |
| Number of power module free slots | 0 |
| Number of power module filled slots | 0 |
| Redundant | No |

Physical

| | |
|---------------------|-----------------------|
| Colour | Black |
| Height | 43.2 cm |
| Width | 8.5 cm |
| Depth | 58.4 cm |
| Net weight | 25 kg |
| Mounting location | Front |
| Mounting preference | Lower |
| Mounting mode | Rack-mounted with kit |
| Two post mountable | 0 |
| USB compatible | Yes |
| Mounting position | Vertical |

Input

| | |
|----------------------|------------------------------------|
| Network frequency | 40...70 Hz auto-sensing |
| Input voltage limits | 100...275 V adjustable (half load) |

Output

| | |
|----------------------------------|--|
| Maximum configurable power in VA | 2200 VA |
| Maximum configurable power in W | 1980 W |
| Output frequency | 50/60 Hz +/- 3 Hz sync to mains |
| Wave type | Sine wave |
| Harmonic distortion | Less than 2 % |
| Crest factor | 3 : 1 |
| Bypass type | Internal bypass (automatic and manual) |
| Additional information | Configurable for 220 : 230 or 240 nominal output voltage |

Conformance

| | |
|------------------------|--|
| Product certifications | CE EAC RCM VDE UK PSTI |
| Marking | CE Mark |
| Standards | EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018 |

Environmental

| | |
|---------------------------------------|-----------------------------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % non-condensing |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -15...45 °C |
| Storage Relative Humidity | 0...95 % non-condensing |
| Storage altitude | 0.0000000000...15240.0000000000 m |
| Acoustic level | 55 dBA |
| Heat dissipation | 703 Btu/h |
| IP degree of protection | IP20 |

Communications & Management

| | |
|---------------------|--|
| Free slots | 1 |
| Alarm | Audible and visible alarms : prioritized by severity |
| Emergency power off | Yes |

Surge Protection and Filtering

| | |
|-------------------|-------|
| Surge energy rate | 340 J |
|-------------------|-------|

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 24.6 cm |
| Package 1 Width | 81 cm |
| Package 1 Length | 59.9 cm |
| Package 1 Weight | 30.84 kg |

Logistical informations

| | |
|-------------------|----|
| Country of origin | PH |
|-------------------|----|

Contractual warranty

| | |
|----------|---|
| Warranty | 3 years repair or replace (excluding battery) and 2 years for battery |
|----------|---|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)