

C24G1 24 inch (59.9 cm) LCD MONITOR



Flicker Free

AOC Flicker-Free Technology utilises a DC (Direct Current) backlight panel, reducing flickering light levels. With eye strain and fatigue absolutely minimized, feel free to enjoy those long, intense

gaming sessions in comfort!



ultimate battle station.

FreeSync

Whatever your setup, achieve the highest framerate and smoothest display possible via AMD Free-Sync Technology. Whether you're dashing through explosions or screeching around rain

Minimal bezel distraction for the ultimate

slicked bends, wave goodbye to screen tearing and lag – and leave your opponents in your smoothly rendered dust.

Expand your view with multiple monitor set-up. The narrow border

and frameless design offer the minimal bezel distraction for the



144Hz Refresh Rate

Equip yourself with twice the frame rate of other monitors and say goodbye to image stuttering and blurry motion. With a 144Hz refresh rate every frame is rendered sharply and in smooth succession, so you can line up your shots accurately and appreciate high speed races in all their glory.

G1 Video marketing

Marketing video for G1 series



battle station

 Curved design wraps around you putting you at the center of the action and provides an immersive gaming experience.

Screen Details

Color	Black
Resolution	1920x1080 PX
Refresh rate	144Hz
Response time	1 ms
Panel	VA
Backlight	WLED
sRGB Coverage (%)	96
flickerfree	J
Aspect ratio	16:9
Brightness (typical)	250 cd/m ²
Contrast (dynamic)	80M:1
Contrast (static)	3000:1
Pixel Pitch (H) (V)	0.27156
Diagonal (inch)	24 inch
Active Screen Area (HxW)	521.39 x 293.28 mm
Viewing angle (CR10)	178/178 ^º
Curvature Radius	1500 mm
Display Colours	16.7 Million
Weight without stand	2.946 kg
Adobe RGB Coverage (%)	75
OSD languages	EN, FR , ES, PT, DE, IT, NL, SE, FI, PL ,CZ, RU, KR, CN (T), CN (S), JP
low_blue_light	✓
Connections	
Signal Input	VGA, DisplayPort 1.2 x 1, HDMI

olgha input	1.4 x 2
Audio output	Headphone out (3,5mm)

What's in the box

HDMI cable (1,8 m), Displayport Cable (1,8 m), Power Cable C13 (1,8 m), $\,$

Sustainability

Environmental and energy: RoHS, Lead-free, Mercury Free

Recyclable packaging material: 100 %

Era	onom	nics
L'9'	Shon	103

Swivel-34 ~ +34 °Tilt-4 ~ +21.5 °Height Adjust Amount130mmRemovable Stand~Vesa Wallmount100x100Power detailsExternalPower details00 - 240V 50/60HzPowersource100 - 240V 50/60HzPower ConsumptionOn 20 watt, Off 0.5 watt Standby 0.5 watt,Pinensions512.8x536.9x244.9 mmProduct Dimensions (incl base)512.8x536.9x244.9 mmProduct Dimensions (excl base)322.7x*536.9x66.6 mmReader of the standby 0.5 watt,741x180x408 mmNet Weight (excl package)6.513 KgWarrantySi YearsWarrantyPeriod3 YearsEAN4038986146494MTBF50.000 hours	Ergonomics	
Height Adjust Amount130mmRemovable Stand•Vesa Wallmount100x100Power detailsExternalPowersupplyExternalPowersource100 - 240V 50/60HzPower ConsumptionOn 20 watt, Off 0.5 watt Standby 0.5 watt,Dimensions512.8x536.9x244.9 mmProduct Dimensions (incl base)512.8x536.9x244.9 mmProduct Dimensions (excl base)322.7x*536.9x66.6 mmCartonDimensions<4461 Kg	Swivel	-34 ~ +34 °
Removable Stand·Vesa Wallmount100x100Power detailsExternalPowersource100 - 240V 50/60HzPower ConsumptionOn 20 watt, Off 0.5 watt Standby 0.5 watt,DimensionsS12.8x536.9x244.9 mmProduct Dimensions (incl base)512.8x536.9x244.9 mmProduct Dimensions (excl base)322.7x*536.9x66.6 mmCartonDimensions (excl base)322.7x*536.9x66.6 mmRet Weight (excl package)4.461 KgGross Weight (incl package)6.513 KgWarrantyS128x536.9x66.6 mmWarrantyPeriod3 YearsEAN4038986146494MTBF50.000 hours	Tilt	-4 ~ +21.5 °
Vesa Wallmount100x100Power detailsExternalPowersupplyExternalPowersource100 - 240V 50/60HzPower ConsumptionOn 20 watt, Off 0.5 watt Standby 0.5 watt,DimensionsS12.8x536.9x244.9 mmProduct Dimensions (incl base)512.8x536.9x244.9 mmProduct Dimensions (excl base)322.7x*536.9x66.6 mmCartonDimensions (excl base)322.7x*536.9x66.6 mmReweight (excl package)4.461 KgGross Weight (incl package)6.513 KgWarranty3 YearsEAN4038986146494MTBF50.000 hours	Height Adjust Amount	130mm
Power detailsPowersupplyExternalPowersource100 - 240V 50/60HzPower ConsumptionOn 20 watt, Off 0.5 watt Standby 0.5 watt,DimensionsStandby 0.5 watt,Product Dimensions (incl base)512.8x536.9x244.9 mmProduct Dimensions (excl base)322.7x*536.9x66.6 mmCartonDimensions741x180x408 mmNet Weight (excl package)4.461 KgGross Weight (incl package)6.513 KgWarrantyYearsEAN4038986146494MTBF50.000 hours	Removable Stand	1
PowersupplyExternalPowersource100 - 240V 50/60HzPower ConsumptionOn 20 watt, Off 0.5 watt Standby 0.5 watt,DimensionsStandby 0.5 watt,Product Dimensions (incl base)512.8x536.9x244.9 mmProduct Dimensions (excl base)322.7x*536.9x66.6 mmCartonDimensions4.461 KgRet Weight (excl package)6.513 KgWarrantySame Standby 0.5 wattWarrantyPeriod3 YearsEAN4038986146494MTBF50.000 hours	Vesa Wallmount	100x100
Powersource100 - 240V 50/60HzPower ConsumptionOn 20 watt, Off 0.5 watt Standby 0.5 watt,DimensionsStandby 0.5 watt,Product Dimensions (incl base)512.8x536.9x244.9 mmProduct Dimensions (excl base)322.7x*536.9x66.6 mmCartonDimensions741x180x408 mmNet Weight (excl package)4.461 KgGross Weight (incl package)6.513 KgWarrantyYearsEAN4038986146494MTBF50.000 hours	Power details	
Power ConsumptionOn 20 watt, Off 0.5 watt Standby 0.5 watt,DimensionsProduct Dimensions (incl base)512.8x536.9x244.9 mmProduct Dimensions (excl base)322.7x*536.9x66.6 mmCartonDimensions741x180x408 mmNet Weight (excl package)4.461 KgGross Weight (incl package)6.513 KgWarrantyYarrantyWarrantyPeriod3 YearsEAN4038986146494MTBF50.000 hours	Powersupply	External
Standby 0.5 watt,DimensionsProduct Dimensions (incl base)512.8x536.9x244.9 mmProduct Dimensions (excl base)322.7x*536.9x66.6 mmCartonDimensions (excl base)741x180x408 mmCartonDimensions4.461 KgGross Weight (excl package)6.513 KgWarranty3 YearsEAN3 YearsMTBF50.000 hours	Powersource	100 - 240V 50/60Hz
Product Dimensions (incl base)512.8x536.9x244.9 mmProduct Dimensions (excl base)322.7x*536.9x66.6 mmCartonDimensions741x180x408 mmNet Weight (excl package)4.461 KgGross Weight (incl package)6.513 KgWarranty3 YearsEAN4038986146494MTBF50.000 hours	Power Consumption	
Product Dimensions (excl base)322.7x*536.9x66.6 mmCartonDimensions741x180x408 mmNet Weight (excl package)4.461 KgGross Weight (incl package)6.513 KgWarranty3 YearsEAN4038986146494MTBF50.000 hours	Dimensions	
base) CartonDimensions 741x180x408 mm Net Weight (excl package) 4.461 Kg Gross Weight (incl package) 6.513 Kg Warranty WarrantyPeriod 3 Years EAN 4038986146494 MTBF 50.000 hours	Product Dimensions (incl base)	512.8x536.9x244.9 mm
Net Weight (excl package)4.461 KgGross Weight (incl package)6.513 KgWarranty3 YearsEAN4038986146494MTBF50.000 hours		322.7x*536.9x66.6 mm
Gross Weight (incl package)6.513 KgWarrantyWarrantyPeriod3 YearsEAN4038986146494MTBF50.000 hours	CartonDimensions	741x180x408 mm
WarrantyWarrantyPeriod3 YearsEAN4038986146494MTBF50.000 hours	Net Weight (excl package)	4.461 Kg
WarrantyPeriod3 YearsEAN4038986146494MTBF50.000 hours	Gross Weight (incl package)	6.513 Kg
EAN 4038986146494 MTBF 50.000 hours	Warranty	
MTBF 50.000 hours	WarrantyPeriod	3 Years
	EAN	4038986146494
Populations	MTBF	50.000 hours
negulations	Regulations	

TUV-Bauart 1, ISO 9241-307 class I 1,