


Overview

HP Z6 G5 Workstation



Front View

1. Integrated Front Handle
2. Power Button
3. HDD Activity LED
4. Headphone/microphone combo
5. Front I/O Premium²:
2 SuperSpeed USB Type-C™ 20 Gbps signaling rate (USB Power Delivery 3.0),
2 SuperSpeed USB Type-A 5 Gbps signaling rate [left-most Type-A port supports BC1.2 (Battery Charging)]

Front I/O Entry:
4 SuperSpeed USB Type-A 5 Gbps signaling rate [left-most Type-A ports supports BC1.2 (Battery Charging)]
6. SD Card Reader
7. 2x External 5.25" bay¹
8. 9.5mm Optical Drive Bay

¹Only 1 external 5.25" drive configurable from factory

²Premium Front IO is shown on photography


Overview



Internal View

1. 1 Intel® Xeon® Processor (Sapphire Rapids)
2. 8 DIMM slots for DDR5 ECC Memory
3.
 - Slot 1: PCIe x16 Gen5
 - Slot 2: PCIe x4 Gen4
 - Slot 3: PCIe x4 Gen4
 - Slot 4: PCIe x16 Gen4
 - Slot 5: PCIe x16 Gen4
 - Slot 6: PCIe x16 Gen3
4. 2 PCIe x4 Gen4 configurable with 2x M.2 SSDs
5. 5 SATA ports
6. 3 Internal USB Ports. 1 single USB2.0 port, 1 dual USB2.0 port, 1 USB3.0 port (for the SD card reader).
7. 2 Internal 3.5" bays
8. 2 External 5.25" bays and Slimline Optical Drive
9. 2 Internal NVMe connector to front removable M.2 carrier

Overview



Rear View

- | | |
|---|--|
| 1. Choice of 775W, 1125W or 1450W, 90% Efficient Power Supplies | 5. 1 RJ-45 integrated LAN port (1 GbE AMT) |
| 2. Rear Power Button | 6. 6 SuperSpeed USB Type-A 5 Gbps signaling rate |
| 3. Audio in/out | 7. 2 10GbE LAN ports (optional) |
| 4. Flex I/O Module (optional) | 8. External Antenna (optional) |
| | 9. Integrated Rear Handle |

Form Factor Tower

Operating Systems

Preinstalled:

- Windows 11 Pro for Workstations²
- Windows 11 Pro for Workstations (preinstalled with Windows 10 Pro for Workstations Downgrade)^{2,3}
- Ubuntu 22.04 LTS⁴
- HP Linux[®]-ready (minimal OS ready for customer OS installation)⁵

License Only:

- Red Hat[®] Enterprise Linux[®] Desktop Workstation (includes paper license with 1 year support; no preinstalled OS)⁶

Supported:

- Windows 11, version 22H2, 21H2²
- Windows 10, version 22H2, 21H2²
- Red Hat[®] Enterprise Linux[®] Workstation 8 & 9⁶

Overview

- SUSE Linux® Enterprise Desktop 15⁶
- Ubuntu 20.04 & 22.04 LTS⁵

Web-supported only:

- Windows 11 Enterprise^{2,1}
- Windows 10 Enterprise^{2,1}

¹ Windows Enterprise sold separately and requires that customer have an enterprise license from Microsoft.

² Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.

³This system is preinstalled with Windows 10 Pro software and also comes with a license for Windows 11 Pro software and provision for recovery software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

⁴ Not all features are available in all editions or versions of Ubuntu. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS to take full advantage of Ubuntu functionality. Ubuntu may be automatically updated. ISP fees may apply and additional requirements may apply over time for updates.

⁵A certified preloaded version of Ubuntu® 20.04 LTS is available from HP for this platform. Not all features are available in all editions or versions of Ubuntu. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS to take full advantage of Ubuntu functionality. Ubuntu may be automatically updated. ISP fees may apply, and additional requirements may apply over time for upgrades.

⁶For detailed Linux® OS/hardware support information, see: http://www.hp.com/support/linux_hardware_matrix

NOTE: Your product does not support Windows 8 or Windows 7. In accordance with Microsoft’s support policy, HP does not support the Windows® 8 or Windows 7 operating system on products configured with Intel® and AMD® 7th generation and forward processors or provide any Windows® 8 or Windows 7 drivers on <http://www.support.hp.com>. A full list of HP products and the Windows 10 versions tested is available on the HP support website. <https://support.hp.com/us-en/document/c05195282>

Processors

| Name ¹ | Cores | Threads | Frequency (GHz) | | | Cache (MB) | Max Memory Speed (MT/s) | | TDP (W) |
|-----------------------|-------|---------|------------------|---|--|------------|-------------------------|--------------------|---------|
| | | | Base Clock Speed | Intel® Turbo Boost Max Single-Core Frequency ² | Intel® Turbo Boost Max Tech 3.0 Frequency ² | | 1 DIMM per Channel | 2 DIMM per Channel | |
| Intel® Xeon® W9-3475X | 36 | 72 | 2.2 | 4.6 | 4.8 | 82.5 | 4800 | 4400 | 300 |
| Intel® Xeon® W7-3465X | 28 | 56 | 2.5 | 4.6 | 4.8 | 75 | 4800 | 4400 | 300 |
| Intel® Xeon® W7-3455 | 24 | 48 | 2.5 | 4.6 | 4.8 | 67.5 | 4800 | 4400 | 270 |
| Intel® Xeon® W7-3445 | 20 | 40 | 2.6 | 4.6 | 4.8 | 52.5 | 4800 | 4400 | 270 |
| Intel® Xeon® W5-3435X | 16 | 32 | 3.1 | 4.5 | 4.7 | 45 | 4800 | 4400 | 270 |

Overview

| | | | | | | | | | |
|----------------------|----|----|-----|-----|-----|----|------|------|-----|
| Intel® Xeon® W5-3433 | 16 | 32 | 2.0 | 4.0 | 4.2 | 45 | 4400 | 4400 | 220 |
| Intel® Xeon® W5-3425 | 12 | 24 | 3.2 | 4.4 | 4.6 | 30 | 4800 | 4400 | 270 |
| Intel® Xeon® W5-3423 | 12 | 24 | 2.0 | 4.0 | 4.2 | 30 | 4400 | 4400 | 220 |

Notes:

- Xeon W-3400 processors all feature Intel® vPro® Technology³
- Xeon W-3400 processors all support Hyper-Threading
- Xeon W-3400 processors do not offer integrated graphics

¹ Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

² Intel Turbo Boost Max (ITBM) performance varies depending on hardware, software and overall system configuration. See <http://www.intel.com/technology/turboboost> for more information.

³ Intel vPro® requires Windows 10 Pro 64 bit or higher, a vPro supported processor, vPro enabled chipset, vPro enabled wired LAN and/or Wi-Fi 6E WLAN and TPM 2.0. Some functionality requires additional 3rd party software in order to run. Features of vPro® Essentials and Enterprise vary. See <http://intel.com/vpro>

Overview

| | |
|---|--|
| Color | Black |
| Convertibility | No |
| Expansion Slots (see system board section for more details) | <ul style="list-style-type: none"> •Slot 1: PCIe x16 Gen5 •Slot 2: PCIe x4 Gen4 •Slot 3: PCIe x4 Gen4 •Slot 4: PCIe x16 Gen4 •Slot 5: PCIe x16 Gen4 •Slot 6: PCIe x16 Gen3 |
| Expansion Bays (see storage section for more details) | 2 internal 3.5" bays (both bays include acoustic dampening rail assemblies) 2 external 5.25" bays (175mm depth limit) 1 dedicated 9.5mm slim optical disk drive bay |
| Front I/O | Front I/O Premium: 2 SuperSpeed USB Type-C™ 20 Gbps signaling rate (USB Power Delivery 3.0), 2 SuperSpeed USB Type-A 5 Gbps signaling rate, 1 headphone/microphone combo, SD card reader (optional). [left-most Type-A ports supports BC1.2 (Battery Charging)] Front I/O Entry: 4 SuperSpeed USB Type-A 5 Gbps signaling rate, 1 headphone/microphone combo, SD card reader (optional). [left-most Type-A ports supports BC1.2 (Battery Charging)] |
| Internal I/O [5] | 3 Internal USB ports and 4 SATA ports. |
| Rear I/O | Audio in/out, 6 SuperSpeed USB Type-A 5 Gbps signaling rate, 1 RJ-45 integrated LAN ports (1 GbE AMT) |
| Optional I/O | 2 10GbE LAN ports Flex I/O Module (Serial Port v3, Dual USB-A 3.2 Gen1, USB-C 3.2 Gen2, 10GbE single port, 2.5GbE LAN single port, 1 GbE single port, 1GbE Fiber single port LC, WiFi6 + BT5.2 WLAN w/ INTAnt) External Antenna |
| On-board RAID Support | SATA RAID 0 Striped Array SATA RAID 1 Mirrored Array SATA RAID 10 Striped/Mirrored SATA RAID 5 Parity Array |
| Chassis Dimensions (H x W x D) | Footprint: H: 17.5" [444.5 mm] W: 6.65" [169 mm] D: 18.3" [465 mm] Maximum: H: 17.5" [444.5 mm] W: 6.65" [169 mm] D: 18.82" [478 mm] |
| Packaged Dimensions | H: 24.0" [610mm] W: 12.3" [313mm] D: 23.3" [593mm] |
| Palletization Profile | 6 units x 3 layers = 18 units per pallet 1200x1000x1836mm (pallet included) |
| Rack Dimensions | 4U |
| Weight | Exact weights depend upon configuration (System weight only). Minimum: 12.8 kg (28.2 lbs.) Typical: 14.1 kg (31.1 lbs.) Maximum: 24.3 kg (53.6 lbs.) |
| Temperature | Operating: 5° to 40°C (40° to 104°F) ¹ Non-operating: -40° to 60°C (-40° to 140°F) |
| | ¹ 40°C has been validated for configs up to a 220W CPU, 2x NVIDIA® RTX A4000 graphics cards, 8x64GB RAM, 2x 2TB M.2 storage, 2x 2TB HDD storage, and 1125W PSU |
| Humidity | Operating: Operating: 10% to 85% RH, non-condensing, 35° C maximum wet bulb |

Overview

| | |
|---|---|
| | Non-operating: 10% to 90%, non-condensing, 35° C maximum wet bulb |
| Maximum Altitude (non-pressurized)⁶ | Operating: 3,048m (10,000ft) Non-operating: 9,144m (30,000ft) NOTE: Above 1524 m (5,000 feet) altitude, maximum operating temperature is reduced by 1° C (1.8° F) per 305 m (1,000 feet) elevation increase |
| Power Supply | Choice of 90% Efficient Power Supplies: <ul style="list-style-type: none">• 1450W• 1125W• 775W <p>NOTE: not all configurations are supported on all power supplies. Configuration support depends on total system power budget and having sufficient number or type of PCIe supplemental power connectors. Confirm power supply and configuration support using configurator on hp.com.</p> <ul style="list-style-type: none">• 1450W supports up to 900W of auxiliary graphics power (dependent on system configuration)• 1125W supports up to 600W of auxiliary graphics power (dependent on system configuration)• 775W supports up to 230W of auxiliary graphics power (dependent on system configuration) <p>NOTE: updating graphics after purchase may require additional power distribution cables and/or auxiliary graphics adapters to support the new graphics configuration.</p> |
| Workstation ISV Certifications | See the latest list of certifications at http://www.hp.com/united-states/campaigns/workstations/partnerships.html |
| Chipset | Intel® W790 chipset |
| Memory | 8 DIMM slots, supporting up to 1TB, DDR5 4800 MT/s speed depending on the system configuration |

Supported Components

Processors

| | Factory Configured | Option Kit | Option Kit Part Number | Support Notes |
|---------------------------------------|--------------------|------------|------------------------|---------------|
| Intel® Xeon® W-3400 processors | | | | |
| Intel® Xeon® W9-3475X | Y | N | | |
| Intel® Xeon® W7-3465X | Y | N | | |
| Intel® Xeon® W7-3455 | Y | N | | |
| Intel® Xeon® W7-3445 | Y | N | | |
| Intel® Xeon® W5-3435X | Y | N | | |
| Intel® Xeon® W5-3433 | Y | N | | |
| Intel® Xeon® W5-3425 | Y | N | | |
| Intel® Xeon® W5-3423 | Y | N | | |

SATA Hard Drives

| | Factory Configured | Option Kit | Option Kit Part Number |
|---|--------------------|------------|------------------------|
| 1TB 7200RPM SATA 3.5in Enterprise HDD ⁵ | Y | Y | W0R10AA |
| 2TB 7200RPM SATA 3.5in Enterprise HDD ⁵ | Y | Y | Z2Z74AA |
| 4TB 7200RPM SATA 3.5in Enterprise HDD ⁵ | Y | Y | K4T76AA/AT |
| 8TB 7200RPM SATA 3.5in Enterprise HDD ⁵ | Y | Y | Z2Z73AA |
| 12TB 7200RPM SATA-6G 3.5in Enterprise HDD ⁵ | Y | Y | 5S461AA |
| 1TB 7200RPM SATA 3.5" Enterprise HDD (not-made-in-China) | Y | N | |
| 2TB 7200RPM SATA 3.5in Enterprise HDD (not-made-in-China) | Y | N | |

PCIe Solid State Drives

| | Factory Configured | Option Kit | Option Kit Part Number |
|--|--------------------|------------|------------------------|
| Z Turbo 512GB 2280 PCIe-4x4 TLC SSD | Y | Y | 38T80AA |
| Z Turbo 512GB 2280 PCIe-4x4 SED OPAL2 TLC M.2 SSD | Y | Y | 38T81AA |
| Z Turbo 512GB 2280 PCIe-4x4 TLC SSD (not-made-in-China) | Y | N | |
| Z Turbo 512GB 2280 PCIe-4x4 TLC Z4/Z6 Kit SSD | Y | Y | 56Q73AA |
| Z Turbo 512GB 2280 PCIe-4x4 SED OPAL2 TLC M.2 Z4/Z6 Kit SSD | N | Y | 56Q74AA |
| Z Turbo 1TB 2280 PCIe-4x4 TLC SSD | Y | Y | 38T77AA |
| Z Turbo 1TB 2280 PCIe-4x4 SED OPAL2 TLC M.2 SSD | Y | Y | 38T76AA |
| Z Turbo 1TB 2280 PCIe-4x4 TLC SSD (not-made-in-China) | Y | N | |
| Z Turbo 1TB 2280 PCIe-4x4 TLC Z4/Z6 Kit SSD | Y | Y | 56Q75AA |
| Z Turbo 1TB 2280 PCIe-4x4 SED OPAL2 TLC M.2 Z4/Z6 Kit SSD | N | Y | 5Z7E7AA |
| Z Turbo 2TB 2280 PCIe-4x4 TLC SSD | Y | Y | 38T75AA |
| Z Turbo 2TB 2280 PCIe-4x4 SED OPAL2 TLC M.2 SSD | Y | Y | 38T79AA |
| Z Turbo 2TB 2280 PCIe-4x4 SED OPAL2 TLC M.2 Z4/Z6 Kit SSD | N | Y | 56Q77AA |
| Z Turbo 4TB 2280 PCIe-4x4 TLC M.2 SSD ⁴ | Y | Y | 5S496AA/AT |
| Z Turbo 4TB 2280 PCIe-4x4 SED OPAL2 TLC M.2 SSD ⁴ | Y | Y | 5S497AA/AT |
| Z Turbo 4TB 2280 PCIe-4x4 SED OPAL2 TLC M.2 Z4/Z6 Kit SSD ⁴ | N | Y | 5S4A1AA |

HP Z Turbo Drive Dual Pro

Supported Components

| | | | |
|--|---|---|---------|
| HP Z Turbo Drive Dual Pro PCIe-4x4 NVMe Carrier ¹ | Y | Y | 56Q86AA |
| HP Z Turbo Drive Dual Pro 512GB TLC SSD | Y | N | |
| HP Z Turbo Drive Dual Pro 1TB TLC SSD | Y | N | |
| HP Z Turbo Drive Dual Pro 2TB TLC SSD | Y | N | |
| HP Z Turbo Drive Dual Pro 4TB TLC SSD ⁴ | Y | N | |
| Intel® Virtual RAID on CPU (Intel® VROC) for NVMe | | | |
| Intel VROC NVMe SSD Premium Ctlr Module ² | N | Y | 3FJ81AA |
| Intel VROC NVMe SSD Standard Ctlr Module ³ | N | Y | 3FJ80AA |

Note 1: Kit includes dual pro carrier and heatsink. Requires separate purchase of Z Turbo PCIe 4x4 M.2 SSD modules.

Note 2: Enables RAID 0, 1 & 10

Note 3: Enables RAID 0, 1 & 10 plus RAID 5 with write hole closure options

Note 4: Available in June 2023

NOTE: For internal bay install, HDD option kits require separate purchase of 73P26AA HP Z6 HDD Cable Kit. For external bay install, HDD options kits require separate purchase of 73P26AA HP Z6 HDD Cable Kit & NQ099AA HP Optical Bay HDD Mounting Bracket.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| Graphics | | Factory Configured | Option Kit | Option Kit Part Number | Supported # of cards |
|--------------------------------|--|--------------------|------------|------------------------|----------------------|
| Graphics Cable Adapters | HP DisplayPort To VGA Adapter | N | Y | AS615AA/AT | |
| | HP DisplayPort To VGA Adapter | N | Y | F7W97AA | |
| | HP DisplayPort to HDMI Adapter | Y | Y | 2JA63AA | |
| | HP (Bulk 12) miniDP-to-DP Adapter Cables | N | Y | 2KW87A6 | |
| | HP Single miniDP-to-DP Adapter Cable | Y | Y | 2MY05AA | |
| | HP miniDP-to-DP Adapter (2-pack) | Y | N | | |
| | HP miniDP-to-DP Adapter (4-pack) | Y | N | | |
| | HP miniDP-to-DP Adapter (8-pack) | Y | N | | |
| | HP DisplayPort To DVI Adapter (Bulk 90) | N | Y | FH973A6 | |
| | NVIDIA NVLink 3-Slot Bridge | Y | Y | 340L3AA | |
| | NVIDIA 3D Stereo Bracket | N | Y | K0A25AA | |
| | HP Graphics Power Cable CPU-8p to CPU-8p ⁴ | N | Y | 6J6H7AA | |
| | HP Graphics Power Cable CPU-8p to x2 PCIe 8p(6+2) ⁴ | N | Y | 6J6H8AA | |
| Ultra High-End Graphics | NVIDIA® RTX 6000 Ada 48GB ^{1,3} | Y | Y | 79C23AA/AT | 3 |
| | NVIDIA® RTX A6000 48GB ^{1,3} | Y | Y | 2S6U3AA/AT | 3 |
| | AMD Radeon Pro W6800 32GB ^{1,3} | Y | Y | 340K7AA | 2 |
| | NVIDIA® RTX A5000 24GB ¹ | Y | Y | 20X23AA/AT | 3 |
| High-End Graphics | NVIDIA® Quadro® Sync II | N | Y | 1WT20AA | |
| | NVIDIA® RTX A4500 20GB ¹ | Y | Y | 5S458AA/AT | 3 |
| Midrange Graphics | NVIDIA® RTX A4000 16GB ^{1,*} | Y | Y | 20X24AA/AT | 3 |
| | NVIDIA® RTX A2000 12GB ¹ | Y | Y | 5Z7D9AA/AT | 3 |

Supported Components

| Component | Factory Configured | Option Kit | Option Kit Part Number | Support Notes |
|---|--------------------|------------|------------------------|---------------|
| AMD Radeon RX 6700XT 12GB | Y | N | | 1 |
| NVIDIA® T1000 8GB ² | Y | Y | 5Z7D8AA/AT | 3 |
| AMD® Radeon™ Pro W6600 8GB ¹ | Y | Y | 340K5AA | 3 |
| Entry Graphics NVIDIA® T400 4GB ² | Y | Y | 5Z7E0AA/AT | 3 |
| AMD® Radeon™ RX 6400 4GB | Y | Y | 6Q3U4AA/AT | 1 |
| NVIDIA T1000 4GB ² | Y | Y | 20X22AA/AT | 3 |
| Intel Arc Pro A40 6GB ⁵ | Y | Y | 6E3Y8AA | 1 |

*Only supported with 1125W and 1450W PSUs

Note 1: Single, dual, or triple graphics configurations require the HP Z6 Fan and Front Card Guide. If configured as an after-market option, a separate purchase of the HP Z6 Fan and Front Card Guide 56Q80AA is required. If factory configured, the fan and front card guide is included.

Note 2: Dual T1000 or triple T1000 or T400 graphics configurations require the HP Z6 Fan and Front Card Guide. If configured as an after-market option, a separate purchase of the HP Z6 Fan and Front Card Guide 56Q80AA is required. If factory configured, the fan and front card guide is included.

Note 3: Dual A6000 or W6800 graphics or triple graphics configuration requires the HP Z6 PCIe Retainer with Fans. If configured as an after-market option, a separate purchase of the HP Z6 PCIe Retainer with Fans 56Q85AA is required. If factory configured, the PCIe retainer with fans is included.

Note 4: Required for select graphics configurations.

Note 5: Available in June 2023

Memory

| Memory Configuration | Factory Configured | Option Kit | Option Kit Part Number | Support Notes |
|---|--------------------|------------|------------------------|---------------|
| 16GB (1x16GB) DDR5 4800 DIMM ECC REG Memory (not-made-in-China) | Y | N | | |
| 32GB (2x16GB) DDR5 4800 DIMM ECC REG Memory | Y | N | | |
| 32GB (2x16GB) DDR5 4800 DIMM ECC REG Memory (not-made-in-China) | Y | N | | |
| 64GB (4x16GB) DDR5 4800 DIMM ECC REG Memory | Y | N | | |
| 64GB (4x16GB) DDR5 4800 DIMM ECC REG Memory (not-made-in-China) | Y | N | | |
| 64GB (2x32GB) DDR5 4800 DIMM ECC REG Memory | Y | N | | |
| 128GB (8x16GB) DDR5 4800 DIMM ECC REG Memory | Y | N | | |
| 128GB (4x32GB) DDR5 4800 DIMM ECC REG Memory | Y | N | | |
| 256GB (8x32GB) DDR5 4800 DIMM ECC REG Memory | Y | N | | |
| 256GB (4x64GB) DDR5 4800 DIMM ECC REG Memory | Y | N | | |
| 256GB (2x128GB) DDR5 4800 DIMM ECC REG Memory | Y | N | | 1,2 |
| 512GB (8x64GB) DDR5 4800 DIMM ECC REG Memory | Y | N | | |
| 512GB (4x128GB) DDR5 4800 DIMM ECC REG Memory | Y | N | | 1,2 |
| 1TB (8x128GB) DDR5 4800 DIMM ECC REG Memory | Y | N | | 1,2 |
| After Market Options | | | | |
| 16GB (1x16GB) DDR5 4800 DIMM ECC REG Memory | Y | Y | 340K1AA | |
| 32GB DDR5 (1x32GB) 4800 DIMM ECC REG Memory | N | Y | 340K2AA | |
| 64GB DDR5 (1x64GB) 4800 DIMM ECC REG Memory | N | Y | 340K3AA | |
| 128GB (1x128GB) DDR5 4800 DIMM ECC REG Memory | N | Y | 69D46AA | 1,2 |

Note 1: This memory configuration requires the 1125W/1450W PSU

Note 2: Available in June 2023

Supported Components

NOTE: When configuring the system with 2 DIMMS per channel (DPC), max memory speed will decrease from 4800MHz to 4400MHz.

| Multimedia and Audio Devices | Factory Configured | Option Kit | Option Kit Part Number |
|---|--------------------|------------|------------------------|
| HyperX Cloud Mix Wireless Gaming Headset | N | Y | 4P5K9AA |
| HyperX Cloud Core Gaming Headset | N | Y | 4P4F2AA |
| HyperX Cloud Flight Wireless Gaming Headset | N | Y | 4P5L4AA |
| HyperX Cloud Stinger Core Gaming Headset | N | Y | 4P4F4AA |
| HyperX SoloCast - USB Microphone | N | Y | 4P5P8AA |
| Integrated Realtek ALC3205-CG Audio | Y | N | |

| Optical and Removable Storage | Factory Configured | Option Kit | Option Kit Part Number |
|---|--------------------|------------|------------------------|
| HP CRU QX448 Removable with 200mm Cable (Qty.2) Frame/Carrier ^{1,4} | Y | Y | 56R10AA |
| HP DX175 Removable HDD Frame/Carrier ^{2,4} | Y | Y | 1ZX71AA |
| HP DX175 Removable HDD Spare Carrier ^{2,4} | N | Y | 1ZX72AA |
| HP CRU Secure High Performance Storage Module with 2TB M.2 SSD ³ | Y | Y | 56Q87AA |
| HP CRU Secure High Performance Storage Module with 1TB M.2 SSD ³ | Y | Y | 56Q88AA |
| HP CRU Secure High Performance Storage Module with 512GB M.2 SSD ³ | Y | Y | 56Q89AA |
| HP 9.5mm Slim DVD-ROM Drive | Y | Y | K3R63AA |
| HP 9.5mm Slim BDXL Blu-Ray Writer Drive | Y | Y | K3R65AA |
| HP 9.5mm Slim SuperMulti DVD Writer | Y | Y | K3R64AA |

Note 1: Requires separate purchase of HP CRU Secure High Performance Storage (SHIPS) Module(s).

Note 2: Only supports 4TB or lower capacity HDDs.

Note 3: HP CRU SHIPS Module Kit contains select M.2 SSD for install into a factory configured or after market option front removable storage carrier (HP CRU QX448 Frame/Carrier).

Note 4: Planned to be available in June 2023

| Networking and Communications | Factory Configured | Option Kit | Option Kit Part Number |
|--|--------------------|------------|------------------------|
| NVIDIA Mellanox ConnectX-6 DX Dual Port 10/25GbE SFP28 NIC ¹ | Y | Y | 436M8AA |
| HP Dual Port 10GbE NIC G2 | Y | Y | 360K6AA |
| Intel X550 Dual Port 10GbE NIC | Y | Y | 1QL46AA |
| Allied Telesis AT-2911T/2-901 Dual Port 1GbE NIC | Y | Y | 6E3Y9AA/AT |
| Intel I225 Single Port 2.5GbE NIC | Y | Y | 406L9AA |
| AT-2914SX/LC-901 Single Port 1GbE NIC | Y | Y | 1C7Q2AA |
| Intel I350-T4 4-Port 1GbE NIC | N | Y | W8X25AA |
| HP Flex 10GbE Single Port | Y | Y | 56Q71AA |
| HP Flex 2.5GbE LAN Single Port | Y | Y | 169K0AA/AT |
| HP Flex 1GbE Fiber Single Port LC | Y | Y | 20J15AA |
| HP Flex 1GbE Single Port NIC | Y | N | |
| Intel® AX210 Wi-Fi 6E non-vPro + Bluetooth® 5.2 with External Antenna WLAN | Y | Y | 340L7AA |
| Intel® AX210 Wi-Fi 6 non-vPro + Bluetooth® 5.2 Flex Port NIC with | Y | N | |

Supported Components

Internal Antenna WLAN

Note1: 3rd party transceivers sold separately. You must have a transceiver installed to connect this card to a network.

| Racking and Physical Security | Factory Configured | Option Kit | Option Kit Part Number |
|---|--------------------|------------|------------------------|
| Z2 Mini/Z2 Tower/Z4/Z6 Depth Adjustable Fixed Rail Rack Kit | N | Y | 2A8Y5AA |

| Input Devices | Factory Configured | Option Kit | Option Kit Part Number |
|---|--------------------|------------|------------------------|
| HP 320K Wired Keyboard | Y | Y | 9SR37AA/ET/UT |
| HP 125 Wired Keyboard | Y | Y | 266C9AA/ET/UT |
| HP 975 USB+BT Dual-Mode Wireless Keyboard | N | Y | 3Z726AA/ET/UT |
| HP 455 Programmable Wireless Keyboard | N | Y | 4R177AA/ET/UT/A6 |
| HP Wired Desktop 320MK Mouse and Keyboard | N | Y | 9SR36AA/ET/UT |
| HP 655 Wireless Keyboard and Mouse Combo | N | Y | 4R009AA/ET/UT/A6 |
| HP Wired 320M Mouse | Y | Y | 9VA80AA/ET/UT |
| HP Creator 935 Black Wireless Mouse | N | Y | 1D0K8AA/ET/UT |
| HP 128 LSR Wired Mouse | Y | Y | 265D9AA/ET/UT |
| HP 125 Wired Mouse | N | Y | 265A9AA/ET/UT |
| HP Business Slim Smartcard Keyboard | Y | Y | Z9H48AA/AT |

NOTE: Keyboard and Mouse are optional or add on features.

| Other Hardware | Factory Configured | Option Kit | Option Kit Part Number |
|--|--------------------|------------|------------------------|
| HP Flex USB-C 3.2 Gen2 | Y | Y | 141K6AA/AT |
| HP Flex Dual USB-A 3.2 Gen1 | Y | Y | 141J8AA/AT |
| HP Flex Serial Port v3 | Y | Y | 13L56AA/AT |
| HP Dual Thunderbolt4 PCIe x4 Low Profile Card | Y | Y | 340L1AA |
| HP Type-C SuperSpeed USB 20Gbps Front IO v2 Premium Module | Y | Y | TBD |
| HP Internal Serial+PS/2 Port | Y | Y | 56Q78AA |
| HP USB 2.0 Type-A Port Adapter Kit ³ | Y | Y | 79C24AA |
| HP SD Card Reader Zx G4 | Y | Y | 2VK54AA |
| HP Z6 Fan and Front Card Guide Kit ⁵ | Y | Y | 56Q80AA |
| HP Z6 Memory Cooling Solution ⁴ | Y | Y | 56Q82AA |
| HP Z6 PCIe Retainer with Fans ⁵ | Y | Y | 56Q85AA |
| HP 2.5in to 3.5in HDD Adapter Kit | N | Y | J5T63AA |
| HP 2.5in HDD/SSD 2-in-1 Optical Bay Bracket | N | Y | K4T74AA |
| HP Z6 HDD Cable Kit ¹ | N | Y | 73P26AA |
| HP Optical Bay HDD Mounting Bracket ² | N | Y | NQ099AA |
| HP C13 1.83m Power Cord Kit (halogen-free) | Y | N | |

Supported Components

HP C13 1.83m Power Cord Kit Y Y 6Z1T9AA

Note 1: 73P26AA HP Z6 HDD Cable Kit is required as a separate purchase for HDD option kit install into an internal bay. For external bay install, a separate purchase of 73P26AA HP Z6 HDD Cable Kit & NQ099AA HP Optical Bay HDD Mounting Bracket is required.

Note 2: NQ099AA HP Optical Bay HDD Mounting Bracket is required as a separate purchase for HDD option kits into an external bay.

Note 3: The USB 2.0 Type-A Port Adapter Kit has a single USB 2.0 type A connector.

Note 4: HP Z6 Memory Cooling Solution 56Q82AA is required as a separate purchase for after-market memory configurations using 32GB Registered DIMMs or greater. If configured from the factory, configurations using 32GB Registered DIMMs or greater will include a memory cooling solution.

Note 5: HP Z6 Fan and Front Card Guide 56Q80AA and HP Z6 PCIe Retainer with Fans 56Q85AA are required for specific graphics configurations (see Graphics section).

Software

| | Factory Configured | Option Kit | Support Notes |
|---|--------------------|------------|---------------|
| HP Anyware | Y | N | |
| HP Performance Advisor | Y | N | 1 |
| HP PC Hardware Diagnostics UEFI (Windows OS only) | Y | N | 2 |
| HP PC Hardware Diagnostics Windows | Y | N | |
| HP Wolf Security | Y | N | 3 |
| HP Notifications | Y | N | |
| HP Desktop Support Utility | Y | N | |
| HP Documentation | Y | N | |
| myHP | Y | N | |
| HP Easy Clean | Y | N | |
| Kingsoft WPS Office | Y | N | 4 |
| Z by HP Data Science Stack Manager | Y | N | 5, 6 |
| WSL2/Ubuntu Data Science Stack | Y | N | 5 |
| HP Image Assistant | N | N | |
| HP Support Assistant | N | N | |
| HP Smart Health | N | N | |

Note 1: Supported with Windows only. Also available as a free download from <http://www.hp.com/go/performanceadvisor>

Note 2: Windows OS only

Note 3: Not available in Russia

Note 4: Not available in China

Note 5: Only available with NVIDIA® graphics

Note 6: Only available with Ubuntu

Supported Components

Operating Systems Windows 11 Pro for Workstations^{1,2}

Windows 11 Pro for Workstations (preinstalled with Windows 10 Pro for Workstations Downgrade)^{1,2,3}

Ubuntu 22.04 LTS⁴

HP Linux[®]-ready

¹ Windows Enterprise sold separately and requires that customer have an enterprise license from Microsoft.

² Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.

³This system is preinstalled with Windows 10 Pro software and also comes with a license for Windows 11 Pro software and provision for recovery software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

⁴ Not all features are available in all editions or versions of Ubuntu. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS to take full advantage of Ubuntu functionality. Ubuntu may be automatically updated. ISP fees may apply and additional requirements may apply over time for updates.

NOTE: Your product does not support Windows 8 or Windows 7. In accordance with Microsoft's support policy, HP does not support the Windows[®] 8 or Windows 7 operating system on products configured with Intel[®] and AMD[®] 7th generation and forward processors or provide any Windows[®] 8 or Windows 7 drivers on <http://www.support.hp.com>. A full list of HP products and the Windows 10 versions tested is available on the HP support website. <https://support.hp.com/us-en/document/c05195282>

Supported Components

HP BIOS

Key features of the HP BIOS include:

- Deployment and manageability – HP BIOS provides several technologies that help integrate the HP Z6 G5 Workstation into the enterprise, such as PXE, remote recovery, remote configuration, remote control, and BIOS (F10) Setup support for 15 languages.
- Network firmware updates – Update your BIOS via the cloud or standardize on a BIOS version hosted on an Enterprise network.
- Stability – HP BIOS supports the HP stable product roadmap by releasing only critical BIOS changes to the factory and advanced change notification.
- Class 3 UEFI specification version 2.7
- Absolute Persistence agent – For tracking and tracing services, available in select countries, separate software and purchase of a subscription is required.
- Thermal and power management – The HP BIOS provides and enables thermal and power management technologies so component temperatures are managed for high reliability and to assist in operating the HP Workstation computer in any enterprise environment.
- Acoustic performance – Industry leading acoustic emissions across the range of operating conditions.
- Serviceability – HP BIOS provides diagnostic and detailed service information.
- Upgrades and recovery – HP BIOS provides numerous ways to upgrade HP Workstation computers, including BIOS updates from within Windows (HP Firmware Update and Recovery), Capsule update, HP Client Manager, and fail-safe recovery. In addition, the HP BIOS Configuration Utility enables replication of BIOS settings within Windows while the Replicated Setup feature provides the same capability within BIOS (F10) Setup. The BIOS Configuration Utility is available from the HP support website.
- HP BIOS uses PKI signing of the BIOS for trusted BIOS upgrades and recovery. Additional HP BIOS Features:
 - Power-On password – Helps prevent an unauthorized user from powering on the system.
 - Administrator password – Also known as the BIOS Setup password, this helps prevent unauthorized changes to the system configuration. If the administrator password is not known, the BIOS cannot be updated and changes cannot be made to BIOS settings using BIOS Setup or under the OS.
 - S4/S5 Maximum Power Savings setting supports EU Lot6 requirement and allows the computer to power down below 0.5W in S4/S5 (when turned off). When S4/S5 Maximum Power Savings feature is enabled below features are turned off:
 - Power to expansion connectors / slots
 - Most Wake events other than power buttons and WOL (Wake on LAN supported by embedded Lan controller under S4/S5 Maximum Power Saving Enabled)
 - USB charging ports

HP Sure Start Gen7

- BIOS Integrity checking – Sure Start protection ensures that only trusted BIOS code is executed and not rootkits, viruses and malware. Verification is done upon boot up, shutdown and while the system is on.
- Sure Start is set by default to automatically repair the BIOS if corrupted or compromised but is policy driven for better manageability. Start is set by default to automatically repair the BIOS if corrupted or compromised but is policy driven for better manageability.
- Protecting beyond BIOS – Integrity checking and repair is extended to other data that should be protected such as network configuration parameters, platform specific information (i.e. system IDs), secure boot credentials, and other code the system needs to boot.
- Audit enabled – System Audit via Sure Start Event Logs capture data such as incident, repair date and time for troubleshooting and investigating.

Supported Components

SOFTWARE COMPONENTS AND APPLICATIONS WITH WINDOWS

BIOS

- HP BIOSphere Gen6¹³
- HP DriveLock & Automatic DriveLock
- BIOS Update via Network
- Master Boot Record Security
- Power On Authentication
- Absolute Persistence Module²³
- Pre-boot Authentication
- HP Wireless Wakeup

Software

- HP Desktop Support Utility
- HP Performance Advisor¹
- HP Privacy Settings
- HP Notifications
- myHP

Manageability Features

- HP Driver Packs²
- HP System Software Manager (SSM)
- HP BIOS Config Utility (BCU)
- HP Client Catalog
- HP Manageability Integration Kit Gen6³

Client Security Software

- HP Wolf Security (Including HP Sure Click & HP Sure Sense)²²
- HP Pro Wolf Security (Including Credential Manager)¹⁸
- HP Client Security Manager Gen 7⁴
- HP Sure Run⁹
- HP Sure Recover¹⁰
- HP Power On Authentication
- Microsoft Defender⁷

Security Management

- HP Security Update Service (SUS)
- Secure Erase¹⁶
- TPM 2.0 Embedded Security Chip(Common Criteria EAL4+ Certified)²⁴
- SATA port disablement (viaBIOS)
- Serial, USB enable/disable (viaBIOS)
- Power-on password (viaBIOS)
- Setup password (viaBIOS)
- Support for chassis padlocks and cable lock devices
- Integrated hood sensor⁰
- HP Sure Start Gen4⁸

¹ HP Performance Advisor Software - HP Performance Advisor is ready to help you get the most out of your HP Workstation from day one—and every day after. Learn more or download at: <http://hp.com/PerformanceAdvisor>

² HP Driver Packs not preinstalled, however available for download at <http://www.hp.com/go/clientmanagement>.

³ HP Manageability Integration Kit can be downloaded from <http://www8.hp.com/us/en/ads/clientmanagement/overview.html>

⁴ HP Client Security Manager Gen7 requires Windows and is available on the select HP PCs.

Supported Components

⁷ Microsoft Defender Opt in and internet connection required for updates.

⁸ HP Sure Start Gen 7 is available on select HP PCs and workstations. See product specifications for availability.

⁹ HP Sure Run Gen5 is available on select Windows 11 based HP Pro, Elite and Workstation PCs with select Intel® or AMD processors

¹⁰ HP Sure Recover Gen4 is available on select HP PCs and requires Windows 10 and an open network connection. You must back up important files, data, photos, videos, etc. before using HP Sure Recover to avoid loss of data. Network based recovery using Wi-Fi is only available on PCs with Intel Wi-Fi Module

¹³ HP BIOSphere Gen6 features may vary depending on the platform and configurations.

¹⁶ Secure Erase - For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane.

¹⁸ HP Wolf Pro Security Edition is available preloaded on select SKUs and, depending on the HP product purchased, includes a paid 1-year or 3-year license. The HP Wolf Pro Security Edition software is licensed under the license terms of the HP Wolf Security Software - End-User license Agreement (EULA) that can be found at: https://support.hp.com/us-en/document/ish_3875769-3873014-16 as that EULA is modified by the following: "7. Term. Unless otherwise terminated earlier pursuant to the terms contained in this EULA, the license for the HP Wolf Pro Security Edition (HP Sure Sense Pro and HP Sure Click Pro) is effective upon activation and will continue for either a twelve (12) month or thirty-six (36) month license term ("Initial Term"). At the end of the Initial Term you may either (a) purchase a renewal license for the HP Wolf Pro Security Edition from HP.com, HP Sales or an HP Channel Partner, or (b) continue using the standard versions of HP Sure Click and HP Sure Sense at no additional cost with no future software updates or HP Support.

²² HP Wolf Security for Business requires Windows 10 or higher, includes various HP security features and is available on HP Pro, Elite, RPOS and Workstation products. See product details for included security features

²³ Absolute agent is shipped turned off, and will be activated when customers activate a purchased subscription.

Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit: <http://www.absolute.com/company/legal/agreements/computrace-agreement>. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either obtain a PIN or purchase one or more RSA SecurID tokens from Absolute Software.

²⁴Firmware TPM is version 15.21. Hardware TPM is v2.0.

System Technical Specifications

System Board

| | | |
|---|--|--|
| System Board Form Factor | Approximately 284.48mm x 297.18mm (11.2x11.9 inches). | |
| Processor Socket | Single LGA-4677 | |
| CPU Bus Speed | DMI Gen4 x 8 lanes | |
| Chipset | Intel W790 Alder Lake – WS PCH | |
| Super I/O Controller | Nuvoton SIO21 | |
| Memory Expansion Slots | 8 DDR5 memory slots | |
| Memory Type Supported | DDR5 RDIMMs (Registered), RDIMMs and 3DS RDIMMs | |
| Memory Modes | Non-Interleaving for single channel. Interleaving when multiple channels are populated | |
| Memory Speed Supported | 4800MT/s for 1DPC and 4400MT/s for 2DPC; DDR5 | |
| Memory Protection | ECC on data | |
| Maximum Memory | 1TB | |
| Memory Configuration (Supported) | 16GB, 32GB, 64GB RDIMMs and 128GB 3DS RDIMMs are supported. RDIMMs and 3DS RDIMMs cannot be mixed in the same system. 64GB RDIMMs cannot be mixed with other capacities in the same system. | |
| NVDIMM Memory | No | |
| PCI Express Connectors | Standard PCIe Slots: <ul style="list-style-type: none"> • 1 PCI Express Gen5 slot x16 mechanical/ x16 electrical (full height, full length) • 2 PCI Express Gen4 slot x16 mechanical/ x16 electrical (full height, full length) • 2 PCI Express Gen4 slot x4 mechanical/ x4 electrical (full height, half length) • 1 PCI Express Gen3 slot x16 mechanical/ x8 electrical (full height, full length) M.2 Slots: <ul style="list-style-type: none"> • 2 PCI Express Gen4 slot x4. Other PCIe Connections: <ul style="list-style-type: none"> • 2 Front NVMe Storage (SlimSAS PCIe Gen4 x8) (each PCIe connection supports two x4 M.2 devices for a total system support of four x4 M.2 devices via QX448) • 1 10GbE (PCIe Gen3 x4) | |
| Supported Drive Interfaces | SATA | Number of SATA ports: 5 Intel® SATA controller: primary SATA |
| | Integrated RAID | On-board RAID Support Intel® VROC® SATA RAID 0, 1, 5, and 10 supported on Windows 10 and 11, RHEL 8.6 and later, SLE 15 SP4 and later Intel® VROC® NVMe RAID 0, 1, 5, and 10 supported with presence of appropriate VROC upgrade module (after-market kits) on Windows 10 and 11, RHEL 8.6 and later, SLE 15 SP4 and later |
| | | Factory Configured RAID: None |
| | Integrated Graphics | No |
| | Network Controller | WGI219LM. WGI219LM LOM provides Management capabilities: WOL, PXE 2.1, DASH 1.1 and AMT |
| | External SATA (eSATA) | No |
| | Serial | 1 internal header (requires optional Serial Port Adapter Kit) |
| | 2nd Serial | No |
| | HD Integrated Audio | Yes |

System Technical Specifications

| | | |
|--|---|--|
| USB Connector(s) | Front | <p>Front I/O Entry: 4 USB 3.1 Gen1 Type-A (left-most port supports Battery Charging 1.2)</p> <p>Front I/O Premium: 2x USB 3.2 Gen2x2 Type-C™ (Power Delivery 3.0) 2x USB 3.1 Gen1 Type-A (left-most port supports Battery Charging 1.2)</p> <ul style="list-style-type: none"> • USB Type-C Ports provide 3 Amps @ 5 Volts • Charging USB Type-A port provides 1.5 Amps @ 5 Volts • Standard USB Type-A Ports provide 900mA @ 5 Volts |
| | Rear | <p>4x USB 3.1 Gen1 Type-A with USB hub and 2x USB 3.2 Gen 1 Type-A without hub. (Optional: 2x USB 3.0 Type-A (optional via Flex module) or 1x USB 3.1 Gen2 Type-C charging port (optional via Flex module).</p> |
| | Internal | <p>1 USB 3.2 Gen1 header, with a single 12-pin shrouded connector. This header supports a USB Media Card reader. 1 USB 2.0 single port header 1 USB 2.0 dual port header</p> |
| Flash ROM | Yes | |
| CPU Fan Header | Yes | |
| Memory Fan Header | Yes (dual header) | |
| Chassis Fan Header | 1 front, one rear and one Aux Fan Header (dual) | |
| Front PCI Fan Header | Yes (connects to AUX fan header) | |
| Front Control Panel/Speaker Header | Yes | |
| CMOS Battery Holder - Lithium | Yes | |
| Integrated Trusted Platform Module | Integrated TPM 2.0. Convertible to FIPS 140-2 Certified Mode through firmware v15.21. The TPM module is disabled where restricted by law. | |
| Power Supply Headers | Yes | |
| Power Switch, Power LED & Hard Drive LED Header | Yes | |
| Clear Password Jumper | Yes | |
| Keyboard/Mouse | USB and PS/2 (option) | |

¹Maximum memory capacities assume 64-bit operating systems, such as Genuine Windows® 11 Professional 64 bit, Red Hat Linux 64-bit.

²M.2 storage supports compatible devices up to 80mm

System Technical Specifications

| System Configurations | | |
|---------------------------------|-----------------------------|---|
| Example Configuration #1 | Processor Info | Intel® Xeon® W5-3423 12C 2.1GHz 4800 220W |
| | Memory Info | 32GB DDR5 (2x16GB) RegRAM |
| | Graphics Info | 1x NVIDIA® A2000 |
| | Disks/Optical/Floppy | 1x 4TB Internal M.2 SSD + 1x DVDRW SATA |
| | PSU | 775W |
| | Other | N/A |

| Energy Consumption (Watts) | 115 VAC | | 230 VAC | | 100 VAC | |
|----------------------------|-------------|--------------|-------------|--------------|-------------|--------------|
| | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled |
| Windows Idle (S0) | 103.608 | 101.857 | 103.956 | 102.238 | 103.159 | 101.483 |
| Windows Busy Typ (S0) | 305.875 | | 301.956 | | 304.253 | |
| Windows Busy Max (S0) | 337.145 | | 329.662 | | 337.118 | |
| Sleep (S3) | 3.624 | 3.614 | 3.628 | 3.617 | 3.621 | 3.608 |
| Off (S5) | 2.136 | 2.143 | 2.165 | 2.146 | 2.158 | 2.138 |
| Zero Power Mode (EuP) | 0.238 | | 0.288 | | 0.237 | |

| Heat Dissipation (Btu/hr) | 115 VAC | | 230 VAC | | 100 VAC | |
|---------------------------|-------------|--------------|-------------|--------------|-------------|--------------|
| | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled |
| Windows Idle (S0) | 353.577 | 347.536 | 354.697 | 348.836 | 351.978 | 346.261 |
| Windows Busy Typ (S0) | 1043.646 | | 1030.274 | | 1038.111 | |
| Windows Busy Max (S0) | 1150.339 | | 1124.807 | | 1150.247 | |
| Sleep (S3) | 12.365 | 12.331 | 12.378 | 12.341 | 12.354 | 12.311 |
| Off (S5) | 7.381 | 7.311 | 7.386 | 7.322 | 7.363 | 7.294 |
| Zero Power Mode (EuP) | 0.812 | | 0.982 | | 0.808 | |

| | | |
|---------------------------------|-----------------------------|--|
| Example Configuration #2 | Processor Info | Intel® Xeon® W5-3433 16C 2.0GHz 4800 220W |
| | Memory Info | 64GB DDR5 (4x16GB) RegRAM |
| | Graphics Info | 1x NVIDIA® A4000 |
| | Disks/Optical/Floppy | 1x 1TB Internal SATA HDD + 2x 4TB Internal M.2 SSD + 1x DVDRW SATA |
| | PSU | 775W |
| | Other | N/A |

| Energy Consumption (Watts) | 115 VAC | | 230 VAC | | 100 VAC | |
|----------------------------|-------------|--------------|-------------|--------------|-------------|--------------|
| | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled |
| Windows Idle (S0) | 117.751 | 114.977 | 117.982 | 115.689 | 116.598 | 116.482 |
| Windows Busy Typ (S0) | 382.156 | | 378.561 | | 380.263 | |
| Windows Busy Max (S0) | 400.368 | | 396.988 | | 398.233 | |
| Sleep (S3) | 4.221 | 4.138 | 4.286 | 4.236 | 4.211 | 4.203 |
| Off (S5) | 2.246 | 2.238 | 2.315 | 2.305 | 2.226 | 2.211 |
| Zero Power Mode (EuP) | 0.241 | | 0.291 | | 0.237 | |

| Heat Dissipation (Btu/hr) | 115 VAC | | 230 VAC | | 100 VAC | |
|---------------------------|---------|-----|---------|-----|---------|-----|
| | LAN | LAN | LAN | LAN | LAN | LAN |

System Technical Specifications

| | Enabled | Disabled | Enabled | Disabled | Enabled | Disabled |
|-----------------------|----------|----------|----------|----------|----------|----------|
| Windows Idle (S0) | 401.766 | 392.301 | 402.554 | 394.731 | 397.832 | 397.436 |
| Windows Busy Typ (S0) | 1303.916 | | 1291.65 | | 1297.457 | |
| Windows Busy Max (S0) | 1366.056 | | 1354.523 | | 1358.771 | |
| Sleep (S3) | 14.402 | 14.118 | 14.623 | 14.453 | 14.367 | 14.341 |
| Off (S5) | 7.663 | 7.636 | 7.898 | 7.864 | 7.595 | 7.543 |
| Zero Power Mode (EuP) | 0.822 | | 0.992 | | 0.808 | |

| | | |
|---------------------------------|-----------------------------|--|
| Example Configuration #3 | Processor Info | Intel® Xeon® W7-3445 20C 2.6GHz 4800 270W |
| | Memory Info | 128GB DDR5 (8x16GB) RegRAM |
| | Graphics Info | 2x NVIDIA® A4000 |
| | Disks/Optical/Floppy | 2x 1TB Internal SATA HDD + 2x 4TB Internal M.2 SSD + 1x DVDRW SATA |
| | PSU | 1125W |
| | Other | N/A |

| Energy Consumption (Watts) | 115 VAC | | 230 VAC | | 100 VAC | |
|----------------------------|-------------|--------------|-------------|--------------|-------------|--------------|
| | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled |
| Windows Idle (S0) | 143.728 | 141.622 | 144.552 | 142.138 | 142.115 | 142.023 |
| Windows Busy Typ (S0) | 529.174 | | 524.226 | | 528.456 | |
| Windows Busy Max (S0) | 647.546 | | 639.41 | | 646.234 | |
| Sleep (S3) | 5.617 | 5.438 | 5.686 | 5.592 | 5.601 | 5.318 |
| Off (S5) | 2.438 | 2.417 | 2.513 | 2.468 | 2.429 | 2.386 |
| Zero Power Mode (EuP) | 0.246 | | 0.296 | | 0.244 | |

| Heat Dissipation (Btu/hr) | 115 VAC | | 230 VAC | | 100 VAC | |
|---------------------------|-------------|--------------|-------------|--------------|-------------|--------------|
| | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled |
| Windows Idle (S0) | 490.399 | 483.214 | 493.211 | 484.974 | 484.896 | 484.582 |
| Windows Busy Typ (S0) | 1805.542 | | 1788.659 | | 1803.092 | |
| Windows Busy Max (S0) | 2209.426 | | 2181.687 | | 2204.951 | |
| Sleep (S3) | 19.165 | 18.554 | 19.401 | 19.079 | 19.111 | 18.145 |
| Off (S5) | 8.318 | 8.246 | 8.574 | 8.421 | 8.287 | 8.141 |
| Zero Power Mode (EuP) | 0.839 | | 1.009 | | 0.832 | |

| | | |
|---------------------------------|-----------------------------|--|
| Example Configuration #4 | Processor Info | Intel® Xeon® W7-3455 24C 2.5GHz 4800 270W |
| | Memory Info | 256GB DDR5 (8x32GB) RegRAM |
| | Graphics Info | 2x NVIDIA® A6000 |
| | Disks/Optical/Floppy | 2x 4TB Internal SATA HDD + 1x 4TB Internal M.2 SSD + 1x DVDRW SATA |
| | PSU | 1450W/200V |
| | Other | N/A |

| Energy Consumption (Watts) | 115 VAC | | 230 VAC | | 100 VAC | |
|----------------------------|-------------|--------------|-------------|--------------|-------------|--------------|
| | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled |
| Windows Idle (S0) | N/A | | 165.724 | 158.644 | N/A | |
| Windows Busy Typ (S0) | N/A | | 724.391 | | N/A | |

System Technical Specifications

| | | | | | | | |
|--|-----------------------|-----|-----|----------|-------|-----|-----|
| | Windows Busy Max (S0) | N/A | | 1092.632 | | N/A | |
| | Sleep (S3) | N/A | N/A | 6.458 | 6.157 | N/A | N/A |
| | Off (S5) | N/A | N/A | 4.623 | 4.428 | N/A | N/A |
| | Zero Power Mode (EuP) | N/A | | 2.268 | | N/A | |

| Heat Dissipation (Btu/hr) | | 115 VAC | | 230 VAC | | 100 VAC | |
|---------------------------|-----------------------|-------------|--------------|-------------|--------------|-------------|--------------|
| | | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled | LAN Enabled | LAN Disabled |
| | Windows Idle (S0) | N/A | | 565.451 | 541.293 | N/A | |
| | Windows Busy Typ (S0) | N/A | | 2471.622 | | N/A | |
| | Windows Busy Max (S0) | N/A | | 3728.061 | | N/A | |
| | Sleep (S3) | N/A | N/A | 22.682 | 21.007 | N/A | N/A |
| | Off (S5) | N/A | N/A | 15.804 | 15.108 | N/A | N/A |
| | Zero Power Mode (EuP) | N/A | | 7.738 | | N/A | |

NOTE: The numbers in this table are from actual measurements on a single system. There will be some variation from unit to unit.

NOTE: The busy power number and associated BTU/hr number for each configuration will be a strong function of the actual application software run on the system. There can be a great deal of variation in this number.

NOTE: The Power Supply Efficiency report may be found at the following links:
<https://www.plugloadsolutions.com/80PlusPowerSuppliesDetail.aspx?id=0&type=2>

System Technical Specifications

| | |
|--|---|
| Operating Voltage Range | 90-269 VAC |
| Rated Voltage Range | 100-240 VAC |
| Rated Line Frequency | 50-60 Hz |
| Operating Line Frequency Range | 47-66 Hz |
| ENERGY STAR® certified (Config Dependent) | Yes |
| CECP Compliant @ 220V | Yes |
| FEMP Standby Power Compliant | Yes, with Wake-on-LAN disabled: <1W in S5 - Power Off |
| Built-in Self Test (BIST) LED | Yes |
| Surge Tolerant Full Ranging Power Supply (withstands power surges up to 2000V) | Yes |
| Hood Lock Header | Yes |
| ErP Lot 6- Tier 1 Compliance @ 230V (<1W in S5 - Power Off) | Yes |
| ErP Lot 6- Tier 2 Compliance @ 230V (<0.5W in S5 - Power Off) | Yes |

| Declared Noise Emissions (Entry-level, Mid-level, and High-end configurations; tested on floor) | | | |
|---|---|---|---|
| System Configuration (Entry level) | Processor Info | 1x Intel Xeon w5-3423 12C 2.1GHz 4800 220W | |
| | Memory Info | 64GB (4x16GB) DDR5 4800MHz RDIMM | |
| | Graphics Info | 1xNVIDIA RTX A2000 | |
| | Disks/Optical | 1x Internal 4TB M.2+ 1xDVDRW SATA | |
| | Power Supply | 775W | |
| Declared Noise Emissions | | Sound Power (LWAd, bels) | Deskside Sound Pressure (LpAm, decibels) |
| | Idle | 3.3 | 15 |
| | Hard drive Operating (Drive Random Seek) | 3.4 | 15 |
| | Active mode | 3.3 | 15 |
| System Configuration (Mid-level) | Processor Info | 1x Intel Xeon w-3445 20C 2.6GHz 4800 270W | |
| | Memory Info | 128GB (8*16GB) DDR5 4800MHz RDIMM | |
| | Graphics Info | 1xNVIDIA RTX A4000 | |
| | Disks/Optical | 1x1TB HDD + 1xInternal 4TB M.2 SSD + 1xDVDRW SATA | |
| | Power Supply | 775W | |
| Declared Noise Emissions | | Sound Power (LWAd, bels) | Deskside Sound Pressure (LpAm, decibels) |
| | Idle | 3.1 | 16 |
| | Hard drive Operating (Drive Random Seek) | 3.4 | 22 |

System Technical Specifications

| | | | |
|--|---|---|---|
| | Active mode | 3.4 | 21 |
| System Configuration (High-end) | Processor Info | 1x Intel Xeon w-3465X 28C 2.5GHz 4800 300W | |
| | Memory Info | 512GB (8x64GB) DDR5 4800MHz RDIMM | |
| | Graphics Info | 3x NVIDIA RTX A6000 | |
| | Disks/Optical | 2x4TB HDD + 2xInternal 4TB M.2 SSD + 1xDVDRW SATA | |
| | Power Supply | 1125W | |
| Declared Noise Emissions | | Sound Power (LWAd, bels) | Deskside Sound Pressure (LpAm, decibels) |
| | Idle | 3.8 | 21 |
| | Hard drive Operating (Drive Random Seek) | 3.9 | 24 |
| | Active mode | 4.7 | 29 |

Environmental Requirements

Temperature

Operating: 5° to 40°C (40° to 104°F)¹
 Non-operating: -40° to 60°C (-40° to 140°F)

¹40°C has been validated for configs up to a 220W CPU, 2x NVIDIA® RTX A4000 graphics cards, 8x64GB RAM, 2x 2TB M.2 storage, 2x 2TB HDD storage, and 1125W PSU

Humidity

Operating: 8% to 85% RH, non-condensing
 Non-operating: 8% to 90% RH, non-condensing

Maximum Altitude

Operating: 3,048 m (10,000 feet)
 Non-operating: 9,144 m (30,000 feet)

Dynamic

Shock
 Operating: ½-sine: 40g, 2-3ms (~62 cm/sec)
 Non-operating: ½-sine: 160 cm/s, 2-3ms (~105g)
 square: 422 cm/s, 20g
NOTE: Values represent individual shock events and do not indicate repetitive shock events

Vibration
 Operating random: 0.5g (rms), 5-300 Hz, up to 0.0025g²/Hz
 Non-operating random: 2.0g (rms), 5-500 Hz, up to 0.0150 g²/Hz
NOTE: Values do not indicate continuous vibration.

Cooling

Above 1524 m (5,000 feet) altitude, the maximum operating temperature is reduced by 1° C (1.8° F) for every 305 m (1,000 feet) increase in elevation, up to 3048 m (10,000 feet)

System Technical Specifications

Physical Security and Serviceability

| | |
|---|---|
| Access Panel | Tool-less Includes system board and memory information |
| Optical Drive | Tool-less, 2nd Optical Drive requires a 5.25" bay carrier |
| Hard Drives | Tool-less |
| Expansion Cards | Tool-less |
| Processor Socket | Screw-in processor coolers |
| Blue User Touch Points | Yes, on tool-less internal chassis mechanisms |
| Color-coordinated Cables and Connectors | Yes |
| Memory | Tool-less |
| System Board | Screw-in |
| Power and HD LED on Front of Computer | Yes |
| Over-Temp Warning on Screen | Yes |
| Dual Function Front Power Switch | Yes, causes a fail-safe power off when held for 4 seconds |
| Padlock Support | Yes (optional): Locks side cover and secures chassis from theft 7.0 mm (0.2756 in) diameter padlock loop at rear of system |
| Cable Lock Support | Yes, Kensington Cable Lock (optional): Locks side cover and secures chassis from theft 3 mm x 7 mm slot at rear of system |
| Universal Chassis Clamp Lock Support | Yes (optional): Locks side cover and locks cables to chassis. Secures chassis from theft and allows multiple units to be chained together when used with optional cable with threaded feature at rear of system |
| Chassis Interlock Sensor | Yes Sensor detects when the access panel has been removed. The access panel must be installed for the system to power ON. Removal of the access panel during operation will power OFF the system. |
| Solenoid Lock and Hood Sensor | Yes (optional) The Solenoid Hood Lock eliminates the need for a physical key by making the chassis lockable through software and a password. You can also lock and unlock the chassis remotely over the network. The Sensor Kit detects when the access panel has been removed |
| Rear Port Control Cover | No |
| Serial, USB, Audio, Network, Enable/Disable Port Control | Yes |
| Removable Media Write/Boot Control | Yes |
| Power-On Password | Yes |
| Setup Password | Yes, prevents an unauthorized person from changing the workstation configuration. |
| 3.3V Aux Power LED on System PCA | No |
| NIC LEDs (integrated) (Green & Amber) | Yes |
| CPUs and Heatsinks | A torx driver (T30) is needed to remove the processor heatsink. CPU attached to heatsink via tool-less clip |
| Power Supply Diagnostic LED | Yes |
| Front Power Button | Yes |

System Technical Specifications

| | |
|---|---|
| Front Power LED | Yes, white (normal), red (fault) |
| Front Hard Drive Activity LED | Yes |
| Front ODD Activity LED | Yes, on device |
| Internal Speaker | Yes |
| System/Emergency ROM Flash Recovery | Yes |
| Cooling Solutions | Air cooled forced convection |
| Power Supply Fans | 80 mm x 80 mm x 25 mm (non-serviceable) |
| CPU Heatsink Fan | 108 mm x 108 mm x 25 mm |
| Chassis Fan | Rear: 120 mm x 120mm x 25 mm Front (optional): 120 mm x 120 mm x 25 mm PCI Retainer (optional based on configuration): Dual 80 mm x 80 mm x 20 mm |
| Memory Heatsink Fan | Dual 60 mm x 60 mm x 25 mm Blindmate (optional based on configuration) |
| HP PC Hardware Diagnostics UEFI | Yes |
| Access Panel Key Lock | Yes, side panel barrel keylock (optional from the factory only) |
| ACPI-Ready Hardware | Advanced Configuration and Power Management Interface (ACPI). <ul style="list-style-type: none"> • Allows the system to wake from a low power mode. • Controls system power consumption, making it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system. |
| Integrated Chassis Handles | Yes, Front handle and dedicated rear recess |
| Power Supply | Requires T15 Torx or flat blade screwdriver |
| PCI Card Retention | Yes, rear (all), middle (all), front (full-length cards with extender, using Fan and Front Card Guide Kit) |
| Flash ROM | Yes |
| Diagnostic Power Switch LED on board | Yes |
| Clear Password Jumper | Yes |
| Clear CMOS Button | Yes |
| CMOS Battery Holder | Yes |
| DIMM Connectors | Yes |

Service, Support, and Warranty

On-site Warranty and Service¹: Three-years, limited warranty and service offering delivers on-site, next business-day² service for parts and labor and includes free telephone support³ 8am - 5pm. Global coverage² ensures that any product purchased in one country and transferred to another, non-restricted country will remain fully covered under the original warranty and service offering. 24/7 operation will not void the HP warranty. Storage devices are not covered under warranty for 24/7 operation except for Enterprise class HDDs.

NOTE 1: Terms and conditions may vary by country. Certain restrictions and exclusions apply.

NOTE 2: On-site service may be provided pursuant to a service contract between HP and an authorized HP third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country.

NOTE 3: Technical telephone support applies only to HP-configured, HP and HP-qualified, third-party hardware and software. Toll-free calling and 24x7 support service may not be available in some countries.

HP Care Pack Services extend service contracts beyond the standard warranties. Service starts from date of hardware purchase.

To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at:

<http://www.hp.com/go/lookuptool>. Service levels and response times for HP Care Packs may vary depending on your geographic

System Technical Specifications

location.

Certification and Compliance

Environmental Sustainability questions concerning:

- Ecolabels (EPEAT, TCO, etc.)
- ENERGY STAR, California Energy Commission (CEC)
- Compliance with Environmental legislation (EU ErP, China CECP, EU RoHS and other countries)
- Supply Chain Social Environmental Responsibility (SER) (conflict minerals; human rights, etc.)
- Product specific environmental features (material content, packaging content, recycled content, etc.)
- China Energy Label (CEL)
-

Please contact sustainability@hp.com

For country specific Regulatory Compliance approval documents or Regulatory and Safety questions concerning:

- Declarations of Conformity (for self-service, go to https://www.hp.com/uk-en/certifications/technical/regulations-certificates.html?jumpid=ex_r135_uk/en/any/corp/hpuk-mu_chev/certificates)
- GS Certificates
- Product Safety Certificates (UL, CB, BIS, etc.)
- EMC Certificates, Declarations of Conformity, or Certificates of Conformity (CE, FCC, ICES, etc.)
- CCC Certificates
- Ergonomics
-

Please contact techregshelp@hp.com

BIOS

| | |
|---|--|
| PCIe 5.0 Support | Full BIOS support for PCI Express through industry standard interfaces. Supported speeds and slot information vary. |
| ATA/ATAPI | AT Attachment 6 with Packet Interface (ATA/ATAPI-6), Revision 3b |
| WMI Support | WMI is Microsoft's implementation of Web-Based Enterprise Management (WBEM) for Windows. WMI is fully compliant with the Distributed Management Task Force (DMTF) Common Information Model (CIM) and WBEM specifications. |
| BIOS Power On | Users can define a specific date and time for the system to power on. |
| ROM Based Computer Setup Utility (F10) | Review and customize system configuration settings controlled by the BIOS. |
| System/Emergency ROM Flash Recovery with Video | Recovers system BIOS in corrupted Flash ROM. |
| Replicated Setup | Saves BIOS settings to USB flash device in human readable file (HpSetup.txt). BiosConfigurationUtility.exe utility can then replicate these settings on machines being deployed without entering Computer Configuration Utility (F10 Setup). |
| SMBIOS | System Management BIOS Reference Specification, Version 3.2 |
| Boot Control | Disables the ability to boot from removable media on supported devices. |
| Memory Change Alert | Alerts management console if memory is removed or changed. |
| Thermal Alert | Monitors the temperature state within the chassis. Three modes: <ul style="list-style-type: none">• NORMAL - normal temperature ranges.• ALERTED - excessive temperatures are detected. Raises a flag so action can be taken to avoid shutdown or provide for a smoother system shutdown.• SHUTDOWN - excessive temperatures are encountered. Automatically shuts down the computer without warning before hardware component damage occurs. |

System Technical Specifications

| | |
|---|--|
| Remote ROM Flash | Provides secure, fail-safe ROM image management from a central network console. |
| ACPI (Advanced Configuration and Power Management Interface) | Allows the system to enter and resume from low power modes (sleep states). Enables an operating system to control system power consumption based on the dynamic workload. Makes it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system. Supports ACPI 6.0 for full compatibility with 64-bit operating systems. |
| Ownership Tag | A user-defined string stored in non-volatile memory that is displayed in the BIOS splash screen. |
| Remote Wakeup/Remote Shutdown | System administrators can power on, restart, and power off a client computer from a remote location. |
| Instantly Available PC (Suspend to RAM - ACPI sleep state S3) | Allows for very low power consumption with quick resume time. |
| Remote System Installation via F12 (PXE 2.1) (Remote Boot from Server) | Allows a new or existing system to boot over the network and download software, including the operating system. |
| ROM revision levels | Reports the system BIOS revision level in Computer Configuration Utility (F10 Setup). Version is available through an industry standard interface (SMBIOS and WMI) so that management SW applications can use and report this information. |
| System board revision level | Allows management SW to read revision level of the system board. Revision level is digitally encoded into the HW and cannot be modified. |
| Start-up Diagnostics (Power-on Self-Test) | Assesses system health at boot time with selectable levels of testing. |
| Auto Setup when new hardware installed | System automatically detects addition of new hardware. |
| Keyboard-less Operation | The system can be booted without a keyboard. |
| Localized ROM Setup | Common BIOS image supports System Configuration Utility (F10 Setup) menus in 15 languages with local keyboard mappings. |
| Asset Tag | The user or MIS to set a unique tag string in non-volatile memory. |
| Per-slot Control | Allows I/O slot parameters (option ROM enable/disable, bifurcation, speed) to be configured individually. |
| Adaptive Cooling | Control parameters are set according to detected hardware configuration for optimal acoustics. |
| Pre-boot Diagnostics | (Pre-video) critical errors are reported via beeps and blinks on the power LED. |
| UEFI Specification Revision | 2.7 |
| ACPI | Advanced Configuration and Power Management Interface, Version 6.0 |
| CD Boot | "El Torito" Bootable CD-ROM Format Specification Version 1.0 |
| EHCI | Enhanced Host Controller Interface for Universal Serial Bus, Revision 1.0 |
| PCI Express | PCI Express Base Specification, Revision 2.0 PCI Express Base Specification, Revision 3.0 PCI Express Base Specification, Revision 4.0 PCI Express Base Specification, Revision 5.0 |
| SATA | Serial ATA Specification, Revision 1.0a Serial ATA 3 Gb/s: Serial ATA Specification, Revision 2.5 Serial ATA 6 Gb/s: Serial ATA Specification, Revision 3.0 |
| SPD | JEDEC JESD300-5 |
| TPM | Trusted Computing Group TPM Specification Version 2.0 (Infineon SLB 9672). Common Criteria EAL4+ certified. FIPS 140-2 Certification TCG TPM Certified products list: http://www.trustedcomputinggroup.org/certification/tpm-certified-products/ |
| UHCI | Universal Host Controller Interface Design Guide, Revision 1.1 |
| USB | Universal Serial Bus Revision 1.1 Specification |

System Technical Specifications

- Universal Serial Bus Revision 2.0 Specification
- Universal Serial Bus Revision 3.1 Specification
- Universal Serial Bus Revision 3.2 Specification
- USB Battery Charging specification, Revision 1.2
- USB Power Delivery specification Revision 3.0
- SMBIOS** System Management BIOS Reference Specification, Version 3.2

Social and Environmental Responsibility

Eco-Label Certifications & Declarations This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- ENERGY STAR® (energy-saving features available on selected configurations-Windows only)
- US Federal Energy Management Program (FEMP)
- EPEAT[®] Gold registered worldwide
- TCO Certified
- China Energy Conservation Program (CECP)

- Sustainable Impact Specifications**
- Ocean-bound plastic in system fans
 - 40% post-consumer recycled plastic
 - Contains 10% post-industrial recycled metal
 - Internal Power Supply 90% efficient

System Configuration The configuration used for the Energy Consumption and Declared Noise Emissions data is based on a “Typically Configured Desktop Workstation”.

Energy Consumption (in accordance with US ENERGY STAR® test method)

| | 115VAC, 60Hz | 230VAC, 50Hz |
|------------------------------|---------------------|---------------------|
| Normal Operation (Sort idle) | 119.10 W | 120.50 W |
| Normal Operation (Long idle) | 117.94 W | 118.45 W |
| Sleep | 3.97 W | 4.03 W |
| Off | 2.32 W | 2.42 W |

NOTE:

Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family . HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

| Heat Dissipation* | 115VAC, 60Hz | 230VAC, 50Hz |
|-------------------------------|---------------------|---------------------|
| Normal Operation (Short idle) | 406.13 BTU/hr | 410.91 BTU/hr |
| Normal Operation (Long idle) | 402.18 BTU/hr | 403.91 BTU/hr |
| Sleep | 13.54 BTU/hr | 13.74 BTU/hr |
| Off | 7.91 BTU/hr | 8.25 BTU/hr |

***NOTE:** Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

| Declared Noise Emissions | Sound Power | Sound Pressure |
|---------------------------------|-------------|----------------|
|---------------------------------|-------------|----------------|

System Technical Specifications

Longevity and

This product can be upgraded, possibly extending its useful life by several years. Upgradeable features

**(in accordance with
ISO 7779 and ISO 9296)**

(L_{WAd}, bels)

(L_{pAm}, decibels)

Typically Configured – Idle

3.1

16

Drive Random Seek

3.4

22

Active Mode

3.4

21

System Technical Specifications

Upgrading

and/or components contained in the product may include:

- 3 USB ports
- 1 PC card slot (type I/II)
- 1 ExpressCard/54 slot
- 1 IEEE 1394 Port
- 2 SODIMM memory slots
- Optional expansion base docking station
- 1 multi-bay II storage port
- Interchangeable HDD

Spare parts are available throughout the warranty period and or for up to “5” years after the end of production.

Batteries

This battery in this product complies with EU Directive 2006/66/EC

Battery size: CR2032 (coin cell)

Battery type: Lithium Metal

The battery in this product does not contain:

- Mercury greater than 5ppm by weight
- Cadmium greater than 10ppm by weight
- Lead greater than 40 ppm by weight
- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see www.epeat.net
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product is 94.8% recycle-able when properly disposed of at end of life.

Additional Information

Packaging Materials External:

PAPER/Corrugated

At least 35% Recycled

PAPER/Molded Pulp

100% Recycled

Internal:

PLASTIC/Polyethylene low density - LDPE

80% Recycled

RoHS Compliance

HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam.

We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances—including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical and electronics products.

We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve.

To obtain a copy of the HP RoHS Compliance Statement, see [HP RoHS position statement](#).

System Technical Specifications

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Bis(2-Ethylhexyl) phthalate (DEHP)
- Benzyl butyl phthalate (BBP)
- Dibutyl phthalate (DBP)
- Diisobutyl phthalate (DIBP)
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBEBs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

Packaging Usage

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

HP offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/go/reuse-recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/recyclers>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who

System Technical Specifications

integrate and re-sell HP equipment.

HP, Inc. Corporate Environmental Information

For more information about HP's commitment to the environment:

Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Eco-label certifications

<http://www8.hp.com/us/en/hp-information/environment/ecolabels.html>

ISO 14001 certificates:

<http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842>

and

<http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf>

footnotes

- Percentage of ocean-bound plastic contained in each component varies by product
- Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard.
- External power supplies, WWAN modules, power cords, cables and peripherals excluded.
- 100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers.
- Fiber cushions made from 100% recycled wood fiber and organic materials.

Manageability

Industry Standard Specifications

This product meets the following industry standard specifications for manageability functionality:

- DASH 1.2 (via Intel® LAN on motherboard)

Intel® Active Management Technology (AMT)

Intel® Active Management Technology (AMT) 16.10

An advanced set of remote management features and functionality providing IT administrators the latest and most effective tools to remotely discover, heal, and protect networked client systems regardless of the system's health or power state. AMT 16.10 includes the following advanced management functions:

- Power Management (on, off, reset, graceful shutdown, sleep and hibernate)
 - Support in Max Power Savings (Shutdown and Hibernate Modes)
- Hardware Inventory (includes BIOS and firmware revisions)
- Hardware Alerting
- Agent Presence
- System Defense Filters
- Serial Over LAN (SOL)
- USB Redirect (Media Redirection)
- ME Wake-on-LAN (WOL), even with Maximum Power Savings Enabled
- DASH 1.1 compliance
- IPv6 Support
- Fast Call for Help - a client inside or outside the firewall may initiate a call for help via BIOS screen, periodic connections, or alert triggered connection
- Remote Scheduled Maintenance - pre-schedule when the system connects to the IT or service provider console for maintenance.
- Remote Alerts - automatically alert IT or service provider if issues arise
- Access Monitor - Provides oversight into Intel® AMT actions to support security requirements
- PC Alarm Clock
- Microsoft NAP Support
- Host Base set-up and configuration
- Management Engine (ME) firmware roll back

System Technical Specifications

- Local Time Sync to UTC
- Remote Memory Dump Command – Creates memory dump for debug

Intel® vPro™ Technology Yes, when configured with an Intel® vPro™ supporting processor.

Technical Specifications - Stable & Consistent Offerings

Stable & Consistent Offerings

Global Series SKUs As part of its commitment to hardware, software, and solution innovation, HP is proud to introduce this breakthrough platform configuration stability to HP Workstation customers. HP Stable & Consistent Offerings are built on the foundation of a carefully chosen set of hardware and software designed and tested to work with all HP Z Workstation platforms through their end of life. These components and their corresponding HP Workstation platform compatibility are outlined in this section.

Stable & Consistent Offerings HP Stable & Consistent Offerings are available worldwide to all HP Workstation customers-no special programs, no additional cost-no kidding. Simply select your hardware and software components when you customize your HP Workstation and be assured that you'll be able to buy that same configuration throughout the lifecycle of the product.

| | |
|-------------------|-----------------------------|
| Processors | Product Offering # |
| | 6M6S5AV Intel Xeon W5-3425 |
| | 6M6S7AV Intel Xeon W5-3435X |

| | |
|-----------------|-----------------------------|
| Graphics | Product Offering # |
| | 695F4AV AMD Radeon RX 6400 |
| | 57D43AV AMD Radeon Pro 6600 |

| | |
|----------------|---|
| Storage | Product Offering # |
| | 57F29AV Z Turbo 1TB PCIe-4x4 2280 TLC M.2 Solid State Drive |
| | 57D76AV 1TB 7200RPM SATA 3.5in Enterprise |

Technical Specifications - Hard Drives

STORAGE/HARD DRIVES

| | | | |
|--|--|---|---|
| Performance PCIe SSDs for HP Workstations | Z Turbo 512GB 2280 PCIe-4x4 TLC SSD | Capacity | 512GB |
| | | Protocol | PCIe |
| | | Form Factor | M.2 |
| | | Controller | NVMe |
| | | NAND Type | 3D TLC |
| | | Endurance | 300TBW (TB Written) |
| | | Reliability | 1.5M hours |
| | | Rated for 24/7/365 operation | No |
| | | Interface | PCI Express 4.0 x4 electrical |
| | | Operating Temperature | 32° to 158° F (0° to 70° C) |
| | | Performance | Sequential Read up to 6400MB/s* |
| | | | Sequential Write up to 3400MB/s* |
| | | | Random Read up to 600K IOPS* |
| | | | Random Write up to 600K IOPS* |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | |
|--|--|---|---|
| | Z Turbo 512GB 2280 PCIe-4x4 SED OPAL2 TLC M.2 SSD | Capacity | 512GB |
| | | Protocol | PCIe |
| | | Form Factor | M.2 |
| | | Controller | NVMe |
| | | NAND Type | 3D TLC |
| | | Endurance | 300TBW (TB Written) |
| | | Reliability | 1.5M hours |
| | | Rated for 24/7/365 operation | No |
| | | Interface | PCI Express 4.0 x4 electrical |
| | | Operating Temperature | 32° to 158° F (0° to 70° C) |
| | | Performance | Sequential Read up to 6400MB/s* |
| | | | Sequential Write up to 3400MB/s* |
| | | | Random Read up to 600K IOPS* |
| | | | Random Write up to 600K IOPS* |

**Self-Encrypting Drive
Support** OPAL 2

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | |
|--|---|--------------------|---------------------|
| | Z Turbo 1TB 2280 PCIe-4x4 SED OPAL2 TLC M.2 SSD Module | Capacity | 1TB |
| | | Protocol | PCIe |
| | | Form Factor | M.2 |
| | | Controller | NVMe |
| | | NAND Type | 3D TLC |
| | | Endurance | 400TBW (TB Written) |
| | | Reliability | 1.5M hours |

Technical Specifications - Hard Drives

| | | | | | | | | | |
|--------------------------------------|--|------------------------|-----------------|-------------------------|-----------------|--------------------|------------------|---------------------|------------------|
| Rated for 24/7/365 operation | No | | | | | | | | |
| Interface | PCI Express 4.0 x4 electrical | | | | | | | | |
| Operating Temperature | 32° to 158° F (0° to 70° C) | | | | | | | | |
| Performance | <table> <tr> <td>Sequential Read</td> <td>up to 6500MB/s*</td> </tr> <tr> <td>Sequential Write</td> <td>up to 5000MB/s*</td> </tr> <tr> <td>Random Read</td> <td>up to 800K IOPS*</td> </tr> <tr> <td>Random Write</td> <td>up to 800K IOPS*</td> </tr> </table> | Sequential Read | up to 6500MB/s* | Sequential Write | up to 5000MB/s* | Random Read | up to 800K IOPS* | Random Write | up to 800K IOPS* |
| Sequential Read | up to 6500MB/s* | | | | | | | | |
| Sequential Write | up to 5000MB/s* | | | | | | | | |
| Random Read | up to 800K IOPS* | | | | | | | | |
| Random Write | up to 800K IOPS* | | | | | | | | |
| Self-Encrypting Drive Support | OPAL 2 | | | | | | | | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | | | | | | | | |
|--|-------------------------------------|--|------------------------|-----------------|-------------------------|-----------------|--------------------|------------------|---------------------|------------------|
| Z Turbo 1TB 2280 PCIe-4x4 TLC SSD | Capacity | 1TB | | | | | | | | |
| | Protocol | PCIe | | | | | | | | |
| | Form Factor | M.2 | | | | | | | | |
| | Controller | NVMe | | | | | | | | |
| | NAND Type | 3D TLC | | | | | | | | |
| | Endurance | 400TBW (TB Written) | | | | | | | | |
| | Reliability | 1.5M hours | | | | | | | | |
| | Rated for 24/7/365 operation | No | | | | | | | | |
| | Interface | PCI Express 4.0 x4 electrical | | | | | | | | |
| | Operating Temperature | 32° to 158° F (0° to 70° C) | | | | | | | | |
| | Performance | <table> <tr> <td>Sequential Read</td> <td>up to 6500MB/s*</td> </tr> <tr> <td>Sequential Write</td> <td>up to 5000MB/s*</td> </tr> <tr> <td>Random Read</td> <td>up to 800K IOPS*</td> </tr> <tr> <td>Random Write</td> <td>up to 800K IOPS*</td> </tr> </table> | Sequential Read | up to 6500MB/s* | Sequential Write | up to 5000MB/s* | Random Read | up to 800K IOPS* | Random Write | up to 800K IOPS* |
| Sequential Read | up to 6500MB/s* | | | | | | | | | |
| Sequential Write | up to 5000MB/s* | | | | | | | | | |
| Random Read | up to 800K IOPS* | | | | | | | | | |
| Random Write | up to 800K IOPS* | | | | | | | | | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | | | | | | | | |
|--|-------------------------------------|--|------------------------|-----------------|-------------------------|-----------------|--------------------|------------------|---------------------|------------------|
| Z Turbo 1TB 2280 PCIe-4x4 TLC SSD | Capacity | 1TB | | | | | | | | |
| | Protocol | PCIe | | | | | | | | |
| | Form Factor | M.2 | | | | | | | | |
| | Controller | NVMe | | | | | | | | |
| | NAND Type | 3D TLC | | | | | | | | |
| | Endurance | 400TBW (TB Written) | | | | | | | | |
| | Reliability | 1.5M hours | | | | | | | | |
| | Rated for 24/7/365 operation | No | | | | | | | | |
| | Interface | PCI Express 4.0 x4 electrical | | | | | | | | |
| | Operating Temperature | 32° to 158° F (0° to 70° C) | | | | | | | | |
| | Performance | <table> <tr> <td>Sequential Read</td> <td>up to 6500MB/s*</td> </tr> <tr> <td>Sequential Write</td> <td>up to 5000MB/s*</td> </tr> <tr> <td>Random Read</td> <td>up to 800K IOPS*</td> </tr> <tr> <td>Random Write</td> <td>up to 800K IOPS*</td> </tr> </table> | Sequential Read | up to 6500MB/s* | Sequential Write | up to 5000MB/s* | Random Read | up to 800K IOPS* | Random Write | up to 800K IOPS* |
| Sequential Read | up to 6500MB/s* | | | | | | | | | |
| Sequential Write | up to 5000MB/s* | | | | | | | | | |
| Random Read | up to 800K IOPS* | | | | | | | | | |
| Random Write | up to 800K IOPS* | | | | | | | | | |

Technical Specifications - Hard Drives

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | |
|--|-------------------------------------|-------------------------------|------------------|
| Z Turbo 2TB 2280 PCIe-4x4 SED OPAL2 TLC M.2 SSD | Capacity | 2TB | |
| | Protocol | PCIe | |
| | Form Factor | M.2 | |
| | Controller | NVMe | |
| | NAND Type | 3D TLC | |
| | Endurance | 500TBW (TB Written) | |
| | Reliability | 1.5M hours | |
| | Rated for 24/7/365 operation | No | |
| | Interface | PCI Express 4.0 x4 electrical | |
| | Operating Temperature | 32° to 158° F (0° to 70° C) | |
| | Performance | Sequential Read | up to 6500MB/s* |
| | | Sequential Write | up to 5000MB/s* |
| | | Random Read | up to 800K IOPS* |
| Random Write | | up to 800K IOPS* | |
| Self-Encrypting Drive Support | OPAL 2 | | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | |
|--|-------------------------------------|-------------------------------|------------------|
| Z Turbo 2TB 2280 PCIe-4x4 TLC SSD | Capacity | 2TB | |
| | Protocol | PCIe | |
| | Form Factor | M.2 | |
| | Controller | NVMe | |
| | NAND Type | 3D TLC | |
| | Endurance | 500TBW (TB Written) | |
| | Reliability | 1.5M hours | |
| | Rated for 24/7/365 operation | No | |
| | Interface | PCI Express 4.0 x4 electrical | |
| | Operating Temperature | 32° to 158° F (0° to 70° C) | |
| | Performance | Sequential Read | up to 6500MB/s* |
| | | Sequential Write | up to 5000MB/s* |
| | | Random Read | up to 800K IOPS* |
| Random Write | | up to 800K IOPS* | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | |
|--|--------------------|--------|
| Z Turbo 4TB 2280 PCIe-4x4 TLC M.2 SSD | Capacity | 4TB |
| | Protocol | PCIe |
| | Form Factor | M.2 |
| | Controller | NVMe |
| | NAND Type | 3D TLC |

Technical Specifications - Hard Drives

| | | |
|-------------------------------------|-------------------------------|------------------|
| Endurance | 600TBW (TB Written) | |
| Reliability | 1.5M hours | |
| Rated for 24/7/365 operation | No | |
| Interface | PCI Express 4.0 x4 electrical | |
| Operating Temperature | 32° to 158° F (0° to 70° C) | |
| Performance | Sequential Read | up to 6500MB/s* |
| | Sequential Write | up to 5000MB/s* |
| | Random Read | up to 700K IOPS* |
| | Random Write | up to 700K IOPS* |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

NOTE: available in June 2023

Z Turbo 4TB 2280 PCIe-4x4 SED OPAL2 TLC M.2 SSD

| | | |
|--------------------------------------|-------------------------------|------------------|
| Capacity | 4TB | |
| Protocol | PCIe | |
| Form Factor | M.2 | |
| Controller | NVMe | |
| NAND Type | 3D TLC | |
| Endurance | 600TBW (TB Written) | |
| Reliability | 1.5M hours | |
| Rated for 24/7/365 operation | No | |
| Interface | PCI Express 4.0 x4 electrical | |
| Operating Temperature | 32° to 158° F (0° to 70° C) | |
| Performance | Sequential Read | up to 6500MB/s* |
| | Sequential Write | up to 5000MB/s* |
| | Random Read | up to 700K IOPS* |
| | Random Write | up to 700K IOPS* |
| Self-Encrypting Drive Support | OPAL 2 | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

NOTE: available in June 2023

Performance PCIe SSDs for HP Dual Pro Carrier

HP Z Turbo Drive Dual Pro 512GB SSD

| | | |
|-------------------------------------|-------------------------------|-----------------|
| Capacity | 512GB | |
| Protocol | PCIe | |
| Form Factor | M.2 | |
| Controller | NVMe | |
| NAND Type | 3D TLC | |
| Endurance | 300TBW (TB Written) | |
| Reliability | 1.5M hours | |
| Rated for 24/7/365 operation | No | |
| Interface | PCI Express 4.0 x4 electrical | |
| Operating Temperature | 32° to 158° F (0° to 70° C) | |
| Performance | Sequential Read | up to 6400MB/s* |
| | Sequential Write | up to 5000MB/s* |

Technical Specifications - Hard Drives

| | |
|-------------------------|------------------|
| Sequential Write | up to 3400MB/s* |
| Random Read | up to 600K IOPS* |
| Random Write | up to 600K IOPS* |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | |
|--|---|-------------------------------|------------------|
| HP Z Turbo Drive Dual Pro 1TB SSD | Capacity | 1TB | |
| | Protocol | PCIe | |
| | Form Factor | M.2 | |
| | Controller | NVMe | |
| | NAND Type | 3D TLC | |
| | Endurance | 400TBW (TB Written) | |
| | Reliability | 1.5M hours | |
| | Rated for 24/7/365 operation | No | |
| | Interface | PCI Express 4.0 x4 electrical | |
| | Operating Temperature | 32° to 158° F (0° to 70° C) | |
| | Performance | Sequential Read | up to 6500MB/s* |
| | | Sequential Write | up to 5000MB/s* |
| | | Random Read | up to 800K IOPS* |
| Random Write | | up to 800K IOPS* | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | |
|--|---|-------------------------------|------------------|
| HP Z Turbo Drive Dual Pro 2TB SSD | Capacity | 2TB | |
| | Protocol | PCIe | |
| | Form Factor | M.2 | |
| | Controller | NVMe | |
| | NAND Type | 3D TLC | |
| | Endurance | 500TBW (TB Written) | |
| | Reliability | 1.5M hours | |
| | Rated for 24/7/365 operation | No | |
| | Interface | PCI Express 4.0 x4 electrical | |
| | Operating Temperature | 32° to 158° F (0° to 70° C) | |
| | Performance | Sequential Read | up to 6500MB/s* |
| | | Sequential Write | up to 5000MB/s* |
| | | Random Read | up to 800K IOPS* |
| Random Write | | up to 800K IOPS* | |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | |
|--|--------------------|------|
| HP Z Turbo Drive Dual Pro 4TB SSD | Capacity | 4TB |
| | Protocol | PCIe |
| | Form Factor | M.2 |

Technical Specifications - Hard Drives

| | | |
|-------------------------------------|-------------------------------|------------------|
| Controller | NVMe | |
| NAND Type | 3D TLC | |
| Endurance | 500TBW (TB Written) | |
| Reliability | 1.5M hours | |
| Rated for 24/7/365 operation | No | |
| Interface | PCI Express 4.0 x4 electrical | |
| Operating Temperature | 32° to 158° F (0° to 70° C) | |
| Performance | Sequential Read | up to 6500MB/s* |
| | Sequential Write | up to 5000MB/s* |
| | Random Read | up to 800K IOPS* |
| | Random Write | up to 800K IOPS* |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

NOTE: available in June 2023

SATA Hard Drives for HP Workstations

1TB 7200RPM SATA 3.5in Enterprise HDD

| | | |
|--|-----------------------------------|----------------|
| Capacity | 1TB | |
| Protocol | SATA | |
| Form Factor | 3.5" | |
| Controller | AHCI | |
| Reliability | 2.0M hours | |
| Rated Power On Hours | 8760/yr | |
| Annualized Failure Rate (based on Rated POH) | <0.62% | |
| Rated for 24/7/365 operation | YES | |
| Height | 1 in; 2.54 cm | |
| Width | Media Diameter | 3.5 in; 8.9 cm |
| | Physical Size | 4 in; 10.17 cm |
| Interface | Serial ATA (6.0Gb/s), NCQ enabled | |
| Synchronous Transfer Rate (Maximum) | Up to 600MB/s * | |
| Buffer | 128MB | |
| Cache | Adaptive | |
| Seek Time (typical reads, includes controller overhead, including settling) | Single Track | 0.32 ms * |
| | Average | 7.45 ms * |
| | Full Stroke | 14.2 ms * |
| Rotational Speed | 7,200 rpm | |
| Logical Blocks | 1,953,525,168 | |
| Operating Temperature | 41° to 131° F (5° to 55° C) | |
| Performance | Sequential Read | up to 226MB/s* |
| | Sequential Write | up to 226MB/s* |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

2TB 7200RPM SATA 3.5in

Capacity 2TB

Technical Specifications - Hard Drives

Enterprise HDD

| | | |
|--|-----------------------------------|----------------|
| Protocol | SATA | |
| Form Factor | 3.5" | |
| Controller | AHCI | |
| Reliability | 2.0M hours | |
| Rated Power On Hours | 8760/yr | |
| Annualized Failure Rate (based on Rated POH) | <0.62% | |
| Rated for 24/7/365 operation | YES | |
| Height | 1 in; 2.54 cm | |
| Width | Media Diameter | 3.5 in; 8.9 cm |
| | Physical Size | 4 in; 10.17 cm |
| Interface | Serial ATA (6.0Gb/s), NCQ enabled | |
| Synchronous Transfer Rate (Maximum) | Up to 600MB/s * | |
| Buffer | 128MB | |
| Cache | Adaptive | |
| Seek Time (typical reads, includes controller overhead, including settling) | Single Track | 0.7 ms * |
| | Average | 8.5 ms * |
| | Full Stroke | 15.7 ms * |
| Rotational Speed | 7,200 rpm | |
| Logical Blocks | 3,907,029,168 | |
| Operating Temperature | 41° to 131° F (5° to 55° C) | |
| Performance | Sequential Read | up to 226MB/s* |
| | Sequential Write | up to 226MB/s* |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

4TB 7200 RPM SATA 3.5in Capacity

Enterprise HDD

| | | |
|---|-----------------------------------|----------------|
| Capacity | 4TB | |
| Protocol | SATA | |
| Form Factor | 3.5" | |
| Controller | AHCI | |
| Reliability | 2.0M hours | |
| Rated Power On Hours | 8760/yr | |
| Annualized Failure Rate (based on Rated POH) | <0.62% | |
| Rated for 24/7/365 operation | YES | |
| Height | 1 in; 2.54 cm | |
| Width | Media Diameter | 3.5 in; 8.9 cm |
| | Physical Size | 4 in; 10.17 cm |
| Interface | Serial ATA (6.0Gb/s), NCQ enabled | |
| Synchronous Transfer Rate (Maximum) | Up to 600MB/s * | |
| Buffer | 256MB | |
| Cache | Adaptive | |

Technical Specifications - Hard Drives

| | | |
|--|-----------------------------|----------------|
| Seek Time (typical reads, includes controller overhead, including settling) | Single Track | 0.7 ms * |
| | Average | 8.5 ms * |
| | Full Stroke | 15.7 ms * |
| Rotational Speed | 7,200 rpm | |
| Logical Blocks | 7,814,037,168 | |
| Operating Temperature | 41° to 131° F (5° to 55° C) | |
| Performance | Sequential Read | up to 226MB/s* |
| | Sequential Write | up to 226MB/s* |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | |
|--|--|-----------------------------------|----------------|
| 8TB 7200RPM SATA 3.5in Enterprise HDD | Capacity | 8TB | |
| | Protocol | SATA | |
| | Form Factor | 3.5" | |
| | Controller | AHCI | |
| | Reliability | 2.0M hours | |
| | Rated Power On Hours | 8760/yr | |
| | Annualized Failure Rate (based on Rated POH) | <0.62% | |
| | Rated for 24/7/365 operation | YES | |
| | Height | 1 in; 2.54 cm | |
| | Width | Media Diameter | 3.5 in; 8.9 cm |
| | Physical Size | 4 in; 10.17 cm | |
| | Interface | Serial ATA (6.0Gb/s), NCQ enabled | |
| | Synchronous Transfer Rate (Maximum) | Up to 600MB/s * | |
| | Buffer | 256MB | |
| | Cache | Adaptive | |
| | Seek Time (typical reads, includes controller overhead, including settling) | Single Track | 0.7 ms * |
| | | Average | 8.5 ms * |
| | | Full Stroke | 15.7 ms * |
| | Rotational Speed | 7,200 rpm | |
| | Logical Blocks | 15,628,053,168 | |
| | Operating Temperature | 41° to 140° F (5° to 60° C) | |
| | Performance | Sequential Read | up to 226MB/s* |
| | | Sequential Write | up to 226MB/s* |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

| | | | |
|---|--------------------|------------|--|
| 12TB 7200 RPM SATA-6G 3.5in Enterprise HDD | Capacity | 12TB | |
| | Protocol | SATA | |
| | Form Factor | 3.5" | |
| | Controller | AHCI | |
| | Reliability | 2.0M hours | |

Technical Specifications - Hard Drives

| | |
|--|--|
| Rated Power On Hours | 8760/yr |
| Annualized Failure Rate (based on Rated POH) | <0.62% |
| Rated for 24/7/365 operation | YES |
| Height | 1 in; 2.54 cm |
| Width | Media Diameter 3.5 in; 8.9 cm |
| | Physical Size 4 in; 10.17 cm |
| Interface | Serial ATA (6.0Gb/s), NCQ enabled |
| Synchronous Transfer Rate (Maximum) | Up to 600MB/s * |
| Buffer | 256MB |
| Cache | Adaptive |
| Seek Time (typical reads, includes controller overhead, including settling) | Single Track 0.7 ms * |
| | Average 8.5 ms * |
| | Full Stroke 15.7 ms * |
| Rotational Speed | 7,200 rpm |
| Logical Blocks | 23,437,770,752 |
| Operating Temperature | 41° to 140° F (5° to 60° C) |
| Performance | Sequential Read up to 226MB/s* |
| | Sequential Write up to 226MB/s* |

*Actual performance may vary.

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36GB of system disk (for Windows) is reserved for system recovery software.

Technical Specifications - Graphics

GRAPHICS

| | | |
|-----------------------------------|-----------------------------------|---|
| NVIDIA® RTX™ 6000 Ada 48GB | Form Factor | Full-Height Dual Slot (4.4" Height x 10.5" Length) Weight: 1230 grams / 2.71 lbs (with extender) |
| | Max Power Consumption | Power: 300 Watts Cooling: Active |
| | GPU Memory | 48GB GDDR6 memory ECC Memory Bandwidth: Up to 960 GB/s Memory Width: 384 bits |
| | Connectors | 4x DisplayPort 1.4a Quadro Sync II connector Stereo Sync Requires CEM 5.0 16-pin auxiliary power adapter |
| | Maximum Resolution | 7680x4320 @ 120Hz |
| | Bus Type | PCI Express 4.0 x16 |
| | Available Graphics Drivers | Windows 11 Windows 10 Linux® 64-bit |

| | | |
|--------------------------------|-----------------------------------|---|
| NVIDIA® RTX™ A6000 48GB | Form Factor | Full-Height Dual Slot (4.4" Height x 10.5" Length) Weight: 1230 grams / 2.71 lbs (with extender) |
| | Max Power Consumption | Power: 300 Watts Cooling: Active |
| | GPU Memory | 48GB GDDR6 memory ECC optional Memory Bandwidth: Up to 768 GB/s Memory Width: 384 bit |
| | Connectors | 4x DisplayPort 1.4a Quadro Sync II connector NVLink® Stereo Sync Requires 8-pin auxiliary power |
| | Maximum Resolution | 7680x4320 @ 120Hz |
| | Bus Type | PCI Express 4.0 x16 |
| | Available Graphics Drivers | Windows 11 Windows 10 Linux® 64-bit |

| | | |
|--------------------------------|------------------------------|---|
| NVIDIA® RTX™ A5000 24GB | Form Factor | Full-Height Dual Slot (4.4" Height x 10.5" Length) Weight: 1049 grams + 80 grams extender |
| | Max Power Consumption | Power: 230W Cooling: Active |
| | GPU Memory | 24GB GDDR6 memory ECC optional Memory Bandwidth: Up to 768 GB/s Memory Width: 384 bit |
| | Connectors | 4x DisplayPort 1.4a Quadro Sync II connector NVLink® Stereo Sync Requires 8-pin auxiliary power |
| | Maximum Resolution | 7680x4320 @ 120Hz |

Technical Specifications - Graphics

| | |
|-----------------------------------|---|
| Bus Type | PCI Express 4.0 x16 |
| Available Graphics Drivers | Windows 11 Windows 10 Linux® 64-bit |

NVIDIA® RTX A4500 20GB

| | |
|-----------------------------------|---|
| Form Factor | Full-Height Dual Slot (4.4" Height x 10.5" Length) Weight: 1049 grams + 80 grams extender |
| Max Power Consumption | Power: 200W Cooling: Active |
| GPU Memory | 20GB GDDR6 memory Memory Bandwidth: Up to 640 GB/s Memory Width: 320 bit |
| Connectors | 4x DisplayPort 1.4a Quadro Sync II connector NVLink® Stereo Sync Requires 8-pin auxiliary power |
| Maximum Resolution | 7680x4320 @ 120Hz |
| Bus Type | PCI Express 4.0 x16 |
| Available Graphics Drivers | Windows 11 Windows 10 Linux® 64-bit |

NVIDIA® RTX A4000 16GB

| | |
|-----------------------------------|--|
| Form Factor | Full-Height Single Slot (4.4" Height x 9.5" Length) Weight: 500 grams |
| Max Power Consumption | Power: 140W Cooling: Active |
| GPU Memory | 16GB GDDR6 memory Memory Bandwidth: Up to 448 GB/s Memory Width: 256 bit |
| Connectors | 4x DisplayPort 1.4a Quadro Sync II connector Stereo Sync Requires 6-pin auxiliary power |
| Maximum Resolution | 7680x4320 @ 120Hz |
| Bus Type | PCI Express 4.0 x16 |
| Available Graphics Drivers | Windows 11 Windows 10 Linux® 64-bit |

NVIDIA® RTX A2000 12GB

| | |
|------------------------------|--|
| Form Factor | Half-Height Dual Slot (2.713" Height x 6.6" Length) Weight: 306 grams |
| Max Power Consumption | Power: 70W Cooling: Active |
| GPU Memory | 12GB GDDR6 memory Memory Bandwidth: Up to 288 GB/s Memory Width: 192 bit |
| Connectors | 4x mini-DisplayPort 1.4a |
| Maximum Resolution | 7680x4320 @ 120Hz |

Technical Specifications - Graphics

| | |
|-----------------------------------|---|
| Bus Type | PCI Express 4.0 x16 |
| Available Graphics Drivers | Windows 11 Windows 10 Linux® 64-bit |

| | | |
|--------------------------|-----------------------------------|--|
| NVIDIA® T1000 8GB | Form Factor | Half-Height Single Slot (2.713” Height x 6.137” Length) Weight: 132.6 grams |
| | Max Power Consumption | Power: 50W Cooling: Active |
| | GPU Memory | 8GB GDDR6 memory Memory Bandwidth: Up to 160 GB/s Memory Width: 128 bit |
| | Connectors | 4x mini-DisplayPort 1.4a |
| | Maximum Resolution | 7680x4320 @ 120Hz |
| | Bus Type | PCI Express 3.0 x16 |
| | Available Graphics Drivers | Windows 11 Windows 10 Linux® 64-bit |

| | | |
|--------------------------|-----------------------------------|--|
| NVIDIA® T1000 4GB | Form Factor | Half-Height Single Slot (2.713” Height x 6.137” Length) Weight: 132.6 grams |
| | Max Power Consumption | Power: 50W Cooling: Active |
| | GPU Memory | 4GB GDDR6 memory Memory Bandwidth: Up to 160 GB/s Memory Width: 128 bit |
| | Connectors | 4x mini-DisplayPort 1.4a |
| | Maximum Resolution | 7680x4320 @ 120Hz |
| | Bus Type | PCI Express 3.0 x16 |
| | Available Graphics Drivers | Windows 11 Windows 10 Linux® 64-bit |

| | | |
|----------------------------------|-----------------------------------|--|
| NVIDIA® T400 4GB Graphics | Form Factor | Half-Height Single Slot (2.713” Height x 6.137” Length) Weight: 123.5 grams |
| | Max Power Consumption | Power: 30W Cooling: Active |
| | GPU Memory | 4GB GDDR6 memory Memory Bandwidth: Up to 80 GB/s Memory Width: 64 bit |
| | Connectors | 3x mini-DisplayPort 1.4a |
| | Maximum Resolution | 7680x4320 @ 120Hz |
| | Bus Type | PCI Express 3.0 x16 |
| | Available Graphics Drivers | Windows 11 Windows 10 Linux® 64-bit |

Technical Specifications - Graphics

| | | |
|--|--|--|
| AMD® Radeon™ Pro W6800 32GB | Form Factor | Full-Height Dual Slot (4.4" Height x 10.5" Length) Weight: 850 grams |
| | Max Power Consumption | Power: 261W Cooling: Active |
| | GPU Memory | 32GB GDDR6 memory Memory Bandwidth: Up to 512 GB/s Memory Width: 256 bit |
| | Connectors | 6x mini-DisplayPort 1.4 Requires 8-pin+6-pin auxiliary power |
| | Maximum Resolution | 7680x4320 @ 60Hz |
| | Bus Type | PCI Express 4.0 x16 |
| | Available Graphics Drivers | Windows 11 Windows 10 Linux® 64-bit |
| | AMD® Radeon™ RX 6700XT 12GB | Form Factor |
| Max Power Consumption | | Power: 238W Cooling: Active |
| GPU Memory | | 12GB GDDR6 memory Memory Bandwidth: Up to 384 GB/s Memory Width: 192 bit |
| Connectors | | 4x DisplayPort 1.4 1x HDMI Requires 8-pin+6-pin auxiliary power |
| Maximum Resolution | | 7680x4320 @ 60Hz |
| Bus Type | | PCI Express 4.0 x16 |
| Available Graphics Drivers | | Windows 11 Windows 10 Linux® 64-bit |
| AMD® Radeon™ Pro W6600 8GB | | Form Factor |
| | Max Power Consumption | Power: 122W Cooling: Active |
| | GPU Memory | 8GB GDDR6 memory Memory Bandwidth: Up to 224 GB/s Memory Width: 128 bit |
| | Connectors | 4x DisplayPort 1.4 Requires 6-pin auxiliary power |
| | Maximum Resolution | 7680x4320 @ 60Hz |
| | Bus Type | PCI Express 4.0 x16 (x8 electrical) |
| | Available Graphics Drivers | Windows 11 Windows 10 Linux® 64-bit |
| | AMD® Radeon™ RX 6400 4GB | Form Factor |

Technical Specifications - Graphics

| | |
|-----------------------------------|--|
| Max Power Consumption | Power: 50W Cooling: Active |
| GPU Memory | 4GB GDDR6 memory Memory Bandwidth: Memory Width: |
| Connectors | 1x DisplayPort 1.4a 1x HDMI |
| Maximum Resolution | 7680x4320 @ 60Hz |
| Bus Type | PCI Express 4.0 x4 |
| Available Graphics Drivers | Windows 11 Windows 10 Linux® 64-bit |

| | | |
|-------------------------------|-----------------------------------|---|
| Intel® Arc Pro A40 6GB | Form Factor | Half-Height Single Slot (2.7” Height x 6.6” Length) Weight: 220 grams |
| | Max Power Consumption | Power: 50W Cooling: Active |
| | GPU Memory | 4GB GDDR6 memory Memory Bandwidth: 192GB Memory Width: 96 bit |
| | Connectors | 4x mini- DisplayPort 1.4 |
| | Maximum Resolution | 7680x4320 @ 60Hz |
| | Bus Type | PCI Express 4.0 x8 |
| | Available Graphics Drivers | Windows 11 Windows 10 |

Notes for all graphics cards:

- Some graphics and GPU compute cards can consume a great deal of power, thus combinations of cards with other components may exceed a particular power supply's output capability.
- Some graphics and GPU compute cards require supplemental power cables.
- Not all chassis/PSU configurations have enough supplemental power cables of the correct type for all graphics configurations.

Refer to the Power Supply section within Overview for more information.

Technical Specifications - Optical and Removable Storage

OPTICAL AND REMOVABLE STORAGE

| | | |
|-------------------------------------|---|---|
| HP 9.5mm Slim Blu-Ray Writer | Description | 9.5mm height, tray-load |
| | Mounting Orientation | Either horizontal or vertical |
| | Interface Type | SATA/ATAPI |
| | Dimensions (WxHxD) | 128 x 9.5 x 127mm |
| | Supported Media Types | BD-ROM BD-R BD-RE DVD+R DVD+RW DVD+R DL DVD-R DL DVD-R DVD-RW CD-R CD-RW |
| | Disc Capacity | DVD-ROM 8.5 GB DL or 4.7 GB standard Blu-ray 25 GB (single-layer) 50 GB (dual-layer) 100/128 GB (BDXL) |
| | | Full Stroke DVD < 230 ms (seek) |
| | | Full Stroke CD < 220 ms (seek) |
| | | Blu-ray < 230 ms (seek) (Full Stroke Blu-ray) |
| | | Startup Time (Time to drive ready from tray loading) BD-ROM (SL/DL) 25S / 28S BD-R (SL/DL) 25S / 28S BD-RE (SL/DL) 25S / 28S DVD-ROM (SL/DL) 18S / 18S DVD-R (SL/DL) 25S / 25S DVD-RW 25S DVD+R (SL/DL) 25S / 25S DVD+RW 25S CD-ROM 15S |
| Maximum Data Transfer Rates | CD ROM Read CD-ROM, CD-R Up to 24X CD-RW Up to 24X | |
| | DVD ROM Read DVD+RW Up to 8X DVD-RW Up to 8X DVD+R DL Up to 8X DVD-R DL Up to 8X DVD-ROM Up to 8X DVD-ROM DL Up to 8X DVD+R Up to 8X DVD-R Up to 8X | |
| | Blu-ray BD-ROM Up to 6X BD-ROM DL Up to 6X BD-R Up to 6X BD-R DL Up to 6X BD-RE SL/DL Up to 6X | |

Technical Specifications - Optical and Removable Storage

| | | |
|---|--|---------------------------------------|
| Power | Source | SATA DC power receptacle |
| | DC Power Requirements | 5 VDC ± 5%-100 mV ripple p-p |
| | DC Current | 5 VDC -900 mA typical, 2000mA maximum |
| Operating Environmental (all conditions non-condensing) | Temperature | 41° to 122° F (5° to 50° C) |
| | Relative Humidity | 10% to 80% |
| | Maximum Wet Bulb Temperature | 84° F (29° C) |
| Operating Systems Supported | Windows 11, Windows 10, Windows 7 Professional 64-bit, Red Hat® Enterprise Linux® (RHEL) 8, 9 Desktop/Workstation, SUSE Linux® Enterprise Desktop 15, Ubuntu 20.04, 22.04 LTS | |
| | No driver is required for this device. Native support is provided by the operating system. | |
| Kit Contents | 9.5mm Slim BDXL Blu-Ray Writer, 5.25" ODD Bay adapter/carrier, slim SATA data/power cable, installation guide As Blu-ray is a new format containing new technologies, certain disc, digital connection, compatibility and/or performance issues may arise, and do not constitute defects in the product. Flawless playback on all systems is not guaranteed. In order for some Blu-ray titles to play, they may require a DVI or HDMI digital connection and your display may require HDCP support. HD-DVD movies cannot be played on this workstation. | |
| | NOTE: HD-DVD disks cannot be played on the DVD-ROM drive. No support for DVD-RAM. Actual speeds may vary. Don't copy copyright-protected materials. Double Layer discs can store more data than single layer discs. Discs burned with this drive may not be compatible with many existing single-layer DVD drives and players. Flawless playback on all systems is not guaranteed. | |

HP 9.5mm Slim DVD Writer

| | | |
|------------------------------------|---|--|
| Description | 9.5mm height, tray-load | |
| Mounting Orientation | Either horizontal or vertical | |
| Interface Type | SATA/ATAPI | |
| Dimensions (WxHxD) | 128 x 9.5 x 127mm | |
| Supported Media Types | DVD+R DVD+RW DVD+R DL DVD-R DL DVD-R DVD-RW CD-R CD-RW | |
| Disc Capacity | DVD-ROM | 8.5 GB DL or 4.7 GB standard |
| | Full Stroke DVD | < 200 ms (seek) |
| | Full Stroke CD | < 200 ms (seek) |
| Maximum Data Transfer Rates | CD ROM Read | CD-ROM, CD-R Up to 24X CD-RW Up to 24X |
| | DVD ROM Read | DVD+RW Up to 8X DVD-RW Up to 8X DVD+R DL Up to 8X DVD-R DL Up to 8X |

Technical Specifications - Optical and Removable Storage

DVD-ROM Up to 8X
 DVD-ROM DL Up to 8X
 DVD+R Up to 8X
 DVD-R Up to 8X

| | | |
|---|--|---|
| Power | Source | SATA DC power receptacle |
| | DC Power Requirements | 5 VDC ± 5%-100 mV ripple p-p |
| | DC Current | 5 VDC -< 800 mA typical, <1600 mA maximum |
| Operating Environmental (all conditions non-condensing) | Temperature | 41° to 122° F (5° to 50° C) |
| | Relative Humidity | 10% to 80% |
| | Maximum Wet Bulb Temperature | 84° F (29° C) |
| Operating Systems Supported | Windows 11, Windows 10, Windows 7 Professional 64-bit, Windows Vista Business 64*, Windows 2000. Red Hat® Enterprise Linux® (RHEL) 8, 9 Desktop/Workstation SUSE Linux® Enterprise Desktop 15 Ubuntu 20.04, 22.04 LTS | |

* No driver is required for this device. Native support is provided by the operating system

Kit Contents HP SATA DVD Writer drive, installation guide.

NOTE: Actual speeds may vary. No support for DVD-RAM (DVD Writer). Does not permit copying of commercially available DVD movies or other copyright protected materials. Intended for creation and storage of your original material and other lawful uses. Double Layer discs can store more data than single layer discs. However, double-layer discs burned with this drive may not be compatible with many existing single-layer DVD drives and players.

Technical Specifications - Optical and Removable Storage

| | | | |
|------------------------------|---|--|---|
| HP 9.5mm Slim DVD-ROM | Description | 9.5mm height, tray-load | |
| | Mounting Orientation | Either horizontal or vertical | |
| | Interface Type | SATA/ATAPI | |
| | Dimensions (WxHxD) | 128 x 9.5 x 127mm | |
| | Disc Capacity | DVD-ROM Single layer: Up to 4.7 GB Double layer: Up to 8.5 GB | |
| | Access Times | DVD-ROM Single Layer | < 110 ms (typical) |
| | | CD-ROM Mode 1 | < 110 ms (typical) |
| | | Full Stroke DVD | < 230 ms (typical) |
| | | Full Stroke CD | < 220 ms (typical) |
| | Power | Source | SATA DC power receptacle |
| | | DC Power Requirements | 5 VDC ± 5%-100 mV ripple p-p |
| | | DC Current | 5 VDC -< 800 mA typical, <1600 mA maximum |
| | Operating Environmental (all conditions non-condensing) | Temperature | 41° to 122° F (5° to 50° C) |
| | | Relative Humidity | 10% to 80% |
| | | Maximum Wet Bulb Temperature | 84° F (29° C) |
| | Operating Systems Supported | Windows 11, Windows 10, Windows 8.1, Windows 7 Professional 64-bit Red Hat® Enterprise Linux® (RHEL) 8, 9 Desktop/Workstation SUSE Linux® Enterprise Desktop 15 Ubuntu 20.04, 22.04 LTS | |
| | | No driver is required for this device. Native support is provided by the operating system. | |
| | Kit Contents | 9.5mm Slim DVD-ROM Drive, 5.25" ODD Bay adapter/carrier, slim SATA data/power cable, installation guide | |

NOTE: Actual speeds may vary. No support for DVD-RAM (DVD Writer). Does not permit copying of commercially available DVD movies or other copyright protected materials. Intended for creation and storage of your original material and other lawful uses. Double Layer discs can store more data than single layer discs. However, double-layer discs burned with this drive may not be compatible with many existing single-layer DVD drives and players.

Technical Specifications - Networking and Communications

NETWORKING AND COMMUNICATIONS

| | | |
|---|------------------------------|---|
| NVIDIA® Mellanox® ConnectX-6 DX Dual Port 10/25GbE SFP28 NIC | Connector | 2 x SFP28 Transceiver Cage (Dual Port)* |
| | Cabling | Depends on transceiver pairing. Typically OM4 or higher MMF LC fiber optic cabling with LC SFP28 Transceivers. |
| | Controller | ConnectX6-DX |
| | Memory | 256Mbit SPI Quad Flash Device |
| | Data Rates Supported | 1/10/25GbE |
| | Compliance | <ul style="list-style-type: none"> – IEEE 802.3by 25 Gigabit Ethernet – IEEE 802.3ae 10 Gigabit Ethernet – IEEE 802.3ap based auto-negotiation and KR startup – IEEE 802.3ad, 802.1AX Link Aggregation – IEEE 802.1Q, 802.1P VLAN tags and priority – IEEE 802.1Qau (QCN) – Congestion Notification – IEEE 802.1Qaz (ETS) – IEEE 802.1Qbb (PFC) – IEEE 802.1Qbg – IEEE 1588v2 – Jumbo frame support (9.6KB) – Safety: CB/cTUVus/CE – EMC: CE/FCC/VCCI/RCM – RoHS Compliant – KCC – CAN ICES-3 (B) – NM EN 55035/55032 (Morocco) – UKCA |
| | Bus Architecture | PCIe Gen 4 x8 |
| | Data Transfer Mode | PCI Express - stores and accesses Ethernet fabric connection information and packet data |
| | Power Requirements | 11.5 Watts (typical) |
| | Network Transfer Rate | 1Gbps, 10Gbps, 25Gbps |

NOTE: Network Transfer Rate depends on transceiver model.*

Kit Contents NVIDIA® Mellanox® ConnectX-6 DX Dual Port 10/25GbE SFP28 NIC

*3rd party transceivers sold separately. You must have a transceiver installed in order to connect this card to a network.

| | | |
|--|-----------------------------|--|
| Intel® X550 10GBASE-T Dual Port NIC | Connector | 2 x RJ-45 |
| | Cabling | Cat5 (or higher) for 100Mbps Cat5e (or higher) for 1Gbps, 2.5Gbps, or 5Gbps Cat6 (or higher) for 10Gbps up to 55m Cat6a (or higher) for 10Gbps up to 100m |
| | Controller | Intel X550-AT2 |
| | Memory | Jumbo Frames up to 15.5KB, 64 Tx and 64Rx Queues per port, 160KB/port of programmable memory transmit buffers |
| | Data Rates Supported | 100Mbps (BASE-TX), 1Gbps (BASE-T, 2.5Gbps, 5Gbps, 10Gbps) |
| | Compliance | 802.1q (VLAN), 802.1Qbb, 802.1p, 802.1Qaz |
| Bus Architecture | PCIe 3x4 | |

Technical Specifications - Networking and Communications

| | |
|--------------------------------|--|
| Data Transfer Mode | PCIe Gen 3 x4 based interface |
| Power Requirements | 3.9W at 100Mbps 5.5W at 1Gbps 11.2W at 10Gbps |
| Boot ROM Support | Yes |
| Network Transfer Mode | Auto negotiation between 1GbE, 2.5GbE, 5GbE and 10GbE |
| Management Capabilities | DMI 2.0 Support, Windows Management Instrumentation (WMI) and SNMP, PXE 2.0 through boot ROM, Multi-mode I/O Virtualization, VxLAN, VMDq, VLAN support with VLAN tag insertion |
| Kit Contents | Intel® X550 10GBASE-T Dual Port NIC |

Intel® I225-T1 Single Port 2.5GbE PCIe NIC

| | |
|--------------------------------|---|
| Connector | RJ-45 (Single Port) |
| Cabling | Cat5e (or better) up to 100m |
| Controller | Intel® Ethernet I225 Controller |
| Memory | Jumbo Frames up to 9.5KB, 4 Tx and Rx Queues, |
| Data Rates Supported | 2.5GbE, 1GbE, 100MbE, 10MbE |
| Compliance | IEEE 802.3 auto negotiation, 802.3x, 802.3z |
| Bus Architecture | PCIe Gen 3.1x1 |
| Data Transfer Mode | PCIe-based interface for active state operation |
| Power Requirements | 1.9 Watts (typical) |
| Management Capabilities | WOL, PXE 2.1, Power Management Protocol Offload (proxying), MAC Power Management, Active State Power Management, |
| Kit Contents | Intel® I225-T1 1-Port 2.5GbE NIC with standard height bracket attached and Low-profile bracket included Product Literature |

Intel® Ethernet I350-T4 V2 4-Port 1Gb NIC

| | |
|--------------------------------|---|
| Connector | 4x RJ-45 (Quad Port) |
| Cabling | Cat3 (or higher) for 10Mbps Cat5 (or higher) for 100Mbps Cat5e (or higher) for 1Gbps up to 100m |
| Controller | Intel® I350 |
| Memory | Jumbo Frames up to 9.5KB, 8 Tx/Rx Queue pairs per port, Main Internal memory is Error Code Correcting |
| Data Rates Supported | 10Mbps, 100Mbps, 1Gbps |
| Compliance | IEEE 802.3 auto negotiation, 802.3, 802.3u, 802.3ab, 802.3x, 802.3z, IEEE1588 protocol and 802.1AS implementation, 802.3az EEE |
| Bus Architecture | PCI Express 2.1 x4 |
| Data Transfer Mode | PCIe-based interface for active state operation |
| Power Requirements | 5W |
| Network Transfer Mode | Multi-speed, full, and half-duplex |
| Network Transfer Rate | 10BASE-T 100BASE-Tx 1000BASE-T |
| Management Capabilities | WOL, PXE 2.1, UEFI, Power Management Protocol Offload (proxying), MAC Power Management, Active State Power Management, VLAN, ACPI |
| Kit Contents | Intel® Ethernet I350-T4V2 4-Port 1Gb NIC with full-height bracket installed |

Technical Specifications - Networking and Communications

Low-profile bracket included

| | | |
|---|--------------------------------|--|
| Allied Telesis AT-2911T/2-901 Dual Port 1GbE NIC | Connector | 2 x RJ-45 (Dual Port) |
| | Cabling | Cat3 (or higher) for 10Mbps Cat5 (or higher) for 100Mbps Cat5e (or higher) for 1Gbps up to 100m |
| | Memory | 17 Rx and 16 Tx queues |
| | Data Rates Supported | 10/100/1000 Mbps |
| | Compliance | IEEE 802.1p (Quality of Service), IEEE 802.1Q (VLANs), IEEE 802.2 (LLC), IEEE 802.3ac (MAC), IEEE 802.3x (Flow control auto-negotiation), IEEE 802.3z (1000 Base-X), IEEE 802.3ad (Link aggregation), IEEE 802.3ab (10/100/1000T) RoHS, UL, FCC/EN55022 Class A, TUV, EN55024, CE, C-TICK, VCCI |
| | Bus Architecture | PCIe 2x1 |
| | Data Transfer Mode | PCIe-based interface |
| | Power Requirements | 2.4 Watts (typical) |
| | Management Capabilities | VLAN support, Link aggregation LACP, Link aggregation smart switch, Failover, Smart Load Balancing (SLB), iSCSI boot support, Windows Management Instrumentation (WMI), PXE 2.1, SNMP |
| | Kit Contents | Allied Telesis AT-2911T/2-901 Dual Port 1GbE NIC with low-profile bracket attached and standard bracket included |

| | | |
|---|---|---|
| Allies Telesis AT-2914SX/LC 1GB LC Fiber NIC | Connector | LC Fiber (Single Port) |
| | Cabling | 50/125 μm (core/cladding) multimode fiber optic cable up to 500m 62.5/125 μm (core/cladding) multimode fiber optic cable up to 220m |
| | Memory | Jumbo Frames up to 9.6KB |
| | Data Rates Supported | 1000SX (1GbE Fiber at 850nm Wavelength) |
| | Compliance | IEEE 802.1p (Quality of Service), IEEE 802.1Q (VLANs), IEEE 802.2 (LLC), IEEE 802.3ac (MAC), IEEE 802.3x (Flow control auto-negotiation), IEEE 802.3z (1000 Base-X), IEEE 802.3ad (Link aggregation) RoHS, UL, FCC/EN55022 Class A, TUV, EN55024, CE, C-TICK, VCCI |
| | Bus Architecture | PCIe x1 |
| | Data Transfer Mode | PCIe-based interface |
| | Power Requirements | 1.5 Watts (typical) |
| | Network Transfer Rate | 1000SX only (1GbE Fiber at 850nm Wavelength) |
| | Management Capabilities | UEFI, Smart Load Balancing and failover, Link aggregation (IEEE802.3ad), Generic trunking (FEC/GEC) / IEEE 802.3ad-draft static, VLAN Support |
| Kit Contents | Allied Telesis AT-2914SX/LC 1GB LC Fiber NIC with low-profile bracket attached and standard height bracket included | |

| | | |
|-------------------------------|-----------------------------|--|
| HP 10GBase-T Flex Port | Connector | RJ-45 |
| | Cabling | Twisted Pair Cabling, up to 100 meter |
| | Controller | Marvell AQC113C |
| | Memory | 128KB Tx Buffer, 192KB Rx Buffer on-chip |
| | Data Rates Supported | 10/100/1000 Mbps and 2.5/5/10 Gbps |
| | Compliance | 802.3 - 2018, 802.1AS-2011 |

Technical Specifications - Networking and Communications

| | |
|--------------------------------|--|
| Bus Architecture | PCI Express and SMBus |
| Data Transfer Mode | PCIe-based interface for active state operation (S0 state) and SMBus for host and management traffic |
| Power Requirement | Requires 0.7V VDD, 1V, and 2V for analog, 3.3V for VDDIO |
| Boot ROM Support | Yes |
| Network Transfer Mode | Full-duplex |
| Network Transfer Rate | 10GBASE-T 5GBASE-T 2.5GBASE-T 1000BASE-T 100BASE-TX 10BASE-Te |
| Management Capabilities | WOL, PXE, UEFI, |
| Kit Contents | HP 10GBase-T Flex Port NIC Module |

| | | |
|--------------------------------|--------------------------------|---|
| HP 2.5GbE LAN Flex Port | Connector | RJ45 (Single Port) |
| | Cabling | Copper twisted pair, Cat5e up to 100 meters |
| | Controller | Intel® I225-V |
| | Memory | 4 Tx and 4 Rx Queues, Jumbo Frames up to 9KB and without TSN |
| | Data Rates Supported | 10/100/1000Mbps and 2.5Gbps BASE-T |
| | Compliance | IEEE 802.3, 802.3u (auto-negotiation), 802.3ab, 1588, 802.1AS-Rev, 802.1Qav, 802.1Qbu, 802.1Qbv, 802.3br, 802.3az |
| | Bus Architecture | PCIe G2x1 |
| | Data Transfer Mode | PCIe-based interface for active state operation (S0 state) and SMBus for host and management traffic (Sx low power state) |
| | Power Requirements | 2.2 Watts |
| | Network Transfer Mode | Automatic link configuration for speed duplex and flow control |
| | Network Transfer Rate | 2500BASE-T 1000BASE-T 100BASE-TX (Half-duplex supported) 10BASE-Te (Half-duplex supported) |
| | Management Capabilities | WOL, PXE, UEFI, Intel vPro® support with appropriate Intel Chipset, Error Correcting Memory in packet buffers, UDP/TCP/IP Checksum Offload, SCTP receive and transmit integrity offload |
| | Kit Contents | HP 2.5GbE LAN Flex Port Networking Interface Card |

| | | |
|--|--------------------------------|--|
| HP 1GbE Fiber LC Single Flex Port | Connector | LC (Little Connector) Fiber (Single Port) |
| | Cabling | LC Fiber Cabling |
| | Controller | AT-29M2 |
| | Data Rates Supported | 1GBASE-SX |
| | Bus Architecture | USB 3.1G1 |
| | Power Requirements | Up to 3.3 Watts |
| | Network Transfer Mode | 1GBASE-SX |
| | Network Transfer Rate | 1GBASE-SX |
| | Management Capabilities | Wake on LAN, Digital Diagnostic Monitoring |

Technical Specifications - Networking and Communications

Kit Contents HP 1GbE Fiber LC Single Flex Port NIC

| | | |
|-------------------------------------|------------------------------|--|
| HP Flex 1GbE Single Port NIC | Connector | RJ45 (Single Port) |
| | Cabling | 1GbE over Category 5e (or better) up to 100m |
| | Controller | Realtek RTL8153 |
| | Data Rates Supported | 10/100/1000 Mbps |
| | Bus Architecture | USB3.1G1, USB2 |
| | Power Requirements | Requires 3.3V (integrated regulators for core Vdc) |
| | Network Transfer Mode | Full-duplex; Half-duplex |
| | Network Transfer Rate | 10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps |
| Management Capabilities | Wake on LAN, PXE, UEFI | |
| Kit Contents | HP 1GbE Single Flex Port | |

| | | |
|---|--------------------------------|--|
| Intel® AX210 Wi-Fi 6 + Bluetooth® 5.2 Flex Port NIC with Internal Antennae | Connector | Wireless |
| | Cabling | N/A |
| | Controller | Intel® AX210 |
| | Data Rates Supported | Wi-Fi 6 (2.4GHz/5GHz) |
| | Compliance | Wi-Fi Alliance* Wi-Fi Alliance CERTIFIED 6, WiFi CERTIFIED a/b/g/n/ac, WMM, WMM-Power Save, WPA2, WPA3, Wi-Fi Direct, and Wi-Fi Agile Multiband IEEE WLAN Standard 802.11-2016, 802.11a, b, d, e, g, h, l, k, n, r, u, v, w, ac, and ax, Bluetooth® 5.2 |
| | Bus Architecture | PCIe G3x1 for WLAN, USB3.1G1 for BT |
| | Management Capabilities | Authentication Protocols: 802.1X EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0 - MSCHAPv2 (EAP-SIM, EAP-AKA, EAP-AKA') Encryption: 128-bit AES-CCMP, 256-bit AES-GCMP UEFI |
| | Kit Contents | Intel® AX210 Wi-Fi 6 + Bluetooth® 5.2 Flex Port NIC Installation Instructions |

* Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 (802.11 ax) is backwards compatible with prior 802.11 specs.

| | | |
|--|-------------------------------------|--|
| Intel® AX210 Wi-Fi 6E non-vPro + Bluetooth® 5.2 with External Antennae WLAN | Connector | Wireless |
| | Cabling | N/A |
| | Controller | Intel® AX210 |
| | Data Rates Supported | Wi-Fi 6e (2.4GHz/5GHz/6GHz) |
| | Compliance | Wi-Fi Alliance* Wi-Fi Alliance CERTIFIED 6, WiFi CERTIFIED a/b/g/n/ac, WMM, WMM-Power Save, WPA2, WPA3, Wi-Fi Direct, and Wi-Fi Agile Multiband IEEE WLAN Standard 802.11-2016, 802.11a, b, d, e, g, h, l, k, n, r, u, v, w, ac, and ax, Bluetooth® 5.2 |
| Bus Architecture | PCIe G3x1 for WLAN, USB3.1G1 for BT | |

Technical Specifications - Networking and Communications

Management Capabilities Authentication Protocols: 802.1X EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0 - MSCHAPv2 (EAP-SIM, EAP-AKA, EAP-AKA')
Encryption: 128-bit AES-CCMP, 256-bit AES-GCMP
UEFI

Kit Contents Intel® AX210 Wi-Fi 6 + Bluetooth® 5.2 PCIe NIC
External Dipole Antenna
Installation Instructions

*Wi-Fi 6E requires a Wi-Fi 6E router, sold separately to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported.

| Date of change: | Version History: | | Description of change: |
|-----------------|------------------|---------|--|
| March 1, 2023 | From v1 to v2 | Changed | Optical and Removable Storage, Networking and Communications sections and Changed Format |
| March 30, 2023 | From v2 to v3 | Changed | Image page 1 |
| April 1, 2023 | From v3 to v4 | Changed | Format |
| April 6, 2023 | From v4 to v5 | Changed | Processors section |

© 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Intel, Intel Core, Xeon, Pentium, Thunderbolt and vPro are trademarks of Intel Corporation in the U.S. and other countries. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. AMD is a trademark of Advanced Micro Devices, Inc. ENERGY STAR® is a registered trademark owned by the U.S. government. Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries. NVIDIA, NVS and Quadro and the NVIDIA logo are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Red Hat® is a registered trademark of Red Hat, Inc. in the United States and other countries. SD is a trademark or registered trademark of SD-3C in the United States, other countries or both. Bluetooth is a trademark of its proprietor used by HP Inc. under license.