

HP LaserJet 3390/3392 All-in-One series

Specifications



System features	
Functions	Black-and-white printing, black-and-white copying, black-and-white faxing, black-and-white and colour scanning
Print speed / processor / memory	
Print speed (black, normal quality, A4)	Up to 21 ppm
Processor type	Motorola Coldfire® v 4e
Processor speed	264 MHz
Standard memory	HP LJ 3392 AIO: 128 MB HP LJ 3390 AIO: 64 MB
Memory slots	HP LJ 3392 AIO: One 100-pin DIMM slot (with 64MB DIMM) HP LJ 3390 AIO: One available 100-pin DIMM slot
Maximum memory	192 MB
Printing system	
First page out (black, A4)	8.5 sec
Duty cycle (monthly, A4)	Up to 10000
Print quality (black, normal quality)	Up to 1200 x 1200 dpi
Duplex print options	Automatic (standard)
Standard printer languages	HP PCL 6, HP PCL 5e, HP Postscript Level 3 emulation
Copy system	

Copy speed (black, draft quality, A4)	Up to 21 cpm
Maximum number of copies	Up to 99
Copy resolution (black graphics)	Up to 600 x 600 dpi
Copier resize	25 to 400%
Scan system	
Scan type	Flatbed, ADF
Enhanced scanning resolution	Up to 19200 dpi
Optical scanning resolution	Up to 1200 dpi
Maximum scanning size	21.6 x 38.1 cm
Minimum scanning size	No minimum
Bit depth	24-bit
Color scanning	Yes
Gray scale levels	256
Scan file format	JPEG, TIF, BMP, GIF, PDF, PNG
Fax functionality	
Fax speed	33.6 Kbps (3 sec per page)
A4 pages held in memory	Up to 250 pages (4 MB)
Colour faxing	No
Auto-redialing	Yes
Fax delayed sending	Yes
Max nr. of broadcasting locations	119 locations
Paper handling / media	
Auto document feeder capacity	Standard, 50 sheets
Standard paper trays	HP LJ 3390 AIO: 2 HP LJ 3392 AIO: 3
Maximum number of paper trays	HP LJ 3390 AIO: 2 HP LJ 3392 AIO: 3

Media types supported	Paper (bond, colour, glossy, heavy, letterhead, light, plain, preprinted, prepunched, recycled, rough), envelopes, transparencies, labels, cardstock
Standard input capacity (sheets)	HP LJ 3390 AIO: Up to 250 HP LJ 3392 AIO: Up to 500
Maximum input capacity (sheets)	Up to 500
Standard output capacity (sheets)	Up to 125
Maximum output capacity (sheets)	Up to 125
Standard media sizes	A4, A5, B5, C5, C6, DL (ISO), postcard; automatic document feeder (ADF): A4, A5
Custom media sizes	Media input tray and priority slot: 76 x 127 to 216 x 356 mm; automatic document feeder (ADF): 127 x 127 to 216 x 381 mm
Recommended media weight	75 to 90 g/m ²
Paper handling	HP LJ 3390 AIO: 250-sheet input tray, single-sheet priority slot, 50-sheet automatic document feeder, optional 250-sheet input tray, 125-sheet output bin and straight-thru paper path HP LJ 3392 AIO: Two 250-sheet input trays, single-sheet priority slot, 50-sheet automatic document feeder, 125-sheet output bin and straight-thru paper path
Other technical information	
Standard connectivity	Built-in 10/100 wired Ethernet network connectivity with 1 RJ-45 port; Hi-Speed USB (compatible with USB 2.0 specifications) port
Compatible operating systems	Microsoft® Windows® 2000, XP (full solution); 98 SE, Me, XP-64, Server 2003, Linux (print driver only); Mac OS X v 10.3 and higher (full solution)
Compatible network operating systems	Via built-in 10/100 Ethernet connection (supports TCP/IP-based solutions): Microsoft® Windows NT® 4.0, 98, Me, 2000, XP, XP-64, Server 2003; Novell® NetWare NDPS services via TCP/IP only on 3.2, 4.2, 5.x, 6.x; HP Gateway (TCP/IP raw only) and Novell LPD gateway; Apple Mac OS X v 10.3 and later; Bonjour discovery supported; Red Hat Linux 6.x and later; SuSE Linux 6.x and later; HP-UX 10.20, 11.x; Solaris™ 2.5x, 2.6, 7, 8, 9, 10 (SPARC systems only); IBM AIX 3.2.5 and later; MPE-iX; Citrix MetaFrame; Windows Terminal Services
Minimum system requirements	Microsoft® Windows® 98 SE, Me, Server 2003: any Pentium® II processor or greater, 64 MB RAM, 10 MB hard disk space, SVGA 800 x 600 with 16-bit colour display (print driver only); Windows 2000, XP: any Pentium II processor (Pentium III or greater recommended), 128 MB RAM, 250 MB hard disk space, SVGA 800 x 600 with 16-bit colour display, Internet Explorer 5.5 or greater (full install), CD-ROM drive, Hi-Speed USB port or network port
Control panel	Intuitive control panel with 2-line, 16-character back lit display, alphanumeric

	buttons, menu and cancel controls, fax, copy and scan controls, speed-dial keys
Hard disk capacity	None
Power consumption	0 watt (off), 11 watts (Powersave), 15 watts (Standby), 355 watts (active); Typical Electricity Consumption (TEC): 2.81 kWh/Week
Power requirements	Input voltage 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz), 2.6 amp
Operating temperature range	15 to 32.5° C
Dimensions (W x D x H)	HP LJ 3390 AIO: 495 x 400 x 470 mm HP LJ 3392 AIO: 495 x 400 x 560 mm
Weight	HP LJ 3390 AIO: 17.8 kg HP LJ 3392 AIO: 21.8 kg
Warranty	One-year limited warranty