

APC NetShelter Rack PDU Advanced, Switched Metered Outlet, 3Phase, 11kW 400V 16A or 11.5kW 415V 20A, 48 Outlets, IEC309

APDU10250SM

Overview

Lead time Usually in Stock

Main

Colour	Black	
product or component type	PDU	
PDU type	Switched metered outlet	
Cord length	5.9 ft (1.8 m)	

Complementary

Input Voltage	415 V 3 phases 400 V 3 phases
Height	58.7 in (149.0 cm)
Width	2.2 in (5.6 cm)
Output Voltage	240 V
Depth	3.0 in (7.5 cm)
net weight	17.0 lb(US) (7.7 kg)
mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 20 A 3P + N + PE
mounting mode	Rack-mounted
Rack units	OU
Mounting position	Vertical
Communication port protocol	1000BASE-T 10/100BASE-T
[In] rated current	16 A
Permissible voltage	200240 V 346415 V
Input current limits	20 A
Load capacity	11500 VA
Network frequency	50/60 Hz
Outlet type and quantity	24 C13/C15/C19/C21 C13/C15

Environment

Product certifications	TAA compliance	
	UKCA	
Standards	UL 62368-1	
	CSA C22.2 No 62368-1	
	FCC part 15 Subpart B	
	CE	
	EN 62368-1	
IP degree of protection	IP44	
Ambient air temperature for operation	23.0000000000140.0000000000 °F (-560 °C)	
Relative humidity	595 %	
Operating altitude	010000 ft	
Ambient air temperature for storage	-13.0000000000149.0000000000 °F (-2565 °C)	
Storage Relative Humidity	595 %	•
Storage altitude	050000 ft (0.000000000015240.0000000000 m)	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	67.7 in (172 cm)
Package 1 Width	4.6 in (11.6 cm)
Package 1 Length	8.2 in (20.8 cm)
Package 1 Weight	21.4 lb(US) (9.7 kg)

Contractual warranty

Warranty 3 years repair or replace



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Reach Free Of Svhc



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information