Specifications



APC Back-UPS Pro, 1350VA/ 810W, Tower, 120V, 10x NEMA 5-15R outlets, Sine Wave, AVR, USB Type A + C ports, LCD, User Replaceable Battery

BR1350MS

Overview

Lead time

Usually in Stock

Main

wan	
Main Input Voltage	120 V
Main Output Voltage	120 V
Rated power in W	810 W
Rated power in VA	1350 VA
product or component type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA
output connection type	6 NEMA 5-15R 4 NEMA 5-15R surge
Cable length	6 ft (1.8 m)
Number of cables	1
Battery type	Lead-acid battery

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph 🖸
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	16 h
Number of battery replacement quantity	2
Battery charger power	10 W rated
Battery life	35 year(s)
Replacement battery	APCRBC161
Extended runtime	0

General

Provided equipment	coaxial cable user manual USB cable
product web sub-family	Gaming performance

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

5	
Height	10.2 in (26 cm)
Width	3.9 in (10 cm)
Depth	14.5 in (36.8 cm)
net weight	25.8 lb(US) (11.7 kg)
Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	60 Hz +/- 3 Hz
Input voltage limits	88147 V
Maximum input current	12 A
Switching current capacity	15 A

Output

Maximum configurable power in W	810 W
Output frequency	60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Sine wave
Maximum configurable power in VA	1350 VA
Transfer time	8 ms typical : 10 ms maximum

Conformance

Comormanoc	
Product certifications	ENERGY STAR V2.0 (USA) NOM TUV C-US certified
Equipment protection policy	Lifetime : \$500000

Environmental

Ambient air temperature for operation	32.000000000104.0000000000 °F (040 °C)	
Relative humidity	095 % non-condensing	
Operating altitude	010000 ft	
Ambient air temperature for storage	5.000000000104.0000000000 °F (-1540 °C)	
Storage Relative Humidity	095 % non-condensing	
Storage altitude	010000 ft (0.0000000003048.000000000 m)	
Acoustic level	45 dBA	

Communications & Management

control panel Multifunction LCD status and control console

Surge Protection and Filtering

Surge energy rate	1080 J
Noise suppression	Full time multi-pole noise filtering : 5% of IEEE surge let-through : zero clamping
	response time: instantaneous

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.12 in (35.87 cm)
Package 1 Width	19.0 in (48.2 cm)
Package 1 Length	8.8 in (22.3 cm)
Package 1 Weight	29.3 lb(US) (13.3 kg)
SCC14	10731304335396

Contractual warranty

Warranty

3 years repair or replace

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Mercury Free

Rohs Exemption Information

Environmental Certifications

Energy Star®

ENERGY STAR UPS V2.0 (USA)

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information