

Protect It! 3-Outlet Surge Protector with Mounting Brackets, 10 ft. Cord, 510 Joules, 2 USB Charging Ports, Black Housing

MODEL NUMBER: TLP310USBS



Specifications

OUTPUT	
Charging Ports / Amps	(2) 3A / 2A / 1.5A
Frequency Compatibility	60 Hz
Output Receptacles	(4) 5-15R
Circuit Breaker (amps)	15
Right-Angle Outlets	No
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	120V
Input Connection Type	NEMA 5-15P input plug
Input Plug Features	120V, 15A
Input Cord Length (ft.)	10
Input Cord Length (m)	3.05
Input Cord Length Details	Strip
Voltage Compatibility (VAC)	120
Right-Angle Plug	No



SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	510	
AC Suppression Response Time	< 1ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	
Clamping Voltage (RMS)	1000	
UL1449 Let Through Rating	1000	
Immunity	Conforms to IEE 587/ANSI C62.41	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Unit Dimensions (hwd / in.)	2.2 x 7.24 x 1.54	
Unit Dimensions (hwd / cm)	5.59 x 18.39 x 3.91	
Material of Construction	Plastic	
Housing Color	Black	
Receptacle Color	Black	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449, UL962A	
Approvals	RoHS	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$20,000 Ultimate Lifetime Insurance	

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies