

4XEM's 140W Wall Charger Quintuple Output w/ display

4XEM Part- 4XGAN016140WB



4XEM's 140W USB-C Charger offers amazing charging power and speed with five USB ports capable of charging a variety of devices simultaneously. USB-A has long been a standard port allowing for charging or power to legacy and current devices; however, USB-C is rapidly becoming a new standard for charging devices, allowing for up to 140W charging for power at faster speeds. This device features 3x USB-C ports and 2x USB-A port. Keep your USB devices charged on the go or at home reliably with 4XEM's USB-C and A Charger.

Problem it solves: Charge one to three USB devices with reliable power and speed using 4XEM's 140W GaN Charger.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com



Features:

- 140-Watt power budget
- 3x USB-C port
- 2x USB-A port
- Wall mounted charger
- Compatible with any USB charged device
- Compact travel size
- Rounded edges
- Fast Charging
- Power Output Display Hub

Applications:

- Home
- Office
- Travel
- Meetings
- Classrooms
- Quick Charging



4XEM Products Are Available At Your Favorite Online Retailers





DATA SHEET

Warranty Information	Warranty	1 Year
Connector(s)	Charging Port(s)	3x USB Type-C Female 2x USB Type-A Female
	Power Source	Non-Polarized NEMA 1-15P (Standard NA Wall Outlet) Fixed with Retractable Prongs
Performance	Industry Standards Certifications	USB-PD 3.0 CE FCC
Physical Characteristics	Colour	Black
	Display	Yes
	LED Indicator(s)	None
	Power Cable Length	N/A
	Product Height	3.36 in [85.4 mm]
	Product Width	1.22 in [31.1 mm]
	Product Length	3.00 in [76.3 mm]
Weight of Product		3.63 in [92.1 mm] (with power prongs out)
		10.23 oz [290 g]
Power	Total Power Budget	140W
	Power Delivery	100W Max
	Input Voltage	100-240VAC, 50Hz-60Hz @ 2.5A
	Output Voltage (C1/C2/C3)	100W: 5/9/12/15V 3A, 20V 5A
	Output Voltage (A1/A2)	60W: 5/9/12/20V 3A
	Output Voltage (C1/C2) + (C2/C3)	140W MAX - 95W: 5/9/12/15 3A, 20V 4.75A + 45W: 5/9/12/15V 3A, 20V 2.25A
	Output Voltage (A1) + (A2)	24W MAX - 12W: 5V 2.4A + 12W: 5V 2.4A
	Output Voltage (C1/C2/C3) + (A1/A2)	136W MAX - 100W: 5/9/12/15V 3A, 20V 5A + 36W: 5/9 3A, 12 2.5A, 20V 1.5A
	Output Voltage (C1/C2/C3) + (A1) + (A2)	124W MAX - 100W: 5/9/12/15V 3A, 20V 5A + 12W: 5V 2.4A + 12W: 5V 2.4A
	Output Voltage (C1) + (C2) + (C3)	140W MAX - 65W: 5/9/12/15V 3A, 20V 3.25A + 45W: 5/9/12/15V 3A, 20V 2.25A + 30W: 5/9V 3A, 12V 2.5A, 15V 2A, 20V 1.5A
	Output Voltage (C1/C2) + (C2/C3) + (A1/A2)	135W MAX - 65W: 5/9/12/15V 3A, 20V 3.25A + 45W: 5/9/12/15V 3A, 20V 2.25A + 25W: 5 3A, 9 2.5A, 12V 2A, 20V 1.25A
Output Voltage (C1/C2) + (C2/C3) + (A1) + (A2)	134W MAX - 65W: 5/9/12/15V 3A, 20V 3.25A + 45W: 5/9/12/15V 3A, 20V 2.25A + 12W: 5V 2.4A + 12W: 5V 2.4A	
Output Voltage (C1) + (C2) + (C3) + (A1/A2)	140W MAX - 65W: 5/9/12/15V 3A, 20V 3.25A + 30W: 5/9V 3A, 12V 2.5A, 15V 2A, 20V 1.5A + 20W: 5V 3A, 9V 2.22A, 12V 1.67A, 15V 1.33A + 25W: 5 3A, 9 2.5A, 12V 2A, 20V 1.25A	
Output Voltage (C1) + (C2) + (C3) + (A1) + (A2)	139W MAX - 65W: 5/9/12/15V 3A, 20V 3.25A + 30W: 5/9V 3A, 12V 2.5A, 15V 2A, 20V 1.5A + 20W: 5V 3A, 9V 2.22A, 12V 1.67A, 15V 1.33A + 12W: 5V 2.4A + 12W: 5V 2.4A	
Environmental	Operating Temperature	32°F to 104°F [0°C to 40°C]
	Storage Temperature	-4°F to 176°F [-20°C to 80°C]
	Humidity	5% to 90% (non-condensing)
Packaging Information	Package Type	Poly-Bag
	Package Height	7.00 in [177.8 mm]
	Package Width	5.00 in [127.0 mm]
	Package Length	1.23 in [31.3 mm]
	Shipping (Package) Weight	10.37 oz [294 g]
What's in the Box	Included in Package	1x 140W USB GaN Charger

* Product appearance and specifications are subject to change without notice.
* Same day shipping is only available for orders shipping within the United States.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

**Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com**

