

## VX3228C-2K - 32" CURVED 1440P 1MS 180HZ GAMING MONITOR WITH FREESYNC

### Key Features

---

- 32" 1000R curved screen with ultra-thin bezels for immersive viewing
- 180Hz refresh rate and 1ms (MPRT) response time for incredibly smooth gameplay
- AMD FreeSync™ technology for a stutter-free gaming experience
- 2K QHD resolution with a 16:9 aspect ratio delivers expansive clarity
- Dual integrated speakers for a potent audiovisual experience



32  
DISPLAY



MVA  
PANEL



2560x1440  
RESOLUTION



### Product Description

---

Work hard and play harder with the ViewSonic® VX3228C-2K monitor. Designed with an immersive 32" 1000R curved screen and stunning WQHD 2560 x 1440 resolution, the VX3228C-2K monitor provides an incredible viewing experience for both office use and home entertainment. And with features including a 180Hz\* refresh rate, 1ms (MPRT) response time and AMD FreeSync™ technology, this monitor virtually eliminates screen tearing and stuttering for a silky-smooth gaming experience. The VX3228C-2K also comes equipped with ViewSonic's exclusive ViewMode™ presets, which deliver optimized screen performance for various usage scenarios. Two HDMI (v2.0) inputs and one DisplayPort (v1.4) input offer flexible connectivity for your favorite devices.

\*180Hz refresh rate with DisplayPort

# Specifications

---

|                                    | More Information                             |
|------------------------------------|----------------------------------------------|
| <b>UPC</b>                         | 766907028232                                 |
| <b>Screen Size</b>                 | 32                                           |
| <b>Viewable Area (in.)</b>         | 31.5                                         |
| <b>Panel Type</b>                  | MVA                                          |
| <b>Display Resolution</b>          | 2560 x 1440                                  |
| <b>Display Resolution</b>          | WQHD (2560x1440)                             |
| <b>Static Contrast Ratio</b>       | 3,000:1                                      |
| <b>Dynamic Contrast Ratio</b>      | 50,000,000:1                                 |
| <b>Light Source</b>                | LED                                          |
| <b>Brightness</b>                  | 300 cd/m2                                    |
| <b>Colors</b>                      | 16.7M                                        |
| <b>Color Space Support</b>         | 6 bit + FRC                                  |
| <b>Aspect Ratio</b>                | 16:9                                         |
| <b>Response Time (Typical GTG)</b> | 2ms                                          |
| <b>Response Time (MPRT)</b>        | 1ms                                          |
| <b>Viewing Angles</b>              | 178° horizontal, 178° vertical               |
| <b>Backlight Life (Hours)</b>      | 30,000                                       |
| <b>Panel Surface</b>               | Anti-Glare type, Hard-coating (3H), Haze 25% |
| <b>Curvature</b>                   | 1000R                                        |
| <b>Refresh Rate</b>                | 180Hz                                        |
| <b>PC Resolution (max)</b>         | 2560x1440                                    |
| <b>Mac® Resolution (max)</b>       | 2560x1440                                    |
| <b>3.5mm Audio Out</b>             | 1                                            |
| <b>HDMI 2.0 In</b>                 | 2                                            |
| <b>DisplayPort</b>                 | 1                                            |
| <b>Internal Speakers</b>           | 2W (x2)                                      |
| <b>Eco Mode (Conserve)</b>         | 20W                                          |
| <b>Eco Mode (optimized)</b>        | 23W                                          |
| <b>Consumption (typical)</b>       | 26W                                          |
| <b>Consumption (max)</b>           | 36W                                          |
| <b>Voltage</b>                     | 100-240 VAC                                  |
| <b>Stand-by</b>                    | 0.5W                                         |
| <b>Power Supply</b>                | External                                     |

|                                     |                                                                                     |
|-------------------------------------|-------------------------------------------------------------------------------------|
| <b>Cable Organization</b>           | No                                                                                  |
| <b>Physical Controls</b>            | Up, Right, Down, Left, Power                                                        |
| <b>On Screen Display</b>            | Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu |
| <b>Temperature</b>                  | 32-104° F (0 - 40° C)                                                               |
| <b>Humidity (non-condensing)</b>    | 20-90%                                                                              |
| <b>VESA Compatible</b>              | 100 x 100 mm                                                                        |
| <b>Frequency Horizontal</b>         | HDMI: 28 ~ 214 KHz, DisplayPort: 28 ~ 263 KHz                                       |
| <b>Frequency Vertical</b>           | HDMI: 48 ~ 144 Hz, DisplayPort: 48 ~ 180 Hz                                         |
| <b>Tilt (Forward/Back)</b>          | 5° / 22°                                                                            |
| <b>Regulations</b>                  | cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Bronze, CEC, NOM, Mexico Energy      |
| <b>Net (lbs)</b>                    | 11.8                                                                                |
| <b>Net Without Stand (lbs)</b>      | 10.1                                                                                |
| <b>Gross (lbs)</b>                  | 16.5                                                                                |
| <b>Net (kg)</b>                     | 5.3                                                                                 |
| <b>Net Without Stand (kg)</b>       | 4.6                                                                                 |
| <b>Gross (kg)</b>                   | 7.5                                                                                 |
| <b>Packaging (in.)</b>              | 30.8 x 19.7 x 8.1                                                                   |
| <b>Physical (in.)</b>               | 27.7 x 20.0 x 10.4                                                                  |
| <b>Physical Without Stand (in.)</b> | 27.7 x 16.6 x 4.1                                                                   |
| <b>Packaging (mm)</b>               | 782.0 x 500.0 x 205.0                                                               |
| <b>Physical (mm)</b>                | 702.5 x 507.9 x 262.8                                                               |
| <b>Physical Without Stand (mm)</b>  | 702.5 x 421.3 x 103.9                                                               |
| <b>Package Contents</b>             | LCD Display, DisplayPort Cable, AC/DC Adapter, Quick Start Guide                    |
| <b>Recycle/Disposal</b>             | Please dispose of in accordance with local, state or federal laws.                  |
| <b>Warranty</b>                     | Three-year limited warranty on parts, labor and backlight                           |

UPC: 766907028232



### Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781

email:

[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)