

# Product data sheet

Specifications



## Device monitoring and management, Network Management Cards, NMC4 for Galaxy VS, Galaxy VL & Galaxy VXL, secure remote UPS monitoring and management

AP9644

### Overview

<b>Presentation</b>	Network Management Card for easy monitoring and managing of the Galaxy VS or Galaxy VL. The UPS status can be monitored and managed remotely through the UPS Web Interface, Modbus, or through EcoStruxure IT's cloud-enabled and on-premise software suites.
<b>Lead time</b>	Usually Ships within 2 Weeks

### Main

<b>Range of product</b>	Network Management Cards
<b>Range compatibility</b>	Galaxy VS Galaxy VL Galaxy VXL
<b>Product or component type</b>	Device monitoring and management
<b>Provided equipment</b>	Temperature sensor Micro-USB cable Installation manual
<b>Number of input phases</b>	3

### General

<b>Variant option</b>	Environmental monitoring with Modbus
-----------------------	--------------------------------------

### Physical

<b>Net weight</b>	0.31 lb(US) (0.14 kg)
<b>Width</b>	4.8 in (12.1 cm)
<b>Height</b>	1.5 in (3.8 cm)
<b>Depth</b>	4.3 in (10.8 cm)

### Conformance

<b>Product certifications</b>	FCC Class A AS/NZS
-------------------------------	-----------------------

### Environmental

<b>Storage Relative Humidity</b>	0...95 %
<b>Relative humidity</b>	0...95 %
<b>Ambient air temperature for storage</b>	5...149 °F (-15...65 °C)

<b>Ambient air temperature for operation</b>	23...113 °F (-5...45 °C)
<b>Storage altitude</b>	0.0000000000...49212.6 ft (0...15000 m) 0...50000 ft (0.0000000000...15240.0000000000 m)
<b>Operating altitude</b>	0...3000 m 0...10000 ft

## Communications & Management

<b>Communication network type</b>	10/100/1000BASE-T
<b>Authentication</b>	Radius
<b>Communication port protocol</b>	HTTP over secure sockets Layer (HTTPS) SSH FTP HTTP SNMP DHCP BOOTP (Bootstrap Protocol) TCP/IP

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	1.970 in (5.004 cm)
<b>Package 1 Width</b>	6.540 in (16.612 cm)
<b>Package 1 Length</b>	9.250 in (23.495 cm)
<b>Package 1 Weight</b>	1.759 lb(US) (0.798 kg)

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)