

Specifications

ΔΡC



APC NetShelter Soundproof, 38U, Server Rack Enclosure, 120V, Maple

AR4038LA

Overview

Lead time

Usually Ships within 2 Weeks

Main	
product or component type	Rack enclosure
Main Input Voltage	100120 V
Input Connection Type	NEMA 5-15P
output connection type	10 NEMA 5-15R
Number of rack unit	38U
Cable length	11.98 ft (3.65 m)
Number of cables	1
Provided equipment	Casters

Physical

-	
Height	76.4 in (1940 mm)
Width	29.5 in (750 mm)
Depth	44.5 in (1130.4 mm)
net weight	571.0 lb(US) (259 kg)
Colour	Maple
Mounting preference	No preference
mounting mode	Not rack-mountable
Mounting position	Horizontal
Maximum mounting depth	2.72 ft (0.83 m)
minimum mounting depth	2.26 ft (0.69 m)
rack width	19"
Permanent permissible load	3306.9 lb(US) (1500 kg) static 1653.47 lb(US) (750 kg) dynamic

Input

Network frequency

50/60 Hz

Output

PDU type

Basic

Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Conformance

Standards

EIA-310D

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	80.7 in (205.1 cm)
Package 1 Width	32.3 in (82 cm)
Package 1 Length	47.2 in (120 cm)
Package 1 Weight	668.001 lb(US) (303 kg)

Contractual warranty

Warranty

2 Years

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency

Eu Rohs Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information