





APC NetShelter Metered Rack PDU, 2U, 1PH, 7.4kW 230V 32A, x12 C13 and x4 C19 outlets, IEC 309 cord

AP7822B

### Overview

Lead time Usually in	n Stock
----------------------	---------

### Main

Product or component type	PDU
PDU type	Metered
Cord length	3.7 m
Number of cables	1
Provided equipment	Cord retention bracket(s) Installation guide Rack mounting brackets User manual

## Complementary

Input Voltage	200 V
	208 V
	230 V
	230 V
Height	8.8 cm
Width	44.4 cm
Output Voltage	230 V
Depth	11.2 cm
Net weight	3.36 kg
Mounting location	Front
g .eeaae	Rear
	rcai
Mounting preference	No preference
In and Bloom Town	
Input Plug Type	IEC 60309 32 A 2P + E
Mounting mode	Rack-mounted
Rack units	2U
Mounting position	Horizontal
	Honzontal
Input current limits	32 A
Load capacity	7400 VA
Network frequency	50/60 Hz
Outlet type and quantity	12 IEC 60320 C13
	4 IEC 60320 C19

### **Environment**

Product certifications	C-Tick CE GOST IRAM MIC VDE VCCI
Standards	FCC part 15 class A ICES-003
Ambient air temperature for operation	-545 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.000000000015240.000000000 m

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14 cm
Package 1 Width	36.8 cm
Package 1 Length	50.8 cm
Package 1 Weight	5.42 kg

## **Contractual warranty**

Warranty 2 years repair or replace



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >







Energy Efficient Take-back RoHS/REACh

### Resource performance

Energy Efficient Product

Take-Back Program Available

### Well-being performance

Mercury Free

Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation

Eu Rohs Directive

Compliant with Exemptions

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

End of Life Information