

Empowered by Innovation

NEC

NEC MultiSync® LCD3210



- TileMatrix function for video walls (up to 4 x 4) with integrated tiling functions
- Intelligent Power Management features to reduce the TCO (Total cost of ownership)
- Intelligent self-diagnosis features
- NaViSet™ and NaViSet™ Administrator compatible
- Video detect for signal priority setting
- Power-Off timer for reduced TCO
- AutoBright technology for longer display life time
- Scheduler function
- 16:9 aspect ratio

see more.

NEC Display Solutions

NEC MultiSync® LCD3210

Panel Technology	S-IPS
Active Screen Area (w x h) [mm]	760 x 450
Screen Size [inch/cm]	31.5/80
Viewing Angle (typ.)	176° horizontal / 176° vertical (at contrast ratio 10:1)
Screen Aspect Ratio	16:9
Pixel Pitch [mm]	0.511 x 0.511
Contrast Ratio (typ.)	600:1
Brightness (typ.) [cd/m ²]	500
Response Time (typ.) [msec]	20 (11 white/black; 9 black/white)
Colours [million]	16.77
Horizontal Frequency [kHz]	31.5-91.1 (analog and digital)
Vertical Frequency [Hz]	58.0-85.0
Optimum Resolution	1360 x 768 at 60 Hz
Other Resolutions	1600 x 1200; 1280 x 1024; 1280 x 768; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480
Connectors	Analog: mini D-sub 15 Pin, 5 x BNC; Digital: DVI-D
Audio Input	1 x RCA; 1 x S-Video; 2 x BNC (Composite and Component)
Audio Output	1 x BNC (Composite and RCA)
Composite Video	BNC/RCA
Component Video	BNC
S-video	yes
Plug & Play	VESA DDC2Bi
Safety and Ergonomics	UL/C-UL or CSA; FCC Class B; TÜV GS; VCCI; CE; C-tick; PSB; CCC
Power Consumption (typ.) [W]	115
Power Management	VESA DPMS
Power Requirements	100-120/220-240V; 1.4/0.6A; internal power supply
Operating Temperature [°C]	+ 5 to + 40
Operating Humidity [%]	20 to 80
VESA Mounting Interface	600 x 200 (FDMI); 16 holes / 100 mm spacing
Dimensions (W x H x D) [mm]	With stand: 789 x 510.3 x 200 Without stand: 789 x 479 x 140
Bezel Width [mm]	45.2 left/right; 43.0 top/bottom
Specials	Picture in Picture Mode; Picture over Picture Mode; CableComp light; sRGB; Temperature Sensor; Colour Temperature Mode; Rapid Response Technology; Vacation switch; Power Off Timer; Sharpness/Softness; Touch Panel ready; AutoBright Technology; TileMatrix; Scheduler Function
Weight [kg]	16.4 (with stand); 15.2 (without stand)
Video ready (no tuner)	NTSC; PAL, SECAM
HDTV ready (no tuner)	480i; 480p; 720p; 1080p
NaViSet™	yes
NaViSet™ Administrator	yes
Audio Functions	Optional speakers (2 x 7 W)
Remote Control	RS-232C (9 pin D-Sub); Administrator compatible (DDC/CI); Remote Control IR
Shipping Content	Display, Stand; Power Cable; Remote Control (IR); CD Manual; VGA-VGA Cable; Remote Control IR
Warranty	3 years warranty including backlight



NaViSet™



NaViSet™
Administrator



All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. July 2005

see more.

NEC Display Solutions

www.nec-display-solutions.com
NEC Display Solutions Europe GmbH