

#### Important Note

Standards that govern use of this product vary by country and sometimes municipality. In the United States, this product is not for use in the Patient Care Vicinity, as defined in the National Electric Code (NEC). This product is approved to CSA C22.2/CuL standards and approved for use in Canada. For application guidance and product selection in your country, please consult a [Healthcare Product Specialist](#) or your own expert.

## Safe-IT UL 1363 Medical-Grade Power Strip, 6x Hospital-Grade Outlets, Antimicrobial, 15 ft. (4.57 m) Cord

MODEL NUMBER: PS-615-HG



Delivers power to devices outside of patient care vicinities, including therapy rooms and administrative areas.

#### Features

**6-Outlet Power Strip Supplies Power Outside Patient Care Vicinities** This medical-grade power strip is for administrative areas or resident rooms of long-term care facilities that do not use line-operated electrical equipment for diagnostic, treatment or monitoring purposes. This includes operating rooms, therapy rooms, imaging environments and administrative areas. With six NEMA 5-15R-HG outlets and a 15-foot (4.6-meter) power cord with NEMA 5-15P-HG plug, this 120V power strip complies with UL 1363.

**Exclusive Antimicrobial Protection Fights Healthcare-Acquired Infections (HAIs)** The PS-615-HG is protected by a patented antimicrobial powder coating with EPA-registered and FDA-compliant silver ionic technology. The antimicrobial surface protection is 99.9 percent effective in inhibiting the growth of bacteria and reducing the risk of HAIs in hospitals and other medical environments. The coating meets the requirements of JIS Z 2801:2000, an international standard for evaluating efficacy in antimicrobial products.

**Premium Safety Features Help Ensure Proper Power Connections** With no central power switch, the PS-615-HG presents no danger of accidental shutoff and cutting off power to essential devices. One resettable 15-amp circuit breaker shuts down all input if the connected load draws too much power.

**Ready for Installation Straight from the Box** Built-in mounting flanges and integrated keyhole slots let you install the durable metal housing on any wall or other flat surface for distributing immediate power to equipment outside a patient care vicinity.

## Specifications

#### Highlights

- UL 1363 power strip for use outside patient care vicinities
- Antimicrobial protection helps prevent the growth of bacteria, viruses, fungi, mold and mildew
- NEMA 5-15P-HG plug permits connection in confined or hard-to-reach spaces
- 15 ft. (4.6 m) power cord allows flexibility in placing power strip in relationship to AC outlet
- Switchless design helps prevent accidental shutdown of essential equipment

#### Applications

Supply safe medical-grade power to lab, imaging and other electric components outside a patient care area

#### Package Includes

- PS-615-HG Medical-Grade Power Strip
- Owner's manual



Powering Business Worldwide

TRIPP LITE  
SERIES

| OVERVIEW                                          |                                                                                 |
|---------------------------------------------------|---------------------------------------------------------------------------------|
| UPC Code                                          | 037332100108                                                                    |
| INPUT                                             |                                                                                 |
| Nominal Input Voltage(s) Supported                | 120V AC                                                                         |
| Recommended Electrical Service                    | 15A 120V                                                                        |
| Input Plug Features                               | Hospital Grade Plug                                                             |
| Voltage Compatibility (VAC)                       | 120                                                                             |
| Input Plug Type                                   | NEMA 5-15P-HG                                                                   |
| Input Cord Length (ft.)                           | 15                                                                              |
| Right-Angle Plug                                  | No                                                                              |
| Input Cord Length (m)                             | 4.57                                                                            |
| Integrated Cord Clip                              | No                                                                              |
| OUTPUT                                            |                                                                                 |
| Frequency Compatibility                           | 50 / 60 Hz                                                                      |
| Output (Watts)                                    | 1800                                                                            |
| Output Receptacles                                | (6) 5-15R-HG                                                                    |
| Circuit Breaker (amps)                            | 15                                                                              |
| Overload Protection                               | 15A circuit breaker                                                             |
| Transformer Accommodation                         | (2) Yes                                                                         |
| Outlet Orientation                                | Single row of 6                                                                 |
| Right-Angle Outlets                               | No                                                                              |
| USER INTERFACE, ALERTS & CONTROLS                 |                                                                                 |
| Switches                                          | No power switch                                                                 |
| PHYSICAL                                          |                                                                                 |
| Color                                             | White                                                                           |
| Material of Construction                          | Metal                                                                           |
| Power Cord Color                                  | White                                                                           |
| Housing Color                                     | White                                                                           |
| Mounting Holes or Slots                           | Yes                                                                             |
| Slot or Hole Mount Measurement (Center to Center) | Distance between keyhole slots = 261.92mm; Distance between end tabs = 330.17mm |
| Outlets Measurement (Center to Center)            | 1.52 in.                                                                        |
| Receptacle Color                                  | White                                                                           |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                                |
|--------------------------------------|--------------------------------|
| Shipping Dimensions (hwd / in.)      | 2.00 x 5.80 x 14.10            |
| Shipping Dimensions (hwd / cm)       | 5.08 x 14.73 x 35.81           |
| Shipping Weight (lbs.)               | 3.30                           |
| Shipping Weight (kg)                 | 1.50                           |
| Unit Dimensions (hwd / in.)          | 1.500 x 13.750 x 2.500         |
| Unit Dimensions (hwd / cm)           | 3.8 x 34.9 x 6.4               |
| Mounting Details                     | Includes flanges               |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                |
| Antimicrobial                        | Yes                            |
| Built-In Circuit Breaker             | Yes                            |
| Antibacterial                        | No                             |
| Built-in Cable Management            | No                             |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                |
| Product Certifications               | cUL Listed; UL 1363; UL Listed |
| Product Compliance                   | RoHS                           |
| <b>WARRANTY &amp; SUPPORT</b>        |                                |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty      |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.