

Product data sheet

Specifications



APC WW 10KVA Isolation Transformer



APTF10KW01

Overview

Presentation	The Step-Down Transformer converts high voltage (208 or 200 VAC) output into low voltage (120 or 100 VAC) output for powering low voltage AC equipment.
Lead time	Usually in Stock

Main

Main Input Voltage	208 V 230 V 240 V
Product or Component Type	Accessory
Main Output Voltage	120 V 208 V 230 V 240 V
Output connector type	Hard Wire 3-wire (H N + E) 1 Hard Wire 3-wire (2PH + G) 1
Number of rack unit	4U
Provided Equipment	Documentation CD Hardwire panel Installation guide Rack Mounting brackets User Manual Mounting Hardware

Physical

Color	Black
Height	6.9 in (17.5 cm)
Width	17.008 in (43.2 cm)
Depth	29.5 in (74.9 cm)
Net Weight	220.5 lb(US) (100 kg)
Mounting Location	Front Side
Mounting preference	Lower
Mounting Mode	Rack-mounted

Input

Max line current	60 A
Input current limits	60 A
Load Capacity	10000 VA

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Input Frequency	45...65 Hz
Number of input connectors	1 Hard Wire 3-wire (2PH + G) 1 Hard Wire 3-wire (1PH+N+G)

Output

Maximum Total Current Draw per Phase	60 A
Number of power socket outlets	0
Efficiency	95 %

Conformance

Product Certifications	CSA UL Listed
Standards	EN 55022 Class A EN 55024 EN 61000-3-2 EN 61000-3-3

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

Ordering and shipping details

GTIN	731304242208
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.0 in (40.6 cm)
Package 1 Width	23.6 in (60 cm)
Package 1 Length	39.4 in (100 cm)
Package 1 Weight	275.0004 lb(US) (124.738 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	6
Package 2 Height	52.6 in (133.5 cm)
Package 2 Width	39.4 in (100 cm)
Package 2 Length	47.2 in (120 cm)
Package 2 Weight	1650.003 lb(US) (748.428 kg)

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)