

Poly Trio C60 IP Conference Phone for Microsoft Teams and PoE-enabled No Radio

One device. Many possibilities.

Bring people together. Launch big ideas. And make sure everyone at the table can be heard, near or far with Poly signature audio. The Trio C60 plays nicely with everyone, delivering native experiences on your favorite collaboration platforms.



*Product image may differ from actual product

Poly signature audio

Get more out of your conference calls. Poly reduces distracting background noise to ensure every inflection is heard. Hear every reaction with up to 22 kHz of rich, full sound.

One-touch join

All it takes is a fingertip to get started. Join your calls in a second with a single touch of a button thanks to the truly intuitive user experience.

Datasheet

Poly Trio C60 IP Conference Phone for Microsoft Teams and PoE-enabled No Radio

Specifications



Display

- Aspect ratio: 16:9
- Native resolution: 720 x 1280
- Panel technology: Color LCD
- Display size (diagonal, metric): 12.7 cm (5")
- Touch-enabled: Gesture-based, multi-touch capable touchscreen

Connectivity and communications

- Wireless range: Up to 6.1 m
- External I/O ports:
 - 1 USB 2.0 Type-A (for USB battery charging)
 - 1 USB 2.0 Micro-B (for USB audio device)
 - 2 RJ-45 (10/100/1000BASE-TX Mbps)
- Wireless technologies:
 - Bluetooth® 4.2
 - Wi-Fi network connectivity: 2.4-2.4835 GHz (802.11b, 802.11g, 802.11n HT-20)
 - 5.15-5.825 GHz (802.11a, 802.11n, HT-20, 802.11n HT-40)

Battery

- Power features:
 - LAN IN: Built-in auto-sensing IEEE 802.3at, PoE Device (Class 4)
 - LAN OUT: Built-in auto-sensing IEEE 802.3af power sourcing equipment¹

User interface features

- Languages:
 - Arabic; Chinese; Czech; Danish; Dutch; English; French; German; Hungarian; Italian; Japanese; Korean; Norwegian; Polish; Portuguese; Romanian; Russian; Slovenian; Spanish; Swedish

Audio

- Audio features:
 - Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression
 - Comfort noise generation
 - DTMF tone generation (RFC 2833 and in-band)
 - Low delay audio packet transmission
 - Adaptive jitter buffers
- Microphone type: Three cardioid microphones
- Frequency response (microphone): 100 Hz to 22 kHz
- Sensitivity (speaker): 92 dB
- Audio codecs:
 - G.711 (A-law and μ -law)
 - G.722
 - G.722.1
 - G.722.1C
 - G.729AB
 - G.719
 - Polycom® Siren™ 7
 - Siren™ 14
 - iLBC
 - OPUS

Environmental

- Certifications and compliances: AS/NZS 60950-1; AS/NZS 62368-1-17; Australia -AS/NZ4268; Australia A&C Tick; CAN/CSA C22.2 No. 60950-1-03; CAN/CSA C22.2 No. 62368-1-14; CE Mark; CISPR22 Class B; EN 301 489-1; EN 301 489-3; EN 301 489-17; EN 61000-3-2; EN 61000-3-3; EN 62368-1; ETSI EN 300 328 v1.91; ETSI EN 300 330; ETSI EN 301 893 v1.71; FCC Part 15 (CFR 47) Class B; FCC Part 15.225; FCC Part 15.247; FCC Part 15.407; ICES-003 Class B; IEC 60950-1; IEC 62368-1; Japan Item (19); Japan Item (19)-3; Japan Item (19)-3-2; Japan MIC/VCCI Class B; NZ Telepermit; ROHS compliant; RSS 247 Issue 1; UL 60950-1; UL 62368-1
- Operating humidity range: 5 to 95%
- Operating Temperature Range (Celsius) / Operating Temperature Range (Fahrenheit): 0 to 40°C / Storage temperature range (Celsius) / Storage temperature range (Fahrenheit): -20 to 70 °C /
- Energy star certified: ENERGY STAR® certified

Certifications

- Certified collaboration software: Microsoft Teams; Skype for Business; Zoom
- Special features:
 - Unicode UTF-8 character support

Applications supported

- Management software:
 - Poly Zero Touch Provisioning
 - RealPresence Resource Manager (v. 101 or above) based provisioning
 - Polycom Device Management Service for Enterprise (PDMS-E)
 - Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management SDP

Display features

- On-screen virtual keyboard

Security

- Security management:
 - 802.1X Authentication and EAPOL Media encryption via SRTP
 - Digest authentication
 - Encrypted configuration files
 - HTTPS secure provisioning
 - Password login
 - Support for signed software executables
 - Support for URL syntax with password
 - Transport Layer Security (TLS)
 - Wi-Fi encryption: WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-TLS, PEAP-MSCHAPv2)
 - FIPS 140-2 compliant cryptographic module

Network

- Supported network protocols:
 - DHCP VLAN discovery
 - LLDP-MED for VLAN discovery
 - FTP/TFTP/HTTP/HTTPS server-based central provisioning
 - Manual or dynamic host configuration protocol (DHCP) network setup
 - QoS Support – IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP
 - Time and date synchronization using SNTP
 - Provisioning and call server redundancy support
- VoIP features:
 - IETF SIP (RFC 3261 and companion RFCs)

Poly Trio C60 IP Conference Phone for Microsoft Teams and PoE-enabled No Radio

Specifications



Headset and handset compatibility

Headset and handset compatibility:
Bluetooth® headset compatibility

Telephony and call handling features

Telephony and call handling features:
Bundled with Polycom UC Software: Corporate Directory Access using LDAP
Call timer and call waiting
Call transfer, hold, divert (forward), park, pickup
Called, calling, connected party information
Distinctive incoming call treatment/call waiting
Do not disturb function
Local configurable digit map/dial plan
Local five-way audio conferencing
Shared call/bridged line appearance
Visual Conference Management
Up to 3 lines (maximum one Skype for Business and Microsoft Teams)
Daisy-chain up to four
One-touch speed dial, redial and meeting join

Weight and dimensions

Product Primary Color: Black
Weight (metric): 950 g
Product Dimensions (metric): 38.3 x 7.5 x 33.2 cm
Package dimensions (metric): 48.3 x 11.5 x 39.4 cm
Package Weight (metric): 1970 g
Product number: 830A1AA

Warranty

Poly standard one-year limited warranty

What is in the box

Console
Network (LAN) cable-CAT-5E
USB Type-A cable
Cable wrap
Tactile overlay for improved accessibility
Setup sheet

Technical Specifications Footnotes

¹ Requires full Class 4 power input on LAN IN for operation