



PBJ5UC PREMIUM HOME THEATER SURGE PROTECTOR

Centralize, protect and power a variety of devices with the CyberPower PBJ5UC, a twelve outlet, braided cord surge solution with USB charging ports, coax and network protection.

The CyberPower Premium Surge Protector PBJ5UC is ideal for the home, office, or home theater because it is designed to provide maximum protection and convenience to a number of devices where wall receptacles are out of reach. This Premium Surge Protector prevents damaging spikes in energy caused by storms and electrical power from reaching your electronic equipment. The PBJ5UC provides 3480 joules of protection, 12 outlets (6 widely spaced for transformer plugs), 4 USB Type-A charging ports, and a right-angle, 5-foot braided power cord.

TYPICAL APPLICATIONS

- Home Theater Equipment
- Personal Computers
- Phone/Fax/Modem
- Cable and Satellite
- Consumer Electronics

FEATURES

- Surge suppression: 3480 J
- Volts: 125
- Circuit breaker: 15 Amp
- Plug type: NEMA 5-15P (45° off-set)
- Outlet type: 12 x NEMA 5-15R
- Power cord: 5 ft braided
- Data line protection: Coaxial, Network
- Cable/Satellite protection: Yes
- EMI/RFI Filtration: Yes
- Warranty: Limited lifetime
- Connected Equipment Guarantee: \$1,000,000



SPECIFICATIONS

INPUT		OUTPUT	
Cord Length (ft)	5 ft.	Outlet Type	NEMA 5-15R
Plug Type	NEMA 5-15P	Outlets - Total	12
Plug Style	Right angle, 45 degree offset to the right	Outlets - Widely Spaced	6
Circuit Breaker	15 Amp	USB Charge Port - Total	4 Type-A
Switch	Non lighted on/off - reset	USB Charging Amperage	4.8A (shared)

PBJ5UC PREMIUM HOME THEATER SURGE PROTECTOR

SPECIFICATIONS

SURGE PROTECTION & FILTERING

Maximum Surge Current H-G	15,000 amps
Clamping Voltage	500 V (L-N, L-G, N-G)
Attenuation	Up to 43dB
Coax Protection RG6 (Gold Plated)	2 Pair
EMI/RFI Filtration	150 kHz to 100 MHz
Maximum Surge Current H-N	75,000 amps
Maximum Surge Current N-G	15,000 amps
Response Time	< 1 nanosecond
Surge Suppression	3480 joules
Ethernet Protection RJ45	1-In, 1-Out
Maximum Surge Current	105,000 amps

PHYSICAL

Dimensions (WxHxD) (mm)	134.112 x 36.576 x 327.152
Dimensions - WxHxD (in)	5.28 x 1.44 x 12.88
Shipping - Weight (lb)	2.2
Shipping - Weight (kg)	1.0
Form Factor	Strip
Enclosure Construction	ABS
Color	Black
Safety Covers	No

CERTIFICATIONS

Environmental	RoHS Compliant, DOE VI
Safety	UL1363, 1310, UL1449 4th Edition, cUL, FCC, DOE6

WARRANTY

CEG Amount	\$1,000,000
Product Warranty	Limited Lifetime
Connected Equipment Guarantee	Yes