

Product data sheet

Specifications



Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 5.7kW, 208V, (21) C13 & (3) C19

AP8661

Overview

Presentation APC Metered by Outlet with Switching Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and individual outlet power metering. Remote outlet level controls allow power on/off functionality for power recycling to reboot locked-up equipment and to avoid unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, and locking IEC receptacles. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.

Lead time Usually in Stock

Main

Color	Black
Product or Component Type	PDU
PDU Type	Switched metered outlet
Cord length	6 ft (1.8 m)
Number of cables	1
Provided Equipment	CAN Port Terminator Installation guide Rack Mounting brackets Safety guide Serial configuration cable

Complementary

Input Voltage	208 V 3 phase
Height	72.008 in (182.9 cm)
Width	2.2 in (5.6 cm)
Output Voltage	208 V
Depth	2.008 in (5.1 cm)
Net Weight	15.74 lb(US) (7.14 kg)
Mounting Location	Side
Mounting preference	No preference
Input Plug Type	NEMA L21-20P
Mounting Mode	Rack-mounted
Rack units	0U

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

USB compatible	No
Mounting position	Vertical
Line Rated Current	16 A
Max line current	20 A
Input current limits	20 A
Load Capacity	5700 VA
Input Frequency	50/60 Hz
Outlet type and quantity	21 IEC 60320 C13 3 IEC 60320 C19

Environment

Product Certifications	cUL Listed UL Listed VCCI Class A
Standards	FCC Part 15 class A ICES-003
Ambient Air Temperature for Operation	23...140 °F (-5...60 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)

Ordering and shipping details

GTIN	731304276999
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	80.2 in (203.8 cm)
Package 1 Width	4.6 in (11.8 cm)
Package 1 Length	6.4 in (16.2 cm)
Package 1 Weight	20.75 lb(US) (9.41 kg)

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH


Resource performance


 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Lead Free

 Mercury Free

 Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)
