


# Duplex Singlemode 9/125 Fiber Patch Cable (LC/LC), 8 m (26 ft.)

MODEL NUMBER: N370-08M



Premium singlemode fiber optic cabling transmits fast, clear data signals through your LAN with data transfer speeds up to 10 Gbps.

## Features

### Fast, Clear Data Transmission Through Your LAN

- Data transfer speeds up to 10 Gbps
- Ideal for network equipment that requires singlemode fiber optic patch cables
- Attenuation loss meets or exceeds latest industry standards

### Superior Construction for Error-Free Signal Transfer

- 9/125 duplex (zipcord) fiber made from glass
- Sturdy LC male connectors meet stringent insertion loss standards
- Beveled edge on glass ends for easy plug insertion
- Yellow-colored for identification as singlemode

## Specifications

| OVERVIEW             |                  |
|----------------------|------------------|
| UPC Code             | 037332195005     |
| Technology           | Singlemode       |
| Optical Mode         | OS2              |
| CONNECTIONS          |                  |
| Side A - Connector 1 | LC DUPLEX (MALE) |
| Side B - Connector 1 | LC DUPLEX (MALE) |
| Endface Polish       | UPC              |

## Highlights

- Attenuation loss meets or exceeds latest industry standards
- 9/125 duplex (zipcord) fiber made from glass
- LC male connectors meet insertion loss standards
- FDDI- and OFNR-rated
- Beveled edge on glass ends for easy plug insertion

## System Requirements

- Fiber optic hardware or NIC card requiring singlemode duplex cable with LC/LC connectors

## Package Includes

- N370-08M Duplex Singlemode 9/125 Fiber Patch Cable, 8 m



Powering Business Worldwide

TRIPP LITE  
SERIES

| PHYSICAL                        |                                                                 |
|---------------------------------|-----------------------------------------------------------------|
| Cable Jacket Color              | Yellow                                                          |
| Connector Color                 | Blue; White                                                     |
| Cable Jacket Material           | LSZH                                                            |
| Cable Jacket Rating             | OFNR                                                            |
| Clad Diameter (microns)         | 125                                                             |
| Core Diameter (microns)         | 9                                                               |
| Number of Fibers                | 2                                                               |
| Cable Length (ft.)              | 26.2                                                            |
| Cable Length (m)                | 7.99                                                            |
| Cable Length (in.)              | 315                                                             |
| Minimum Bend Radius             | 20 mm (Dynamic); 10 mm (Static)                                 |
| Shipping Dimensions (hwd / in.) | 9.00 x 7.00 x 0.50                                              |
| Shipping Dimensions (hwd / cm)  | 22.86 x 17.78 x 1.27                                            |
| Shipping Weight (lbs.)          | 0.15                                                            |
| Shipping Weight (kg)            | 0.07                                                            |
| Fiber Cable Length              | 8M (26.2 ft)                                                    |
| ENVIRONMENTAL                   |                                                                 |
| Operating Temperature Range     | -4° to 140°F (-20° to 60°C)                                     |
| Storage Temperature Range       | -4° to 140°F (-20° to 60°C)                                     |
| Operating Humidity Range        | 5% to 85% RH, Non-Condensing                                    |
| Storage Humidity Range          | 35% to 65% RH, Non-Condensing                                   |
| COMMUNICATIONS                  |                                                                 |
| Network Compatibility           | 1 Gbps (Gigabit); 10 Gbps; 25 Gbps; 40 Gbps; 100 Gbps; 400 Gbps |
| Attenuation @ 1310NM            | 0.36 dB/km                                                      |
| Attenuation @ 1550NM            | 0.22 dB/km                                                      |
| Insertion Loss                  | 0.30 dB                                                         |
| FEATURES & SPECIFICATIONS       |                                                                 |
| Push/Pull Tabs                  | No                                                              |
| Breakout                        | No                                                              |
| Trunk                           | No                                                              |
| STANDARDS & COMPLIANCE          |                                                                 |
| Product Compliance              | RoHS; REACH                                                     |

WARRANTY & SUPPORT

|                                        |                           |
|----------------------------------------|---------------------------|
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty |
|----------------------------------------|---------------------------|

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.