

Product datasheet

Specifications



Rack PDU, Basic, Zero U, 30A, 200/208V, (20)C13 & (4)C19

AP7541

Overview

Presentation APC Basic Rack PDUs distribute reliable rack power distribution via a single input with multiple output receptacles. Easily mount this vertical PDU in racks or enclosures. It occupies zero U of valuable rack space, which allows space for more equipment in the rack. This vertical PDU does not require additional tools to mount into APC NetShelter Enclosures. Enables a quick recovery from overload events. Packaging Includes PDU, Installation guide, Rack Mounting brackets, Toolless Mounting Kit.

Lead time Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	3.05 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets Toolless mounting kit

Complementary

Input Voltage	200 V 208 V 230 V
Height	161.9 cm
Width	5.6 cm
Output Voltage	200 V 208 V
Depth	4.4 cm
Net weight	5.57 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	NEMA L6-30P
Mounting mode	Rack-mounted
Rack units	0U
USB compatible	No
Mounting position	Vertical
[In] rated current	24 A

Input current limits	30 A
Load capacity	4992 VA
Network frequency	50/60 Hz
Outlet type and quantity	20 IEC 60320 C13 4 IEC 60320 C19

Environment

Product certifications	cUL listed METI Denan PSE UL listed
Standards	CSA C22.2 No. 60950-1-03 UL 60950-1
Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	212.1 cm
Package 1 Width	12.7 cm
Package 1 Length	15.2 cm
Package 1 Weight	6.48 kg

Logistical informations

Country of origin	IN
--------------------------	----

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Lead Free

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)