



Power Cord Kit (6 EA), Locking, C19 TO C20, 1.2M (4FT), Red

AP8714SX340

Overview

Lead time Usually in Stock

Main

Product or Component Type	Power cord	
Input Connection Type	IEC 60320 C20	
Cable length	4 ft (1.2 m)	
Number of cables	6	

Physical

Color	Red
Height	11.8 in (30 cm)
Width	2.8 in (7 cm)
Depth	2.8 in (7 cm)
Net Weight	3.62 lb(US) (1.64 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Max line current	16 A
Input current limits	16 A

Output

Maximum Total Current Draw per Phase	16 A
Number of power socket outlets	1 IEC 60320 C19
Cord Length	4 ft (1.2 m)

Conformance

Product Certifications	CCC	
	CSA	
	PSE	
	UL Listed	
	VDE	

Environmental

Ambient Air Temperature for	32.0000000000167.0000000000 °F (075 °C)
Operation	, ,

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Relative Humidity	2080 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13.0000000000167.0000000000 °F (-2575 °C)
Storage Relative Humidity	2080 %
Storage altitude	050000 ft (0.000000000015240.0000000000 m)

Ordering and shipping details

GTIN	731304329428	
Country of origin	CN	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.8 in (30 cm)
Package 1 Width	2.8 in (7 cm)
Package 1 Length	2.8 in (7 cm)
Package 1 Weight	3.62 lb(US) (1.64 kg)

Contractual warranty

Warranty 2 years repair or replace



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >









Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

⊘ En

Energy Efficient Product



Take-Back Program Available

Well-being performance



Lead Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information