



Sometimes you want to  
take it slow.

Sometimes you don't.

# Lexmark **E350d**

High-performance printing for  
your desktop or small  
workgroup!

## **Outstanding performance**

Zip through your print runs as fast as 33 ppm, with instant warm-up and the first page out in as little as 6.5 seconds.

Up to 33 ppm

Duplex as standard

Optional 550 sheet drawer

## **An easier way to work**

Benefit from easy set-up, front-loading consumables and a user-friendly 2-line display, which simplifies printing and maintenance tasks.

## **New environmental features**

In addition to automatic duplex printing – now standard – it includes new Eco and Quiet modes for optimal energy efficiency and minimal noise.

**LEXMARK**  
TM

# Lexmark E350d/E352dn

## Hard at work for your busy office

Compact and easy to use, the Lexmark E350d mono laser is the perfect high-speed partner for your desktop or small workgroup. Available as a standalone or network-ready (Lexmark E352dn), it gives you sharp 1200 x 1200dpi print quality, plus a range of flexible options, including higher-yield cartridges and a second input drawer to boost your total capacity up to 800 sheets.

### True office productivity

Backed by a powerful 366MHz processor and 32MB of standard memory, the Lexmark E350d makes light work of your most complex print jobs. With rapid print speeds, a new instant-warm-up fuser and just 6.5 seconds to first printed page, it's among the fastest in its price range. So now you can finish off documents before other printers even get started!

### Environmental excellence

Leading technology makes the Lexmark E350d one of the most energy-efficient printers in its speed range. Additionally, you can take advantage of automatic duplex printing to save paper and reduce costs. And the new Quiet Mode lets you cut the already-low noise level to as little as 48dB while printing. All in all, you save money, time and energy.

#### Print Technology

Laser, Monochrome

#### Print Speed (A4 mono)

Up to 33 ppm

#### Print Speed (A4 mono) Duplex

Up to 16 spm

#### Print Speed (Letter mono)

Up to 35 ppm

#### Print Speed (Letter mono) Duplex

Up to 16 spm

#### Time to First Page (Black)

as fast as 6.5 seconds

#### Print Resolution, Black

1200 Image Quality

1200 x 1200 dpi

2400 Image Quality

600 x 600 dpi

#### Processor

366 MHz

#### Memory, standard

32 MB

#### Memory network model, maximum

160 MB

#### Expandable Memory Options

Yes

#### Apple Macintosh Operating Systems Supported

Mac OS X, Mac OS 9.x

#### Citrix MetaFrame

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries., Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2003 running Terminal Server with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 running Terminal Server with Citrix Presentation Server 4.0

#### Linux Operating Systems Supported

Red Hat Linux Desktop 4.0, 5.0, Linpus Linux Desktop 9.2, 9.3, Red Hat Enterprise Linux WS 3.0, 4.0, SUSE Linux Enterprise Server 8.0, 9.0, SUSE Linux Professional 9.1, 9.2, 9.3, Debian GNU/Linux 3.0, 3.1, Linpire Linux 4.5, 5.0, SUSE Linux 10.0, 10.1

#### Microsoft Windows Operating Systems Supported

2000, NT (4.00/4.00 Server), Me, XP, Server 2003, 98 2nd Edition, XP x64, Server 2003 running Terminal Server, 2000 Server running Terminal Services, Server 2003 x64 Edition, Vista

#### Paper Handling (Standard)

150-Sheet Output Bin, Integrated Duplex, Single Sheet Exit, Single Sheet Manual Feed Slot, 250-Sheet Input Tray

#### Paper Handling Optional

550-Sheet Drawer

#### Paper Input Capacity (Standard)

250 pages at 80 gsm bond

#### Paper Input Capacity (Maximum)

800 pages at 80 gsm bond

#### Paper Output Capacity (Standard)

150 pages at 80 gsm bond

#### Paper Output Capacity (Maximum)

150 pages at 80 gsm bond

#### Envelope Capacity

1

#### Finishing Option

No

#### Number of Paper Inputs

2

#### Number of Paper Inputs, Maximum

3

#### Media Types Supported

Envelopes, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide

#### Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, A6 Card, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal

#### Noise Level, Operating

52 dBA

#### Product Guarantee

One year return to base, 5-7 business days response time

#### Product Certifications

FCC Class B, UL 60950-1 3rd Edition, U.S. FDA, IEC 320-1, CSA, ICES Class B, Energy Star, CE Class B, CB IEC 60950-1, IEC 60825-1, GS (TÜV), SEMKO, UL AR, CS, TÜV Rh, N Mark, ACA C-tick Class B, CCC Class B, BSMI Class B, MIC, EK Mark, PSB

#### Duty Cycle

Up to 80,000 Pages

#### Specified Operating Environment

Temperature: 16 to 32°C (60 to 90°F), Altitude: 0 - 2500 Meters (8,200 Feet), Humidity: 8 to 80% Relative Humidity for Temperatures less than 25.5°C (78°F)

#### Standard Ports

Centronics IEEE 1284 Bidirectional Parallel, USB 2.0

Specification Hi-Speed Certified

#### Optional Network Ports

Lexmark N4000e Fast Ethernet (Print Only), Lexmark N4050e 802.11g Wireless Print Server (Print Only), External MarkNet™ N7020e Gigabit Ethernet, External MarkNet™ N7000e Fast Ethernet (USB), External MarkNet™ N7002e Fast Ethernet (parallel)

#### Printable Area

4 mm of the top, bottom, right and left edges (within)

#### Printer Languages (Standard)

PCL 5e Emulation, PCL 6 Emulation, PPDS, PostScript 3

Emulation

#### Packaged Size (mm - H x W x D)

378 x 470 x 430 mm

#### Size (mm - H x W x D)

259.5 x 359 x 396 mm

#### Weight (kg)

11.4 kg

#### Noise Level, Idle

inaudible dBA

#### Cartridges

E350d:

Ships with 1.5K\* Return Programme Toner Cartridge

E352dn:

Ships with 3K\* Return Programme Toner Cartridge

Aftermarket cartridges available :

3.5K\* and 9K\* Return Programme Toner Cartridge.

Regular Cartridges also available.  
30K pages Photoconductor

\* Average cartridge yield. Declared Yield value in accordance with ISO/IEC 19752.

#### Cost saving & environmental features

The Energy Star compliance and the instant warm-up fuser technology contributes to reduce energy consumption - Integrated duplex printing, print and hold (verify print), multi-up printing and quality printing on recycled paper help reduce paper consumption - Return Programme cartridges and end-of-life product management help reduce landfill.

#### Models available

E350d — Duplex  
E352dn — Duplex, Network



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit [www.lexmark.com/recycle](http://www.lexmark.com/recycle)



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and or other countries. All other trademarks are the properties of their respective owners.

[www.lexmark.co.uk](http://www.lexmark.co.uk)

**LEXMARK**  
TM