



Overview

HP 31 Ink Bottle, cyan (70 ml)

Print thousands of pages with one simple purchase of a set of Original HP high-yield ink bottles—at an extremely low cost per page.[1] Get high-volume printing, an easy and convenient way to replenish ink, and HP print quality and reliability.

Extremely low cost per page[1]

Print all you want without worrying about the cost of ink using high-yield Original HP ink bottles.[1]

Outstanding quality and durability from HP

Preserve your images and get vivid, borderless, fade-resistant photos that last for decades.[4]

Conveniently manage ink


Manage ink levels and decide when to easily add more—no guessing or waiting until you run low.

Features





Designed to work the first time, every time^[6]





The environmental choice.^[7]



Better together. Better results.



Extremely low cost per page^[1]

High yield ink bottles

[1] HP ink bottles compared to HP ink cartridges. Cost per page based on expected black and composite (cyan/magenta/yellow) page yield results based on HP methodology and continuous printing of ISO/IEC 24712 test pages. Not based on ISO/IEC 24711 test process. Actual yield varies based on content of printed pages and other factors. Some ink from included bottles is used to start up the printer. For more information about fill and yield, see http://www.hp.com/go/learnaboutsupplies.

[4] Photo fade resistance estimates based on HP internal testing and Wilhelm Imaging Research testing on Original HP color inks printed on HP Glossy Photo Papers, displayed under glass. See http://www.hp.com/go/printpermanence.

[6] See http://www.hp.com/go/suppliesclaims.

[7] HP Planet Partners Program availability varies. For details, see http://www.hp.com/recycle. On recycled materials in cartridges, see http://www.hp.com/go/recycledcontent.

Specifications

Ink types	Dye-based
Color(s) of printing supplies	Cyan
Print Technology	Ink
Supply type	Cartridges
Print cartridge volume delivered	70 ml
Operating temperature range	15 to 30°C
Storage temperature range	-40 to 60°C
Operating humidity range	20 to 80% RH
Non-Operating Humidity Range	20 to 80% RH
Print Resolution Technologies	TIJ 2.x
Compatibility	HP Smart Tank 500 All-in-One series,HP Smart Tank 510/530/610 Wireless All-in-One series,HP Smart Tank Plus 550/570/650 Wireless All-in-One series printers
Product count per unit	1
Case or master carton quantity	24
Quantity per pallet	2688
Count of carton in pallet	112
UPC number	193905951154
Pallet barcode	20193905951158
Minimum dimensions (W x D x H)	47 x 47 x 150 mm
Minimum dimensions (W x D x H)	1.85 x 1.85 x 5.91 in
Package dimensions (W x D x H)	47 x 47 x 150 mm
Package dimensions (W x D x H)	1.85 x 1.85 x 5.91 in
Case or master carton dimensions (W x D x H)	313 x 217 x 175 mm
Case dimensions (case or master carton)	12.32 x 8.54 x 6.89 in
Pallet dimensions ($W \times D \times H$)	1016 x 1219.2 x 1354.1 mm
Pallet dimensions	40 x 48 x 53.31 in
Case weight (case or master carton)	2.89 kg
Package weight	0.11 kg
Package weight	0.25 lb
Pallet weight	358.5 kg
Pallet weight	790.4 lb

Page Yield

8000

What's in the box

Ink bottle

Additional specifications

Cartridge Colors	Cyan
Case weight (case or master carton, imperial)	6.37 lb
Count of cartons per pallet layer	16
Count of layers in pallet	7
Country of origin	Made in Malaysia, China, Singapore
Operating temperature range	59 to 86°F
Package count	1
Page yield (color)	~8,000 pages
Page yield footnote	Black and composite color average per bottle (cyan/magenta/yellow) results based on HP methodology from the simulation of continuous printing of ISO/IEC 24712 test pages. Not based on ISO/IEC 24711 test process. An additional black ink bottle is required to print 8,000 color test pages. Actual yield varies based on content of printed pages and other factors. Some ink from included bottles is used to start up the printer. For more information about fill and yield, see http://www.hp.com/go/learnaboutsupplies.
Print technology	HP Thermal Inkjet
Product subgroup	Standard Capacity Ink Cartridges
Segment	GT/Smart Tank
Selectability	31
Smaller master carton barcode	10193905951151
Storage temperature range	-40 to 140°F
Subgroup	Standard Capacity Cartridges
UNSPSC code	44103105
Weight	0.1 kg
Weight	0.22 lb

Generated by Dynamic Collateral Tool – (ww-en) – Dec 24, 2019 6:37 AM UTC+0000