

4XEM USB-C 4K Triple Display Docking Station with 65W Power Delivery

4XEM Part- 4XUG39PD1



Introducing the ultimate productivity tool for your workspace: the USB-C 4K Triple Display Docking Station. With 65W Power Delivery, you'll never have to worry about running out of power while you work. The docking station features 1 HDMI 1.4 port, 1 HDMI 1.2 port, 1 DVI-I SL port, 1 USB 3.0 Fast Charge Type A port, 3 USB-A 3.0 ports, 2 USB 3.0 Type C ports, 1 RJ-45 Gigabit Network port, and 1 4 pole TRRS Phono Jack for audio in and out.

Connect multiple displays to increase your productivity and improve your workflow. Stay connected with fast and reliable Gigabit Networking and take advantage of lightning-fast data transfer speeds with USB 3.0. Optimize your audio with the 4 pole TRRS Phono Jack for audio in and out. This Docking Station is perfect for professionals, gamers, and anyone looking to streamline their workflow and increase their productivity.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104    [tschaus@4xem.com](mailto:tschaus@4xem.com)



## Features

- **4K Triple Display support:** The USB-C 4K Triple Display Docking Station supports resolutions of up to 4K on three displays, allowing for seamless multitasking and improved productivity.
- **65W Power Delivery:** The dock has a 65W power delivery that can charge laptops, tablets, and other devices quickly and efficiently.
- **HDMI 1.4 and HDMI 1.2 ports:** The dock has one HDMI 1.4 port and one HDMI 1.2 port, allowing for the connection of multiple displays.
- **DVI-I SL port:** The dock also has a DVI-I SL port, providing additional display connectivity options.
- **USB 3.0 Fast Charge Type A port:** The dock has a USB 3.0 Fast Charge Type A port, which can quickly charge devices such as smartphones and tablets.
- **USB-A 3.0 ports:** The dock has three USB-A 3.0 ports, providing additional connectivity options for peripherals such as keyboards, mice, and external hard drives.
- **USB 3.0 Type C ports:** The dock has two USB 3.0 Type C ports, allowing for the connection of newer devices such as laptops and smartphones.
- **RJ-45 Gigabit Network port:** The dock has an RJ-45 Gigabit Network port, allowing for a wired internet connection for stable and fast internet access.
- **4 pole TRRS Phono Jack:** The dock has a 4 pole TRRS Phono Jack, providing audio in and out support.

### Application

- Home theatre
- Small business
- Multi-Screen Display
- Device charging

**4XEM Products Are Available At Your Favorite Online Retailers**





**DATA SHEET**

Warranty Information	Warranty	2 Years
Features/Hardware	4K Support Displays Supported USB Ports Fast-Charge Port(s) Network SD Card Reader Audio Power Delivery Lock Slot Industry Standards  Chipset ID	Yes 3 6 Yes Yes No Yes 65W No HDMI 1.2, 1.4 DVI-I SL HDCP 1.4 Power Delivery (PD 2.0) Battery Charging (BC 1.2) DisplayLink - DL3900 Fresco Logic - FL5002 Genesys Logic - GL3253
Connector(s)	Host Bus Type Host Connector Host Connector Cable Connector Type(s)	USB 3.1 Gen 1 (5Gbps) USB Type-C Detachable 1x HDMI 1.4 (10.2Gbps - Alt-Mode Required from Host) 1x HDMI 1.2 (4.95 Gbps) 1x DVI-I SL (4.95 Gbps) 1x USB Type-A (5Gbps - Fast Charge) 3x USB Type-A (5Gbps) 2x USB Type-C (5Gbps) 1x RJ-45 (10/100/1000Mbps) 1x 4-Pole TRRS 3.5mm Phono Jack (Audio In/Out Combo)
Performance	Maximum Digital Resolutions  Maximum Analog Resolutions Audio Specification	HDMI 1.4: 4K UHD (3840 x 2160 @ 30Hz, 8bpc) HDMI 1.2/DVI-I SL: 2048x1152 @ 60Hz, 8bpc each DVI-I (Analog Mode): 1920 x 1200 @ 60Hz, 8bpc 5.1-ch Surround (via HDMI) 2-ch Stereo (via 3.5mm Phono Jack)
Software	OS Compatibility	Windows 7, 8, 8.1, 10 Mac OS X Chrome OS
Power	Power Source Power Adapter Style Power Consumption Input Voltage Power Delivery	AC Adapter Included (100-240 VAC, 50/60Hz, 2A Max , CLASS II) Brick 100W 20V DC @ 5A 65W
Physical Characteristics	Color Shell Material Host Cable Length  Buttons/Switches LED Indicators  Power Cable Length  Product Height Product Width Product Length Weight of Product	Black ABS Plastic C-C Cable: 3.0 ft [0.91 m] C-A Cable: 3.0 ft [0.91 m] None Power: Blue Network: Green AC In: 4.58 ft [1.40 m] DC Out: 3.83 ft [1.17 m] 8.78 in [223 mm] 1.02 in [26 mm] 3.15 in [80 mm] 11.92 oz [338 g]
Environmental	Operating Temperature Storage Temperature	32°F to 104°F [0°C to 40°C] @ 10%-90% RH (Non-Condensing) 14°F to 158°F [-10°C to 70°C] @ 10%-90% RH (Non-Condensing)
Packaging Information	Package Type Package Height Package Width Package Length Shipping (Package) Weight	Box 8.82 in [224 mm] 9.67 in [245.5 mm] 3.84 in [97.5 mm] 3.34 lbs [1.51 kg]
What's in the Box	Included in Package	1x USB-C Triple Display Universal Docking Station 1x USB Type-C to Type-C Cable (E-Mark Chip) 1x USB Type-C to Type-A Cable 1x DVI to VGA Adapter 1x Quick Start Guide 1x 20V DC/5A 100W Power Adapter 1x NEMA 5-15P to IEC 320 C13 Power Cord
Notes / Special Requirements	Notes	*HDMI 4K port requires HDMI Alt-Mode Support from host via USB-C connection. When connecting to host with USB Type-A cable, USB-PD is unavailable and only 2 displays will function."

\* Product appearance and specifications are subject to change without notice.

\* Same day shipping is only available for orders shipping within the United States.

