# Lose Yourself in the Curve

When it comes to the P34hc WQHD Curved Monitor, bigger really is better. Because its immersive, ultrawide screen keeps you focused, you're likely to be less distracted and up to 33% more productive compared to a smaller screen.



\*Product image may differ from actual product

#### Ultrawide Screen. Ultra Immersive.

Immerse yourself in this 34-inch diagonal curved display with sharp WOHD resolution and an integrated speaker. And with all that space available, you'll can see more in one screen, making this monitor ideal for multitaskers and those that want to increase productivity.

#### Clear the Clutter

Now you can focus more on your work instead of the nest of cables on your desk. Because one USB-C™ cable not only transfers data and video, it also charges your PC, you can say goodbye to cord clutter.

#### Work Comfortably

No matter how many great features a monitor may have, if you can't position it comfortably, your productivity may suffer. That's why ergonomics are so important. Rest assured, with adjustable height, tilt and slide settings, you'll be able to find the screen position that's most comfortable for you.

# Sustainability in action

#### Responsibly Made

Feel good about what's on your desk while benefiting from efficient energy performance. This responsibly made curved monitor is ENERGY STAR® certified, TCO certified and EPEAT® registered.



# **Featuring**







**Ports For Everything**Plenty of ports to connect multiple devices.

**Peace of Mind Included**3-year limited warranty included.



# **Specifications**

#### Display specifications

Display size

Display size (diagonal, metric)

86.36 cm (34")

Aspect ratio

21.91

Curvature

1500R

Native resolution

WQHD (3440 x 1440) Resolution (maximum)

WQHD (3440 x 1440 @ 60 Hz)

Resolutions supported

640 x 480; 800 x 600; 1024 x 768; 1280 x 720; 1280 x 800; 1280 x 1024; 1440 x 900; 1600 x 900;

1680 x 1050; 1920 x 1080; 1920 x 1200; 3440 x 1440

Panel type

Bezel

3-sided micro-edge

Panel active area 33.37 x 79.72 cm

Panel bit depth

Display colors

Up to 16.7 million colors supported (through FRC technology)

Display color gamut

85% NTSC

Display scan frequency

48-100 Hz (Vertical) 30-160 KHz (Horizontal)

Response time

5ms GtG (with overdrive)1

**Brightness** 

250 nits1 Contrast ratio

3500:1 (Static)1 5000000:1 (Dynamic)1

Pixel pitch 0.231 mm

Pixels per inch (ppi)

110 ppi Viewing angle

178° (Vertical) 178° (Horizontal)

Backlight type

Edge-lit Display features

Low blue light mode; Anti-glare; Height adjustable

**Display User Control Options** 

Exit; Information; Management; Power; Input control; Menu control; Brightness+; Image;

Management software

HP Display Center

Low blue light modes

Yes (TÜV certified) Flicker-free

Screen treatment Anti-alare

Hardness

VESA mount

100 mm x 100 mm

Height adjustment range

100 mm

Tilt

-5 to +21° Swivel

No swive

Pivot No pivot

Camera

No integrated camera

Microphone

Speaker output power

### Connectivity and communications

Port and connectors

1 HDMI 2.0

1 DisplayPort™ 1.2

1 Line Output

1 SuperSpeed USB Type-C\* 5Gbps signaling rate (up to 65W USB Power Delivery, Alt Mode

DisplayPort™ 1.2)

4 SuperSpeed USB Type-A 5Gbps signaling rate

1USB-B

Nο

HDCP

Yes, DisplayPort™, HDMI and USB Type-C™

Power supply

100 - 240 VAC 50/60 Hz

(Internal)

Power consumption

190 W (maximum), 48 W (typical), 0.5 W (standby)

### Logistics and Physical

Product color

Black

Detachable stand

Physical security

Security lock-ready Dimensions without Stand (WxDxH)

80.94 x 11.21 x 36.69 cm

Dimensions with stand (W x D x H)

80.94 x 23.49 x 51.8 cm

10.51 kg (With stand.)

Packaged Dimensions (W x D x H)

37.4 x 8.86 x 18.9 in 95 x 22.5 x 48 cm

Packaged weight

#### Certification and compliance

Energy efficiency

ENERGY STAR® certified

**Ecolabels** 

EPEAT® registered4 Environmental specifications

Arsenic-free display glass; Low halogen; Mercury-free display backlights; TCO Certified; TCO

Certified Edge

Certifications

BIS: CB: CCC: CE: CEL: cTUVus: EAC: EPA: FCC: GS Mark: ISO 9241-307: KC/KCC: NOM: RCM:

VCCI; WEEE; CEL Grade 3; WW application; ICE<sup>5</sup>

Operating temperature range

41 to 95°F

Operating humidity range

20 to 80% non-condensing

#### **Additional information**

Monitor; DisplayPort™ cable; HDMI cable; Warranty card; Quick Setup Poster; 1 USB Type-C® to Type-C cable; AC power cord



#### **Footnotes**

## **Messaging Footnotes**

<sup>1</sup> Based on HP commission ASL Productivity study, October 2019.

### **Technical Specifications Footnotes**

- <sup>1</sup>All specifications represent the typical specifications provided by HP's component manufacturers, actual performance may vary either higher or lower.
- <sup>2</sup> External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.
- <sup>3</sup> Lock is sold separately.
- <sup>4</sup> EPEAT\* 2019 registered where applicable. EPEAT \* registration varies by country. See www.epeat.net for registration status by country.
- $^{5}$  Monitors produced from June 2024 comply with China regulation GB 21520-2023.