

# Product datasheet

Specifications



APC Smart-UPS On-Line, 3kVA, Rackmount 2U, 230V, 6x C13+2x C19 IEC outlets, SmartSlot, Extended runtime, W/rail kit, W/O Lithium-ion external battery

SRT3000UXI-LI

## Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

## Main

Main Input Voltage	230 V
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	2700 W
Rated power in VA	3000 VA
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
output connection type	6 IEC 60320 C13 2 IEC 60320 C19
number of rack unit	2U
Cable length	1.8 m
Number of cables	1
Provided equipment	CD with software Communication cable Documentation CD Installation guide Removable support feet USB cable Warranty card
Range of product	Smart-UPS On-Line

## Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Extended runtime	1

## General

UPS type	Double conversion online
product web sub-family	High density
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

## Physical

Colour	Black
Height	43.2 cm
Width	8.5 cm
Depth	50.8 cm
Net weight	22 kg
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Vertical

## Input

Network frequency	40...70 Hz auto-sensing
Input voltage limits	50...150 V 40% load 80...150 V

## Output

Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2700 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Wave type	Sine wave
Harmonic distortion	Less than 2 %
Crest factor	3 : 1
Bypass type	Built-in bypass

## Conformance

Product certifications	CE EAC UK PSTI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing

Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.0000000000...15240.0000000000 m
Acoustic level	50 dBA
Heat dissipation	317 Btu/h
IP degree of protection	IP20

## Communications & Management

Free slots	1
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

## Surge Protection and Filtering

Surge energy rate	432 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.6 cm
Package 1 Width	74.9 cm
Package 1 Length	59.4 cm
Package 1 Weight	29.6 kg

## Logistical informations

Country of origin	PH
-------------------	----

## Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

## Resource performance

Energy Efficient Product

Take-Back Program Available

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)