

# Product data sheet

Specifications



APC Smart-UPS, Line Interactive,  
500VA, Lithium-ion, Rackmount  
1U, 230V, 4x IEC C13 outlets,  
Network Card, Short Depth

SCL500RM1UNC

## Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock

## Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	400 W
Rated power in VA	500 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C14
output connection type	4 IEC 60320 C13
Number of rack unit	1U
Battery type	Li-Ion (Lithium-Ion)
Provided equipment	Installation guide Rack mounting support rails USB cable
Range of product	Smart-UPS

## Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended runtime	0
Battery design life	8...10 year(s)
Battery charger power	10 W rated

## General

Redundant	No
-----------	----

## Physical

Colour	Black with silver front bezel
Height	4.4 cm
Width	43.2 cm
Depth	23.2 cm
Net weight	4.1 kg
Mounting preference	No preference
mounting mode	Rack-mounted
USB compatible	Yes

## Input

Input protection type	Circuit breaker
Input voltage limits	208...253 V
Network frequency	50/60 Hz +/- 3 Hz auto sensing

## Output

Harmonic distortion	Less than 5 %
Maximum configurable power in VA	500 VA
Maximum configurable power in W	400 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

## Conformance

Product certifications	C-Tick CE EAC UK PSTI
Equipment protection policy	Lifetime : \$150000
Standards	EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Acoustic level	45 dBA
Heat dissipation	41.61 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
ambient air temperature for storage	-15...45 °C
Storage altitude	0.0000000000...7620.0000000000 m
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing

## Communications & Management

<b>Control panel</b>	LED status display with on line : on battery : replace battery and building wiring fault
<b>Free slots</b>	0
<b>Preinstalled device</b>	Network management card 3
<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

<b>Surge energy rate</b>	510 J
<b>Noise suppression</b>	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	16.8 cm
<b>Package 1 Width</b>	33.7 cm
<b>Package 1 Length</b>	59 cm
<b>Package 1 Weight</b>	6.49 kg

## Contractual warranty

<b>Warranty</b>	5 year repair or replace
-----------------	--------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)