

## PDU Power Cord, C13 to P-Lock C14 - Heavy-Duty, 15A, 250V, 14 AWG, 3 ft. (0.9 m), Black

MODEL NUMBER: P005-E03



Connects a computer, server or switch to a PDU with a P-Lock C13 or C39 power connector and extends your existing power connection by 3 ft.

### Features

#### C13-to-C14 Power Cable for Network Devices That Require a Heavy-Gauge Connection

This power extension cord features 14 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. The P005-E03 can be used to power a computer, server, switch or other device commonly found in a small data center, office workstation or other lower-amp application. The three-foot (0.9-meter) length helps reduce cable clutter by providing a tailor-made fit between the device and the PDU in a crowded rack enclosure.

#### Forms a Special Locking Connection with a P-Lock Outlet

The P-Lock C14 connector forms a secure connection with a PDU with a P-Lock outlet, including Eaton G4 and newer PDUs with C13 and C39 outlets. The P-Lock connection helps reduce costly downtime caused by accidental cable disconnections in a crowded rack or PDU space. The P005-E03 lets you replace a non-locking C14/C13 cable or upgrade an entire PDU application by pairing with an Eaton PDU or other PDU with P-Lock outlets.

### Highlights

- Recommended for powering computers, servers and other network devices
- P-Lock C14 connector eliminates accidental cable disconnections in a crowded PDU
- Thick 14 AWG wire gauge manages high power levels required for larger equipment
- 3 ft. length allows flexibility in mounting devices within a rack while avoiding cable clutter
- PDU-style cord replaces or upgrades non-locking power cable provided by manufacturer

### Package Includes

P005-E03 PDU Power Cord, C13 to P-Lock C14, 3 ft. (0.9 m), Black

## Specifications

| OVERVIEW                    |                                                   |
|-----------------------------|---------------------------------------------------|
| UPC Code                    | 037332292742                                      |
| Product Type                | PDU Power Cord                                    |
| Device Compatibility        | Computer; Monitor/HDTV; Printer; Server; UPS; PDU |
| Country/Region              | North America                                     |
| INPUT                       |                                                   |
| Maximum Input Amps          | 15                                                |
| Voltage Compatibility (VAC) | 100-250                                           |



Powering Business Worldwide

TRIPP LITE  
SERIES

| CONNECTIONS                        |                              |
|------------------------------------|------------------------------|
| Side A - Connector 1               | IEC-320-C14                  |
| Side B - Connector 1               | IEC-320-C13                  |
| PHYSICAL                           |                              |
| Plug Color                         | Black                        |
| Cable Jacket Color                 | Black                        |
| Connector Color                    | Black                        |
| Cable Jacket Material              | PVC                          |
| Cable Jacket Rating                | VW-1                         |
| Power Cord Jacket Type             | SJT                          |
| Cable Outer Diameter (OD)          | 9.3mm                        |
| Number of Conductors               | 3                            |
| Wire Gauge (AWG)                   | 14                           |
| Wire Gauge (OD - mm <sup>2</sup> ) | 2.08                         |
| Cable Length (ft.)                 | 3                            |
| Cable Length (m)                   | 0.91                         |
| Shipping Dimensions (hwd / in.)    | 10.00 x 7.09 x 0.50          |
| Shipping Weight (lbs.)             | 0.44                         |
| Shipping Weight (kg)               | 0.20                         |
| Unit Dimensions (hwd / in.)        | 10.000 x 7.990 x 0.500       |
| ENVIRONMENTAL                      |                              |
| Operating Temperature Range        | 23° to 158°F (-5° to 70°C)   |
| Storage Temperature Range          | 14° to 140°F (-10° to 60°C)  |
| Relative Humidity                  | 35 TO 85% RH, Non-Condensing |
| FEATURES & SPECIFICATIONS          |                              |
| Antibacterial                      | No                           |
| Angled Plug                        | No                           |
| High Voltage                       | Yes                          |
| Locking Plug                       | Yes                          |
| Coiled Power Cord                  | No                           |
| STANDARDS & COMPLIANCE             |                              |
| Product Certifications             | cUL Listed; UL Listed        |

WARRANTY & SUPPORT

|                                        |                           |
|----------------------------------------|---------------------------|
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty |
|----------------------------------------|---------------------------|

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.