

## USB-C Right Angle Adapter (M/F) , 3.1, Gen 2, 10 Gbps, Thunderbolt 3 Compatible, 3A Rating

MODEL NUMBER: U420-000-F-UD



USB-C to USB-C adapter connects an existing USB-C cable or device to your laptop, MacBook or Chromebook's USB-C or Thunderbolt 3 port.

### Features

**USB Type-C to USB Type-C Adapter Connects an Existing USB-C Device to Your USB-C Laptop** This compact adapter allows you to connect USB-C devices to your smartphone, tablet, laptop, MacBook, Chromebook or Ultrabook's USB-C or Thunderbolt 3 port. External hard drives, hubs, wall chargers and other peripherals with USB-C ports will be able to communicate with your computer or other USB-C mobile device.

**Transfers Data and Charges Devices at Lightning-Fast USB 3.1 Gen 2 Speeds** The adapter supports USB 3.1 Gen 2 data transfer rates up to 10 Gbps, which is twice as fast as USB 3.1 Gen 1. It also provides power output up to 3 amps (60 watts), which is sufficient for fast-charging, syncing and powering most devices.

**Reversible USB-C Connectors Attach in Either Direction** Unlike traditional USB cables that connect in only one direction, the reversible USB-C male connectors plug into a USB-C or Thunderbolt 3 port in either direction for a fumble-free connection every time. The unit is backward compatible with USB 3.0 devices.

**Right-Angle USB-C Connector Makes Installation in Tight Spaces Easier** The space-saving right-angle female connector is easy to install in confined spaces, such as behind your computer desk or workstation. You can install the unit facing either up or down to gain convenient vertical access to that USB-C connection.

### Highlights

- Right-angle USB-C plug permits easier connection in confined or hard-to-reach spaces
- Supports USB 3.1 Gen 2 speeds up to 10 Gbps to ensure lightning-fast data transfers
- Provides 3A (60W) power output for charging, syncing and powering mobile devices
- Reversible USB-C plugs connect in either direction for immediate no-fuss use
- USB-C to USB-C adapter compatible with all USB-C and Thunderbolt 3 devices

### Applications

- Charge and sync a USB-C or Thunderbolt 3 mobile device from a USB-C wall charger located behind furniture or another hard-to-reach space
- Transfer data between an external hard drive and your laptop or computer
- Connect your laptop to a docking station or hub with a USB-C or Thunderbolt 3 port

### System Requirements

- Devices with USB-C or Thunderbolt 3 ports (USB 3.1 Gen 2 compatibility required to achieve USB 3.1 Gen 2 speeds)

### Package Includes

- U420-000-F-UD USB-C to C Adapter (M/F)

## Specifications

| OVERVIEW             |              |
|----------------------|--------------|
| UPC Code             | 037332218360 |
| CONNECTIONS          |              |
| Side A - Connector 1 | USB C (MALE) |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                                     |
|--------------------------------------|-------------------------------------|
| Side B - Connector 1                 | USB C (FEMALE) - RIGHT ANGLE        |
| Connector Plating                    | Gold                                |
| Contact Plating                      | Gold                                |
| <b>PHYSICAL</b>                      |                                     |
| Color                                | Black                               |
| Material of Construction             | PVC                                 |
| Shipping Dimensions (hwd / in.)      | 5.90 x 3.90 x 0.50                  |
| Shipping Dimensions (hwd / cm)       | 14.99 x 9.91 x 1.27                 |
| Shipping Weight (lbs.)               | 0.02                                |
| Shipping Weight (kg)                 | 0.01                                |
| Unit Packaging Type                  | Polybag                             |
| <b>ENVIRONMENTAL</b>                 |                                     |
| Operating Temperature Range          | 32° to 113°F (0° to 45°C)           |
| Storage Temperature Range            | 14° to 158°F (-10° to 70°C)         |
| Operating Humidity Range             | 10% to 85% RH, Non-Condensing       |
| Storage Humidity Range               | 5% to 90% RH, Non-Condensing        |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                     |
| USB Specification                    | USB 3.1 Gen 2 (up to 10 Gbps)       |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                     |
| Product Compliance                   | RoHS; CE (Europe); REACH; FCC (USA) |
| <b>WARRANTY &amp; SUPPORT</b>        |                                     |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty           |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.