

Product datasheet

Specifications



APC Easy Rack PDU, Metered,
0U, 1 Phase, 7.4kW, 230V, 32A,
20 x C13 and 4 x C19 outlets,
IEC60309 2P+E inlet

EPDU1132M

Overview

Lead time Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Metered
Cord length	3.00 m
Number of cables	1
Provided equipment	Installation guide Toolless mounting kit User manual Vertical mounting brackets

Complementary

Input Voltage	200 V 208 V 230 V
Height	117.5 cm
Width	6.2 cm
Output Voltage	230 V
Depth	4.44 cm
Net weight	3.72 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 2P + E
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Permissible voltage	220...240 V
Max line current	32 A
Input current limits	32 A
Load capacity	7360 VA
Network frequency	50/60 Hz

Outlet type and quantity	20 IEC 60320 C13 4 IEC 60320 C19
--------------------------	-------------------------------------

Environment

Product certifications	CE TÜV EAC RCM
------------------------	-------------------------

Ambient air temperature for operation	-5...45 °C
---------------------------------------	------------

Relative humidity	5...95 %
-------------------	----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient air temperature for storage	-25...65 °C
-------------------------------------	-------------

Storage Relative Humidity	5...95 %
---------------------------	----------

Storage altitude	0.0000000000...15240.0000000000 m
------------------	-----------------------------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	132 cm
------------------	--------

Package 1 Width	11 cm
-----------------	-------

Package 1 Length	16 cm
------------------	-------

Package 1 Weight	4.48 kg
------------------	---------

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)


[Guide to assess a product's sustainability >](#)



RoHS/REACH

Well-being performance

 Reach Free Of Svhc

 Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)