

Product datasheet

Specifications



APC Back-UPS, 650VA, Tower, 230V, 4 IEC C13 Outlets , User Replaceable Battery

BK650EI

Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	400 W
Rated power in VA	650 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C14
output connection type	3 IEC 60320 C13 1 IEC 60320 C13 surge 2 IEC Jumpers surge
Number of cables	2
Battery type	Lead-acid battery
Provided equipment	CD with software Documentation CD 2 x detachable IEC C13 to IEC C14 power cords USB cable

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Number of battery replacement quantity	1
Battery voltage	12 V
Battery capacity	9.0 Ah
Battery charger power	12 W rated
Battery power in VAh	111 VAh capacity 111 VAh runtime
Battery life	4...6 year(s)
Replacement battery	RBC17

Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
-------------------------------	---

Extended runtime	0
-------------------------	---

General

Number of power module free slots	0
--	---

Number of power module filled slots	0
--	---

Redundant	No
------------------	----

Physical

Colour	Beige
---------------	-------

Height	16.5 cm
---------------	---------

Width	9.1 cm
--------------	--------

Depth	28.4 cm
--------------	---------

Net weight	6.03 kg
-------------------	---------

Mounting location	Front
--------------------------	-------

Mounting preference	No preference
----------------------------	---------------

Mounting mode	Not rack-mountable
----------------------	--------------------

Two post mountable	0
---------------------------	---

USB compatible	Yes
-----------------------	-----

Input

Network frequency	47...63 Hz 50/60 Hz +/- 3 Hz auto-sensing
--------------------------	--

Input voltage limits	160...286 V adjustable 180...266 V
-----------------------------	---------------------------------------

Maximum input current	7 A
------------------------------	-----

Switching current capacity	7 A
-----------------------------------	-----

Output

Maximum configurable power in W	400 W
--	-------

Output frequency	47...63 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
-------------------------	--

UPS type	Standby
-----------------	---------

Wave type	Stepped approximation to a sinewave
------------------	-------------------------------------

Maximum configurable power in VA	650 VA
---	--------

Transfer time	6 ms typical : 10 ms maximum
----------------------	------------------------------

Conformance

Product certifications	A-Tick C-Tick CE GOST NEMKO
-------------------------------	---

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
------------------	--

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.0000000000...15240.0000000000 m
Acoustic level	45 dBA

Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	310 J
--------------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	49.400 cm
Package 1 Width	18.500 cm
Package 1 Length	41.500 cm
Package 1 Weight	7.310 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	35
Package 2 Height	132.500 cm
Package 2 Width	100.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	267.850 kg
SCC14	10731304219788

Logistical informations

Country of origin	PH
--------------------------	----

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)