

Product datasheet

Specifications



Power Cord, C19 to IEC309 16A, 2.5m

AP9876

Overview

Lead time Usually in Stock

Main

Product or component type Power cord
Input Connection Type IEC 60309 16 A
Cable length 2.5 m
Number of cables 1

Physical

Colour Black
Net weight 0.24 kg
Mounting preference No preference
Mounting mode Not rack-mountable

Input

Network frequency 50/60 Hz
Permissible voltage 90...250 V
Max line current 16 A
Input current limits 16 A

Output

Max current draw 16 A
Number of power socket outlets 1 IEC 60320 C19
Protection type Without circuit breaker

Conformance

Product certifications VDE

Environmental

Ambient air temperature for operation 0...45 °C
Relative humidity 0...95 %
Operating altitude 0...10000 ft
Ambient air temperature for storage -25...65 °C

Storage Relative Humidity	0...95 %
---------------------------	----------

Storage altitude	0.0000000000...15240.0000000000 m
------------------	-----------------------------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	5.1 cm
------------------	--------

Package 1 Width	10.2 cm
-----------------	---------

Package 1 Length	20.3 cm
------------------	---------

Package 1 Weight	0.299 kg
------------------	----------

Unit Type of Package 2	CAR
------------------------	-----

Number of Units in Package 2	10
------------------------------	----

Package 2 Height	23.3 cm
------------------	---------

Package 2 Width	32.5 cm
-----------------	---------

Package 2 Length	53 cm
------------------	-------

Package 2 Weight	5.1 kg
------------------	--------

Unit Type of Package 3	PAL
------------------------	-----

Number of Units in Package 3	10
------------------------------	----

Package 3 Height	143.99 cm
------------------	-----------

Package 3 Width	100 cm
-----------------	--------

Package 3 Length	120 cm
------------------	--------

Package 3 Weight	5.1 kg
------------------	--------

Logistical informations

Country of origin	CN
-------------------	----

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)




Take-back Transparency RoHS/REACH

Resource performance

 Take-Back Program Available

Well-being performance

 Lead Free

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

[End of Life Information](#)