

15 ft Cat5e Blue Snagless Shielded RJ45 F/UTP Cat 5e Patch Cable - 15ft Patch Cord

StarTech ID: S45PATCH15BL



StarTech.com's Cat5e Shielded F/UTP Snagless Patch Cables offer reliable Ethernet connections. This 15ft cable meets or exceeds all Category 5e specifications and features a durable blue jacket that simplifies departmental color coding while providing rugged flexibility for network connections.

To reduce susceptibility to EMI/RFI and near end cross-talk, the patch cable is shielded throughout the length of the cable, as well as around the RJ45 connectors. Our Cat5e Shielded F/UTP Snagless Patch Cables also feature a snagless design that protects the RJ45 clip from snagging during installation, as well as PVC molded strain relief that prevents the RJ45 connector termination point from bending at sharp angles - reducing the risk of cable damage.

StarTech.com's Cat5e Shielded F/UTP Snagless Patch Cable is constructed of top quality materials (100% copper conductors, 24 Gauge Wire, 50 micron Gold Connectors) to ensure optimum durability and performance, and backed by our Lifetime Warranty.

Applications

- Designed for Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems and other applications requiring high-speed cables
- Works with 1000 BASE-T, 100 BASE-T, 10 BASE-T, Token Ring, ATM & ISDN networks
- Suited for industrial applications



Features

- StarTech.com Category 5e shielded cables are manufactured to meet or exceed CAT5e specifications
- Molded strain relief and stranded wires for added flexibility and durability
- Colored Hoods for departmental color coding and easy identification

Technical Specifications

Warranty Lifetime

Cable Jacket Type PVC - Polyvinyl Chloride

Cable Type Shielded Snag-less

Fire Rating CMG Rated (General Purpose)

Number of Conductors 4 pair F/UTP

Connector A 1 - RJ-45 Male

Connector B 1 - RJ-45 Male

Cable Length 15 ft [4.6 m]

Color Blue

Product Length 15 ft [4.6 m] Wire Gauge 24 AWG

Shipping (Package) Weight 0.4 lb [0.2 kg]

Certifications, Reports and Compatibility





