VA2626wm

26" (25.5" VIEWABLE) VALUE SERIES WIDESCREEN LCD

WITH 5MS VIDEO RESPONSE

Feature-rich big screen.

ViewSonic's 26" (25.5" viewable) VA2626wm LCD brings high-performance, widescreen displays to home office users, students and others who want a great desktop display. In addition to Super-HD 1920x1200 resolution, this big 26-inch LCD also features EXTREME CLARITY, AMAZING COLOR and FAST 5MS CLEARMOTIV® VIDEO RESPONSE. Enjoy beautiful graphics and view spreadsheets in unbelievable clarity. Enhance your desktop with the stylish, slim-bezel design and enhance your productivity with the ability to VIEW TWO FULL-SIZE DOCUMENTS SIDE-BY-SIDE or work in multiple applications simultaneously on the widescreen display. Only 3.6" deep without the stand this display's VESA® wall-mount compliance allows the VA2626wm to fit beautifully into any office décor. Desktop users can enjoy panoramic performance without breaking their budgets.





6000:1

ENHANCE YOUR VIEW AND PRODUCTIVITY

- > Fast 5ms video response delivers superior picture clarity
- > Full 25.5" viewable widescreen
 Displays a full, flat 25.5" viewable area with crisp detail and fully saturated color.
- > 1920x1200 native resolution
 Incredible image detail for sharp text and graphics.
- > Stylish slim-bezel design An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > OptiSync® digital/analog inputs expand your connectivity
 Multi-mode input technology supports both digital (DVI) and analog
 (VGA) signals for ultimate compatibility and configuration flexibility.
- OSD/power lock secures your settings
 Prevents changes to monitor settings and maintains an optimized image.
- > OnView® controls for superior screen adjustability Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > Multimedia enhanced
 Save desk and workspace and enjoy rich,
 stereo sound with built-in stereo speakers.
- > Windows Vista approved
- > PC and Mac® compatible
- > TCO'03 and ENERGY STAR® qualified





VA2626wm

26" (25.5" VIEWABLE) VALUE SERIES WIDESCREEN LCD WITH 5MS VIDEO RESPONSE





Display Area 21.7* horizontal x 13.5* vertical; 25.5* diagonal Optimum Resolution 1920x1200	LCD	Туре	26" (25.5" viewable) color TFT active matrix WUXGA LCD
Contrast Ratio 800:1 static (typ), 6,000:1 dynamic Viewing Angles 170° horizontal, 160° vertical Response Time 5ms (typ) Light Source Long life, 50,000 hrs. (min) Brightness 450 cd/m2 (typ) Panel Surface Anti-glare Anti-glare		Display Area	21.7" horizontal x 13.5" vertical; 25.5" diagonal
Viewing Angles 170° horizontal, 160° vertical Response Time 5ms (typ)		Optimum Resolution	1920×1200
Response Time Sms (typ) Light Source Long life, 50,000 hrs. (min) Brightness 450 cd/m2 (typ) Panel Surface Anti-glare Anti-glare Anti-glare Frequency Fh: 24-82kHz, Fy: 50-85Hz Sync H/V separated (TTL) COMPATIBILITY PC VGA up to 1920x1200 non-interlaced Mac** Power Mac** G3/G4/G5/Mac mini up to 1920x1200 CONNECTOR Analog/Digital 15-pin mini D-sub/DVI-D, 19-pin HDMI Power 3-pin AC plug (CEE22) POWER Voltage AC 100-240V (universal), 50/60Hz (auto switch) Consumption 64W (typ); below 1W in standby mode AUDIO Speakers 2x2.5 watts CONTROLS Basic Power, 1, down, up, 2 OnView* Auto image adjust, contrast, brightness, input select (analog, digital, HDMI), ViewMatch* color adjust (sRGB, 9300K, 6500K - default, 5400K, RGB), information, manual image adjust (H. size, H. position, V. position, fine tune, sharpness, display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt 5*7+20* OPERATING Temperature 41-95*F (5-35*C) CONDITIONS Humidity 20-80% (non-condensing) DIMENSIONS Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) Wx H x D) Physical without stand 23.5" x 16.0" x 3.6" (596mm x 406mm x 93mm) WEIGHT Net with stand 16.3 lb. (7.4 kg) Net with stand 16.3 lb. (7.4 kg) Net with stand 22.2 lb. (10.1 kg) REGULATIONS U., eU., FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR, PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.		Contrast Ratio	800:1 static (typ), 6,000:1 dynamic
Light Source Long life, 50,000 hrs. (min) Brightness 450 cd/m2 (typ) Panel Surface Anti-glare Anti-glare Analog/Digital RGB analog (75 ohms, 0.7 Vp-p)/HDMI (HDCP) Frequency F _h : 24-82kHz, F _V : 50-85Hz Sync H/V separated (TTL) COMPATIBILITY PC VGA up to 1920x1200 non-interlaced Mac®* Power Mac™ G3/G4/G5/Mac mini up to 1920x1200 CONNECTOR Analog/Digital 15-pin mini D-sub/DVI-D, 19-pin HDMI Power 3-pin AC plug (CEE22) POWER Voltage AC 100-240V (universal), 50/60Hz (auto switch) Consumption 64W (typ); below 1W in standby mode AUDIO Speakers 2x2.5 watts CONTROLS Basic Power, 1, down, up, 2 OnView® Auto image adjust, contrast, brightness, input select (analog, digital, HDMI), ViewMatch® color adjust (sRGB, 9300K, 6500K − default, 5400K, RGB), information, manual image adjust (H. size, H. position, V. position, fine tune, sharpness, display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt -5°/+20° OPERATING Temperature 41-95°F (5-35°C) CONDITIONS Humidity 20-80% (non-condensing) DIMENSIONS (W x H x D) Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) WEIGHT Net with stand 16.3 lb. (7.4 kg) Net with stand 22.2 lb. (10.1 kg) REGULATIONS REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR® FSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards		Viewing Angles	170° horizontal, 160° vertical
Brightness 450 cd/m2 (typ)		Response Time	5ms (typ)
Panel Surface		Light Source	Long life, 50,000 hrs. (min)
VIDEO INPUT Analog/Digital RGB analog (75 ohms, 0.7 Vp-p)/HDMI (HDCP) Frequency Fh: 24~82kHz, F _v : 50~85Hz Sync H/V separated (TTL) COMPATIBILITY PC VGA up to 1920x1200 non-interlaced Mac®* Power Mac™ G3/G4/G5/Mac mini up to 1920x1200 CONNECTOR Analog/Digital 15-pin mini D-sub/DVI-D, 19-pin HDMI Power 3-pin AC plug (CEE22) POWER Voltage AC 100~240V (universal), 50/60Hz (auto switch) Consumption 64W (typ); below 1W in standby mode AUDIO Speakers 2x2.5 watts CONTROLS Basic Power, 1, down, up, 2 OnView® Auto image adjust, contrast, brightness, input select (analog, digital, HDMI), ViewMatch® color adjust (sRGB, 9300K, 6500K – default, 5400K, RGB), information, manual image adjust (H. size, H. position, V. position, fine tune, sharpness, display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt -5°/+20° OPERATING Temperature 41–95°F (5–35°C) CONDITIONS Humidity 20-80% (non-condensing) DIMENSIONS Physical with stand 23.5° x 18.0° x 10.0° (596mm x 480mm x 254		Brightness	450 cd/m2 (typ)
Frequency Sync H/V separated (TTL) COMPATIBILITY PC VGA up to 1920x1200 non-interlaced Mac®* Power Mac™ G3/G4/G5/Mac mini up to 1920x1200 CONNECTOR Analog/Digital 15-pin mini D-sub/DVI-D, 19-pin HDMI Power 3-pin AC plug (CEE22) POWER Voltage AC 100-240V (universal), 50/60Hz (auto switch) Consumption 64W (typ); below 1W in standby mode AUDIO Speakers 2x2.5 watts CONTROLS Basic Power, 1, down, up, 2 OnView® Auto image adjust, contrast, brightness, input select (analog, digital, HDMI), ViewMatch® color adjust (sRGB, 9300K, 6500K - default, 5400K, RGB), information, manual image adjust (H. size, H. position, V. position, fine tune, sharpness, display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt -5°/+20° OPERATING Temperature 41-95°F (5-35°C) CONDITIONS Humidity 20-80% (non-condensing) DIMENSIONS Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) (W x H x D) Physical without stand 23.5" x 18.9" x 10.0" (596mm x 406mm x 93mm) WEIGHT Net with stand 16.3 lb. (7.4 kg) Net with out stand 12.3 lb. (5.6 kg) Gross with stand 22.2 lb. (10.1 kg) REGULATIONS REGULATIONS FREGULATIONS FREGULATIONS LU, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers) ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, ROHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards POWER MANAGEMENT LCD display, video cable, audio cable, power cable,		Panel Surface	Anti-glare
Sync H/V separated (TTL) COMPATIBILITY PC VGA up to 1920x1200 non-interlaced Mac®** Power Mac™ G3/G4/G5/Mac mini up to 1920x1200 CONNECTOR Analog/Digital 15-pin mini D-sub/DVI-D, 19-pin HDMI Power 3-pin AC plug (CEE22) POWER Voltage AC 100-240V (universal), 50/60Hz (auto switch) Consumption 64W (typ); below 1W in standby mode AUDIO Speakers 2x2.5 watts CONTROLS Basic Power, 1, down, up, 2 OnView® Auto image adjust, contrast, brightness, input select (analog, digital, HDMI), ViewMatch® color adjust (sRGB, 9300K, 6500K − default, 5400K, RGB), information, manual image adjust (H. size, H. position, V position, fine tune, sharpness, display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt 5°/+20° OPERATING Temperature 41-95°F (5-35°C) CONDITIONS Humidity 20-80% (non-condensing) DIMENSIONS Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) WEIGHT Net with stand 16.3 lb. (7.4 kg) Net without stand 22.2 lb. (10.1 kg) REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,	VIDEO INPUT	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/HDMI (HDCP)
COMPATIBILITY PC VGA up to 1920x1200 non-interlaced Mac®** Power Mac™ G3/G4/G5/Mac mini up to 1920x1200 CONNECTOR Analog/Digital 15-pin mini D-sub/DVI-D, 19-pin HDMI POWER Voltage AC 100-240V (universal), 50/60Hz (auto switch) Consumption 64W (typ); below 1W in standby mode AUDIO Speakers 2x2.5 watts CONTROLS Basic Power, 1, down, up, 2 OnView® Auto image adjust, contrast, brightness, input select (analog, digital, HDMI), ViewMatch® color adjust (sRGB, 9300K, 6500K – default, 5400K, RGB), information, manual image adjust (H. size, H. position, V position, fine tune, sharpness, display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt -5°/+20° OPERATING Temperature 41-95°F (5-35°C) CONDITIONS Humidity 20-80% (non-condensing) DIMENSIONS Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) (W x H x D) Physical with stand 23.5" x 16.0" x 3.6" (596mm x 406mm x 93mm) WEIGHT Net with stand 16.3 lb. (7.4 kg) Net without stand 22.2 lb. (10.1 kg)		Frequency	F _h : 24~82kHz, F _v : 50~85Hz
Mac®** Power Mac™ G3/G4/G5/Mac mini up to 1920x1200		Sync	H/V separated (TTL)
CONNECTOR Analog/Digital 15-pin mini D-sub/DVI-D, 19-pin HDMI Power 3-pin AC plug (CEE22)	COMPATIBILITY	PC	VGA up to 1920x1200 non-interlaced
Power 3-pin AC plug (CEE22) POWER Voltage AC 100–240V (universal), 50/60Hz (auto switch) Consumption 64W (typ); below 1W in standby mode AUDIO Speakers 2x2.5 watts CONTROLS Basic Power, 1, down, up, 2 OnView® Auto image adjust, contrast, brightness, input select (analog, digital, HDMI), ViewMatch® color adjust (sRGB, 9300K, 6500K – default, 5400K, RGB), information, manual image adjust (H. size, H. position, V. position, fine tune, sharpness, display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt -5°/+20° OPERATING Temperature 41–95°F (5–35°C) CONDITIONS Humidity 20–80% (non-condensing) DIMENSIONS (M x H x D) Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) WEIGHT Net with stand 12.3 lb. (5.6 kg) Gross with stand 22.2 lb. (10.1 kg) REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, ROHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,		Mac®*	Power Mac™ G3/G4/G5/Mac mini up to 1920x1200
POWER Voltage AC 100–240V (universal), 50/60Hz (auto switch) Consumption 64W (typ); below 1W in standby mode AUDIO Speakers 2x2.5 watts CONTROLS Basic Power, 1, down, up, 2 OnView® Auto image adjust, contrast, brightness, input select (analog, digital, HDMI), ViewMatch® color adjust (sRGB, 9300K, 6500K – default, 5400K, RGB), information, manual image adjust (H. size, H. position, V. position, fine tune, sharpness, display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt -5°/+20° OPERATING Temperature 41–95°F (5–35°C) CONDITIONS Humidity 20–80% (non-condensing) DIMENSIONS Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) (W x H x D) Physical without stand 23.5" x 16.0" x 3.6" (596mm x 406mm x 93mm) WEIGHT Net with stand 16.3 lb. (7.4 kg) Net without stand 12.3 lb. (5.6 kg) Gross with stand 22.2 lb. (10.1 kg) REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,	CONNECTOR	Analog/Digital	15-pin mini D-sub/DVI-D, 19-pin HDMI
Consumption 64W (typ); below 1W in standby mode AUDIO Speakers 2x2.5 watts CONTROLS Basic Power, 1, down, up, 2 OnView® Auto image adjust, contrast, brightness, input select (analog, digital, HDMI), ViewMatch® color adjust (sRGB, 9300K, 6500K – default, 5400K, RGB), information, manual image adjust (H. size, H. position, V. position, fine tune, sharpness, display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt -5°/+20° OPERATING Temperature 41–95°F (5–35°C) CONDITIONS Humidity 20–80% (non-condensing) DIMENSIONS Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) (W x H x D) Physical without stand 23.5" x 16.0" x 3.6" (596mm x 406mm x 93mm) WEIGHT Net with stand 16.3 lb. (7.4 kg) Net without stand 12.3 lb. (5.6 kg) Gross with stand 22.2 lb. (10.1 kg) REGULATIONS REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,		Power	3-pin AC plug (CEE22)
AUDIO Speakers 2x2.5 watts CONTROLS Basic Power, 1, down, up, 2 OnView® Auto image adjust, contrast, brightness, input select (analog, digital, HDMI), ViewMatch® color adjust (sRGB, 9300K, 6500K – default, 5400K, RGB), information, manual image adjust (H. size, H. position, V. position, fine tune, sharpness, display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt -5°/+20° OPERATING Temperature 41-95°F (5-35°C) CONDITIONS Humidity 20-80% (non-condensing) DIMENSIONS Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) WEIGHT Net with stand 16.3 lb. (7.4 kg) Net with stand 12.3 lb. (5.6 kg) Gross with stand 22.2 lb. (10.1 kg) REGULATIONS REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,	POWER	Voltage	AC 100–240V (universal), 50/60Hz (auto switch)
CONTROLS Basic Power, 1, down, up, 2 Auto image adjust, contrast, brightness, input select (analog, digital, HDMI), ViewMatch® color adjust (sRGB, 9300K, 6500K – default, 5400K, RGB), information, manual image adjust (H. size, H. position, V. position, fine tune, sharpness, display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt -5°/+20° OPERATING CONDITIONS Humidity 20–80% (non-condensing) DIMENSIONS Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) WEIGHT Net with stand 16.3 lb. (7.4 kg) Net without stand 12.3 lb. (5.6 kg) Gross with stand 22.2 lb. (10.1 kg) REGULATIONS REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, ROHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,		Consumption	64W (typ); below 1W in standby mode
OnView® Auto image adjust, contrast, brightness, input select (analog, digital, HDMI), ViewMatch® color adjust (sRGB, 9300K, 6500K – default, 5400K, RGB), information, manual image adjust (H. size, H. position, V. position, fine tune, sharpness, display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt -5°/+20° OPERATING Temperature 41–95°F (5–35°C) CONDITIONS Humidity 20–80% (non-condensing) DIMENSIONS Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) WEIGHT Net with stand 16.3 lb. (7.4 kg) Net without stand 12.3 lb. (5.6 kg) Gross with stand 22.2 lb. (10.1 kg) REGULATIONS REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, ROHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,	AUDIO	Speakers	2x2.5 watts
(analog, digital, HDMI), ViewMatch® color adjust (sRGB, 930K, 6500K – default, 5400K, RGB), information, manual image adjust (H. size, H. position, V. position, fine tune, sharpness, display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt -5°/+20° OPERATING Temperature 41–95°F (5–35°C) CONDITIONS Humidity 20–80% (non-condensing) DIMENSIONS Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) (W x H x D) Physical without stand 23.5" x 16.0" x 3.6" (596mm x 406mm x 93mm) WEIGHT Net with stand 16.3 lb. (7.4 kg) Net without stand 12.3 lb. (5.6 kg) Gross with stand 22.2 lb. (10.1 kg) REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, ROHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,	CONTROLS	Basic	Power, 1, down, up, 2
9300K, 6500K – default, 5400K, RGB), information, manual image adjust (H. size, H. position, V. position, fine tune, sharpness, display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt -5°/+20° OPERATING Temperature 41–95°F (5–35°C) CONDITIONS Humidity 20–80% (non-condensing) DIMENSIONS (Humidity 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) (W x H x D) Physical with stand 23.5" x 16.0" x 3.6" (596mm x 406mm x 93mm) WEIGHT Net with stand 16.3 lb. (7.4 kg) Net without stand 12.3 lb. (5.6 kg) Gross with stand 22.2 lb. (10.1 kg) REGULATIONS REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,		OnView®	Auto image adjust, contrast, brightness, input select
9300K, 6500K – default, 5400K, RGB), information, manual image adjust (H. size, H. position, V. position, fine tune, sharpness, display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt -5°/+20° OPERATING Temperature 41–95°F (5–35°C) CONDITIONS Humidity 20–80% (non-condensing) DIMENSIONS (Humidity 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) (W x H x D) Physical with stand 23.5" x 16.0" x 3.6" (596mm x 406mm x 93mm) WEIGHT Net with stand 16.3 lb. (7.4 kg) Net without stand 12.3 lb. (5.6 kg) Gross with stand 22.2 lb. (10.1 kg) REGULATIONS REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,			(analog, digital, HDMI), ViewMatch® color adjust (sRGB,
display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt -5°/+20° OPERATING Temperature 41–95°F (5–35°C) CONDITIONS Humidity 20–80% (non-condensing) DIMENSIONS Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) (W x H x D) Physical without stand 23.5" x 16.0" x 3.6" (596mm x 406mm x 93mm) WEIGHT Net with stand 16.3 lb. (7.4 kg) Net without stand 12.3 lb. (5.6 kg) Gross with stand 22.2 lb. (10.1 kg) REGULATIONS REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,* PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR* standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,			
display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall ERGONOMICS Tilt -5°/+20° OPERATING Temperature 41–95°F (5–35°C) CONDITIONS Humidity 20–80% (non-condensing) DIMENSIONS Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) (W x H x D) Physical without stand 23.5" x 16.0" x 3.6" (596mm x 406mm x 93mm) WEIGHT Net with stand 16.3 lb. (7.4 kg) Net without stand 12.3 lb. (5.6 kg) Gross with stand 22.2 lb. (10.1 kg) REGULATIONS REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,* PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR* standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,			image adjust (H. size, H. position, V. position, fine tune, sharpness,
ERGONOMICSTilt-5°/+20°OPERATINGTemperature41–95°F (5–35°C)CONDITIONSHumidity20–80% (non-condensing)DIMENSIONSPhysical with stand23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm)(W x H x D)Physical without stand23.5" x 16.0" x 3.6" (596mm x 406mm x 93mm)WEIGHTNet with stand16.3 lb. (7.4 kg)Net without stand12.3 lb. (5.6 kg)Gross with stand22.2 lb. (10.1 kg)REGULATIONSUL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-SilverRECYCLE/DISPOSALThe lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.POWER MANAGEMENTMeets TCO'03 and ENERGY STAR® standardsPACKAGE CONTENTSLCD display, video cable, audio cable, power cable,			display mode), setup menu (language, resolution notice, OSD
ERGONOMICSTilt-5°/+20°OPERATINGTemperature41–95°F (5–35°C)CONDITIONSHumidity20–80% (non-condensing)DIMENSIONSPhysical with stand23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm)(W x H x D)Physical without stand23.5" x 16.0" x 3.6" (596mm x 406mm x 93mm)WEIGHTNet with stand16.3 lb. (7.4 kg)Net without stand12.3 lb. (5.6 kg)Gross with stand22.2 lb. (10.1 kg)REGULATIONSUL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-SilverRECYCLE/DISPOSALThe lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.POWER MANAGEMENTMeets TCO'03 and ENERGY STAR® standardsPACKAGE CONTENTSLCD display, video cable, audio cable, power cable,			position, OSD timeout, OSD background), memory recall
CONDITIONS Humidity 20–80% (non-condensing) Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm) (W x H x D) Physical without stand 23.5" x 16.0" x 3.6" (596mm x 406mm x 93mm) WEIGHT Net with stand 16.3 lb. (7.4 kg) Net without stand 12.3 lb. (5.6 kg) Gross with stand 22.2 lb. (10.1 kg) REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,	ERGONOMICS	Tilt	
Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm)	OPERATING	Temperature	41–95°F (5–35°C)
Physical with stand 23.5" x 18.9" x 10.0" (596mm x 480mm x 254mm)	CONDITIONS	Humidity	20–80% (non-condensing)
WEIGHT Net with stand 16.3 lb. (7.4 kg) Net without stand 12.3 lb. (5.6 kg) Gross with stand 22.2 lb. (10.1 kg) REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,	DIMENSIONS	Physical with stand	
Net without stand 12.3 lb. (5.6 kg) Gross with stand 22.2 lb. (10.1 kg) REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,	(W x H x D)	Physical without stand	23.5" x 16.0" x 3.6" (596mm x 406mm x 93mm)
Gross with stand 22.2 lb. (10.1 kg) REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,	WEIGHT	Net with stand	16.3 lb. (7.4 kg)
REGULATIONS UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,		Net without stand	12.3 lb. (5.6 kg)
ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,		Gross with stand	22.2 lb. (10.1 kg)
RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,	REGULATIONS		UL, cUL, FCC-B, CB, CE, NOM, IRAM, ERGO (covers
RECYCLE/DISPOSAL The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,			ISO13406-2), BSMI, CCC, ENERGY STAR,® PSB, C-TICK,
in accordance with local, state or federal laws. POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,			RoHS, WEEE, VCCI, GOST-R, SASO, TCO'03, EPEAT-Silver
POWER MANAGEMENT Meets TCO'03 and ENERGY STAR® standards PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,	RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of
PACKAGE CONTENTS LCD display, video cable, audio cable, power cable,			in accordance with local, state or federal laws.
	POWER MANAGEMENT		
Quick Start Guide, ViewSonic Wizard (DVI and HDMI cables	PACKAGE CONT	ENTS	LCD display, video cable, audio cable, power cable,
			Quick Start Guide, ViewSonic Wizard (DVI and HDMI cables











ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



Three-year limited warranty on parts, labor and backlight

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 ViewSonic Corporation. All rights reserved. [14028-028-10/08] VA2626wm-1

WARRANTY