

2D Barcode Scanner with Laser Aimer | 6" Gorilla Glass Display | Android 12 with 4G/64G memory

The unitech EA630Plus continues progressing with an advanced Android 12 system to optimize high-performance 2D barcode experience, accelerating and improving labor productivity tremendously than ever. The full touch 6" Gorilla screen offers clear visibility up to 80% screen-to-body ratio. A bigger 4G/64G mobile storage mitigates the possibility of data missed. The Ultra Slim Rugged Smartphone drives up stock management more efficiently in the retail, hospitality, and health service industries.

Latest Android 12 OS on Large Screen

Operated under Android 12 OS with GMS Certified, the EA630 Plus rugged smartphone has a 6-inch 18:9 display offering 80% screen-to-body ratio. The 450nits brightness provides easy viewability even in sunlight environment.

A Data Collector for All Your Need

EA630 Plus not only fulfills superior 1D/2D scanning performance but surpass end-user expectations. A wide series of practical features, including an NFC reader/writer, GPS, and a high-resolution 5MP front and 16MP rear camera, further strengthen traceability and functionality in a compact device. Attach and ready-to-use. With the unique UHF RFID gun grip, EA630 Plus allows users to add values much simpler.

Stay Connected with Lasting Battery life

Featuring the fastest data speeds with fast roaming function on dual bands WLAN, 4G LTE connectivity and Bluetooth® 5, the EA630 Plus bridges the gap between associates to ensure instant message and alerts are received within teams. With a long-lasting 4000mAh removable smart battery, the EA630 Plus offers continuous use for hours and it is easily replaced.

Durable design and flexible Options

EA630 Plus enhances the industrial durable protection with features including IP65 dustproof, waterproof, and 1.2 meters resistance to fall protection. (1.5 meters with boot case) It has various accessories such as RFID gun grip and cradles and also supports unitech software solutions, SDKs, MoboLink, and 3rd party MDM solutions such as VMware AirWatch, SOTI, Ivanti Wavelink.

Features

- 6 inch rugged smartphone with a screen-to-body ratio of over 80%
- Android 12 OS with GMS Certification
- All-In-One functionality: 2D Imager, NFC, 5MP front camera, and 16MP rear camera
- Rugged: Corning® Gorilla® Glass touch display, IP65 rated, and 1.2M drop (1.5M with boot case)
- Long-lasting removable 4000mAh smart battery
- Dual bands WLAN with fast roaming / 4G LTE / Bluetooth® 5
- Support unitech software solutions, SDKs, MoboLink, and MDM solutions









EA630 Plus

Specifications





System Features

OS Android 12 GMS certified GMS certified

2GHz, Qualcomm® Snapdragon™ 662 CPU

64bits Octa-core Processor

4 GB RAM / 64 GB Flash Memory Multiple languages Languages support

3rd Gen Qualcomm Al Engine ΑI

Display

Capacitive type 5 points multi-touch touch panel with Gorilla® Glass 6", 18:9 Full-HD (2160 x 1080) color screen (450nits)

Buttons / Keypad

5 keys- Programmable function button; dual dedicated scan buttons; volume up/down buttons; on/off button

Indicator Type

LED, Speaker, Vibrator

I/O Interfaces

USB USB 3.1 (type-C) support USB OTG

Support Ethernet/USB-Host via cradle

SIM Slot Dual nano SIM Slot **Expansion Slot** MicroSD, up to 256 GB

PogoPin backside: Support Gun-grip, UHF reader POGO PIN

PogoPin bottom: Charging via cradle

Audio

One speaker with Smart PA (95±3dB @ 10cm), One receiver, Dual noise-cancelling microphones

Power Source

Main Battery 3.85V, 4000mAH Li-polymer battery

Regulatory Approvals

CE, FCC, NCC, VCCI, TELEC, CCC, SRRC, RoHS, CEC, BQB, N-Mark







Headquarters

Taipei, Taiwan http://www.ute.com e-mail: info@hq.ute.com

unitech America

Los Angeles

http://us.ute.com e-mail: info@us.ute.com http://can.ute.com info@can.ute.com

http://latin.ute.com e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East

http://apac.ute.com info@apac.ute.com / info@india.ute.com

http://mideast.ute.com info@mideast.ute.com

Communication

WWAN

RFID/HF

5MP front camera Camera

16 MP Rear with auto-focus function and Flash Light

Bluetooth® 5 supported Bluetooth[®]

Wireless LAN 802.11a/b/g/n/ac, 2.4GHz and 5GHz WI AN

Support 802.11d/e/h/i/k/r/v, fast roaming

Compliant with WEP, WPA and IEEE 802.11i WPA2

GSM: 850,900,1800,1900 MHz

WCDMA: Band 1, Band 2, Band 5, Band 8

LTE:FDD-LTE(B1/B2/B3/B4/B5/B7/B8/B12/B17/B19/B20/B28)

TDD-LTE (B38/B39/B40/B41)

GPS AGPS, GPS, GLONASS, Beidou, Galileo

Support HF/NFC Frequency 13.56Mhz

Support: ISO14443A/B, ISO15693, Mifare, Felica(ISO/IEC18092)

Sensor Gyroscope, Light sensor, e-Compass, Proximity sensor,

Accelerometer sensor

Symbologies

UPC/EAN/JAN, GS1 DataBar, Code 39, Code 1D Barcodes

128, Code 11, Code 93, Codabar/NW7, Interleaved 2

of 5, Matrix 2 of 5, MSI, Trioptic, Code 32

2D Barcodes PDF417, MicroPDF417, GS1 Composite, Aztec Code,

Data Matrix, QR Code, Micro QR Code, MaxiCode, Han

Xin Code, DOT Code

Postal Intelligent Mail Barcode, Postal-4i, Australian

Post, Japanese Post, Netherlands (KIX) Post,

Postnet, Planet Code

OCR OCR-A, OCR-B, E13B (MICR)

Environmental

Operating temperature -10°C to 50°C

- 30°C to 70°C (without battery) Storage temperature

Charging temperature 0°C to 45°C

10% ~ 90% (Non-Condensing) Relative Humidity

Durability

Drop Specification 1.2m, 1.5m with boot case

Sealing

Vibration/ Tumble test MIL-STD 810G

Enclosure

157mm x 76.4mm x 13.9mm (H x W x D) Dimensions

Weight 232q

Accessories

Stylus Hand strap Quick charge adaptor (via USB type-C cable)

USB 3.0 type-C cable

9H glass screen protector Gun grip: standard/ UHF

Single Slot Charging cradle Single Slot USB cradle Single Slot Ethernet cradle 4 Slots Ethernet cradle

4 Slots Terminal Charging cradle

unitech Europe

Tilburg / Netherlands

http://eu.ute.com e-mail: info@eu.ute.com

unitech Japan

http://jp.ute.com e-mail: info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen http://cn.ute.com info@cn.ute.com Taipei http://tw.ute.com info@tw.ute.com





EA630 Plus

Software Solution

Development Tools









Unitech offers a number of SDK toolkits for developers to write apps that can interact with the unitech devices for the mobile, scanner, and the RFID product lines.

Device Management

SOTI **m**ware **9** 426EARS





Staging and Management



Android Enterprise ready EMM for monitoring device health and managing apps, configs and files.



StageGO

Barcode-based device staging utility offering hundreds of script commands for you to work with.



OEMConfig

If you are using a third party EMM, OEMConfig will allow those EMM solutions to configure unitech specific settings on the device.



Enterprise Launcher

Secure your devices by kiosking them with Enterprise Launcher. Block access to the Android system and only allow limited number of apps to be run.



Battery info

Monitor advanced Battery health and manage the battery replacement cycle. Use with MoboLink to get real-time attery health alerts delivered to your phone.



Software Update

Check and install software undates online

To let a device always stay up-to-date, setup the device to automatically check and install for updates on boot up.



System Update Center

Check and install firmware updates via FOTA. You can update the firmware via online FOTA server, or by using a OTA ZIP file placed in the internal storage.







USS Profile

Configure all scanner settings with friendly user interface and enable the service to make scanning data as keypad input.



Capture barcode data using the device camera and send the data to your applications as keyboard inputs.



KeyRemap

Reprogram physical buttons to act as another key or to launch an app.



WLAN Advanced

Configure advanced WLAN settings such as power saving mode and roaming parameters.



NTP Server Settings

Customize the NTP server setting to keep your device date and time synchronized.





UNote

A simple text viewer and editor for use in your work flows.



Startup

Auto-run apps when device boots up.