



2-Port USB/HD Cable KVM Switch with Audio/Video, Cables and USB Peripheral Sharing

MODEL NUMBER: B032-HUA2





Control 2 computers using one HDMI monitor, USB keyboard and USB mouse. Connect a USB 2.0 hub (sold separately) to share USB peripherals, such as printers and hard drives, between computers.

Features

Access and Control 2 Computers with One Keyboard/Mouse/Monitor

- Recommended for home, office, gaming and multimedia applications
- Switch between computers using remote port selector, hotkeys or mouse wheel
- Supports video resolutions up to 1920 x 1200 (1080p)
- Supports 2.1-channel surround sound with full bass
- · Listen to audio files on one computer while accessing the other
- Compliant with EDID and HDCP
- Built-in 4-ft. (1.22 m) HDMI, USB and audio cables

USB 2.0 Peripheral Sharing

 Adding an optional USB hub (sold separately) to the USB console mouse port allows connection of peripherals, such as printers, hard drives, scanners, webcams and thumb drives

Flexible Keyboard/Mouse Applications

- Console mouse port emulation/bypass supports most mouse drivers and multifunction mice
- · Works with multimedia keyboards and wireless keyboards and mice
- Supports Mac keyboard emulation

Easy Plug-and-Play Setup and Use

Compatible with Windows, Mac and Linux

- No external power supply, software or drivers to install
- · Switches automatically to other computer when one powers off
- Upgradable firmware
- Takes up no valuable desk space

Highlights

- Built-in 4-ft. (1.22 m) HDMI, USB and audio cables
- Supports video resolutions up to 1920 x 1200 (1080p)
- Supports 2.1-channel surround sound with full bass
- Remote, hotkey and mouse port switching
- Compatible with Windows®, Mac® and Linux®

System Requirements

- HDMI monitor
- USB keyboard
- USB mouse
- Computers with HDMI and USB ports

Package Includes

- B032-HUA2 2-Port USB/HD Cable KVM Switch
- Owner's manual





Specifications

OVERVIEW		
UPC Code	037332200396	
Max CPU	2	
Technology	HDMI; Stereo Audio; USB 2.0 (High Speed)	
VIDEO		
Number of Monitors Supported	1	
Max Supported Video Resolution	1920 x 1200	
Max Number of Ports (Entire Chain)	2	
Extended Mode	No	
Mirror Mode	No	
AUDIO		
Audio Specification	2.1 Channel Surround Sound	
INPUT		
Built-In Cable Length (ft.)	4	
Built-In Cable Length (m)	1.2	
Built-In Cable Length (in.)	48	
Built-In Cable Length (cm)	121.9	
Redundancy - Dual Power Inputs	No	
Bus Powered	Yes	
CONNECTIONS		
Number of Ports	2	
Daisy-Chain Port	No	
Firmware Upgrade Port	No	
PC/Server Connections	USB; HDMI	
Side A - Connector 1	HDMI (FEMALE)	
Side A - Connector 2	(2) USB A (FEMALE)	
Side A - Connector 3	(2) 3.5MM (FEMALE)	
Side B - Connector 1	(2) HDMI (MALE)	
Side B - Connector 2	(4) USB A (MALE)	
Side B - Connector 3	(4) 3.5MM (MALE)	





PHYSICAL	
Color	Black
Material of Construction	Plastic
Cable Jacket Color	Black
Rackmountable	No
Shipping Dimensions (hwd / in.)	2.40 x 6.70 x 9.40
Shipping Dimensions (hwd / cm)	6.10 x 17.02 x 23.88
Shipping Weight (lbs.)	1.20
Shipping Weight (kg)	0.54
Unit Dimensions (hwd / in.)	0.970 x 2.630 x 3.260
ENVIRONMENTAL	
Operating Temperature Range	32° to 122°F (0° to 50°C)
Storage Temperature Range	-4° to 140°F (-20° to 60°C)
Relative Humidity	0-80% non-condensing
Operating Temperature	32° to 122°F (0° to 50°C)
COMMUNICATIONS	
Hotkey	Yes
Port Control	Push Buttons, Hotkeys
IP Remote Access	No
FEATURES & SPECIFICATIONS	
NIAP-Certified Secure	No
Number of Users	1
On-Screen Display (OSD)	No
Port Selection	Hotkey; Mouse; Remote Selector
Driver Required	No
REMOTE ACCESS	
Modem Port	No
STANDARDS & COMPLIANCE	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	3-year limited warranty





1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.