

4XEM's 33W Wall Charger Dual Output

4XEM Part- 4XGAN00533WW



4XEM's 33W USB-C offers amazing charging power and speed with two USB ports capable of charging a variety of devices simultaneously. USB-A has long been a standard port allowing for charging or power to legacy and current devices; however, USB-C is rapidly becoming the new standard for charging devices, allowing for up to 33W charging for power at faster speeds. This device features 1x USB-C ports and 1x USB-A port. Keep your USB devices charged on the go or at home reliably with 4XEM's USB-C and A Charger.

Problem it solves: Charge one or two USB devices with reliable power and speed using 4XEM's 33W GaN Wall Charger.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com



Features:

- 33-Watt power budget
- 1x USB-C port
- 1x USB-A port
- Wall mounted charger
- Compatible with any USB charged device
- Compact travel size
- Rounded edges
- Fast Charging



Applications:

- Home
- Office
- Travel
- Meetings
- Classrooms
- Quick Charging



4XEM Products Are Available At Your Favorite Online Retailers





DATA SHEET

Warranty Information	Warranty	1 Year
Connector(s)	Charging Port(s)	1x USB Type-C Female 1x USB Type-A Female
	Power Source	Non-Polarized NEMA 1-15P (Standard NA Wall Outlet) Fixed with Retractable Prongs
Performance	Industry Standards	USB-PD 3.0 PPS
	Certifications	CE ROHS ETL CB CCC
Physical Characteristics	Colour	White
	Display	None
	LED Indicator(s)	None
	Power Cable Length	N/A
	Product Height	1.54 in [39.2 mm]
	Product Width	1.33 in [33.7 mm]
	Product Length	1.58 in [40.2 mm]
	Weight of Product	2.21 in [56.2 mm] (with power prongs out) 2.05 oz [58 g]
Power	Total Power Budget	33W
	Power Delivery	33W Max
	Input Voltage	100-240VAC, 50Hz-60Hz @ 0.85A
	Output Voltage (C1)	30W: 5/9V 3A, 12V 2.5A, 15V 2A, 20V 1.5A 33W PPS: 3.3V-11V 3A, 3.3V-16V 2A
	Output Voltage (A1)	30W: 5/9V 3A, 12V 2.5A
	Output Voltage (C1 + A1)	20W: 5V 4A (Shared)
Environmental	Operating Temperature	32°F to 104°F [0°C to 40°C]
	Storage Temperature	-4°F to 176°F [-20°C to 80°C]
	Humidity	5% to 90% (non-condensing)
Packaging Information	Package Type	Poly-Bag
	Package Height	4.00 in [101.6 mm]
	Package Width	3.00 in [76.2 mm]
	Package Length	1.33 in [33.9 mm]
	Shipping (Package) Weight	2.12 oz [60 g]
What's in the Box	Included in Package	1x 33W USB-C + USB-A GaN Charger

* Product appearance and specifications are subject to change without notice.
* Same day shipping is only available for orders shipping within the United States.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com

