






Powering Business Worldwide

9PX G2 10kVA 120V Step-Down Transformer - 8 NEMA 5-20R and 2 L14-30R Outlets, 50/60 Hz, Hardwire Input, 3U Rack/Tower

MODEL NUMBER: 9PXTFMR11G2



10kVA transformer converts UPS 208V input to 120V for powering low-voltage AC components.

Features

208V to 120V Transformer Converts High-Voltage Input to Low-Voltage Output

This 10kVA Step-Down Transformer converts your UPS system's 208V high-voltage input to 120V low-voltage output. It features eight NEMA 5-20R and two L14-30R outlets for connecting equipment. Resettable circuit breakers protect your 120V equipment against overload conditions. The 9PXTFMR11G2 works with Eaton's 9PX8KG2 and 9PX11KG2 9PX G2 UPS systems.

Versatile Installation Options

You can mount the 9PXTFMR11G2 in 3U of space in an EIA-standard 19-inch rack using the included 4-post rail kit or adapt it for tower installation using the included joining bracket and hardware. Cable glands are included for hardwire input.

Specifications

OVERVIEW	
UPC Code	786689876029
Accessory Type	Isolation Transformer
Accessory Class	UPS Accessories
INPUT	
Input Phase	Single-Phase
UPS Input Connection Type	Hardwire
Input Plug Type	Hard-wire
OUTPUT	

Highlights

- Converts 208V AC input into 120V output for powering low-voltage equipment
- 8 NEMA 5-20R and 2 L14-30R 120V outlets for connecting components
- Resettable circuit breakers protect mission-critical equipment from hazardous overloads
- Requires hardwired connection to Eaton 9PX8KG2 or 9PX11KG2 9PX G2 UPS systems

System Requirements

Compatible with Eaton's 9PX8KG2 and 9PX11KG2 9PX G2 UPS systems

Package Includes

- 9PXTFMR11G2 10kVA 120V Step-Down Transformer
- Hardwire cable
- (2) Cable glands
- Joining bracket and hardware for tower configuration
- Rack-mounting hardware
- Owner's manuals



Powering Business Worldwide

Output Capacity (VA)	10000
Output Capacity (kVA)	10
Output Capacity (Watts)	10000
Output Capacity (kW)	10
Frequency Compatibility	50 / 60 Hz
Output AC Waveform (Battery Mode)	Pure Sine wave
Nominal Output Voltage(s) Supported	100V; 110V; 120V
Output Receptacles	(8) 5-20R; (2) L14-30R
Individually Controllable Load Banks	No
BATTERY	
Expandable Runtime	No
PHYSICAL	
Primary Form Factor	Rackmount; Tower
Rack Height	3U
Unit Dimensions (hwd / in.)	5.120 x 17.300 x 27.400
ENVIRONMENTAL	
Operating Temperature Range	32° to 104°F (0° to 40°C)
Relative Humidity	0-95% non-condensing
STANDARDS & COMPLIANCE	
Product Certifications	cUL Listed; NOM (Mexico)
Product Compliance	CE (Europe); ENERGY STAR Qualified; RoHS
WARRANTY & SUPPORT	
Product Warranty Period (U.S. & Canada)	3-year limited warranty
Extended Service Plans	ADVANCED DEPOT EXCHANGE Service Part Number: 9SW5Y-11000UCExpedited parts coverage for 5 yearsParts, electronics and UPS batteries coverageNext business day shippingTechnical support ON-SITE 24X7, NEXT DAY RESPONSE (US ONLY) 2 YEAR UPGRADE: WUN72XXX-11000UCOn-site expedited parts and labor coverage for first 2 yearsParts, electronics and UPS batteries coverageEaton on-site labor coverage24x7 coverage, next day responseNext day shippingTechnical support 3 YEAR FLEX PLAN: FLN73XXX-11000UC On-site parts and labor coverage for years 3 to 5Parts, electronics and UPS batteries coverage24x7 on-site labor coverage, next day repsonseNext day shippingTechnical support

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.