

PowerLite[®]
1720
Multimedia Projector




Light, bright and energy efficient.

- Lightweight and travel friendly — weighs just 3.7 lb
- Ultra bright — 3000 lumens color and 3000 lumens white light output*
- Incredible clarity and detail — native XGA (1024 x 768) resolution
- Rich, vibrant color; reliable performance — Epson 3LCD, 3-chip technology
- Energy and cost-efficient — E-TORL[®] lamp lasts up to 4000 hours**
- Ideal for any setting — sleek design and short throw distance
- Added features, no added cost — built-in closed captioning capabilities



PowerLite 1720

Multimedia Projector



ORDERING INFORMATION

Product Name	Product Code	UPC
PowerLite 1720	V11H269020	010343 86952 3
Replacement Lamp	V13H010L48	010343 86956 1
Replacement Air Filter	V13H134A19	010343 86957 8

SPECIFICATIONS

Projection System

Epson 3LCD, 3-chip technology

Projection

Front/rear/ceiling mode

Driving Method

Epson Poly-silicon TFT Active Matrix

Pixel Number

786,432 dots x 3 (1024 x 768) LCDs

White Light Output*

3000 lumens (ISO 21118 standard)

Color Light Output*

3000 lumens

Aspect Ratio

4:3 (supports 16:9)

Native Resolution

1024 x 768 (XGA)

Resize

640 x 480 (VGA), 800 x 600 (SVGA),
1280 x 800 (WXGA), 1280 x 1024 (SXGA),
1400 x 1050 (SXGA+), 1440 x 900 (WXGA+),
1680 x 1050 (WSXGA+), 1600 x 1200 (UXGA)

Lamp Type

E-TORL 170 W UHE

Lamp Life**

Up to 4000 hours (Low Light Output Mode)
Up to 3000 hours (High Light Output Mode)

Throw Ratio Range

1.09 – 1.34

Size (projected distance)

30" – 300" (2.1' – 27.1')

Keystone Correction Automatic

Automatic: Vertical: ± 30 degrees
Manual: Vertical: ± 30 degrees

Contrast Ratio

Up to 2000:1

Color Reproduction

16.77 million colors

PROJECTION LENS

Type

Manual focus/Manual zoom

F-number

1.58 – 1.68

Focal Length

16.1 – 19.3 mm

Zoom Ratio

Optical zoom 1.0 – 1.2

OTHER

Display Performance

NTSC: 560 line

PAL: 560 line

(depends on observation of the multi-burst pattern)

Input Signal

NTSC/NTSC4.43/PAL/M-PAL/N-PAL/
PAL60/SECAM SDTV/HDTV

Interfaces

Computer/component video:

Mini D-sub HD 15 pin x 1

S-video: Mini DIN x 1

Composite video: RCA x 1

Audio in: Mini stereo x 1

USB connector: Type B x 1 (for mouse/keyboard control)

Audio Output

1 W mono speaker

Audio Signal

500mV rms/47K ohm

Operating Temperature

41° to 95° F (5° to 35° C)

Power Supply Voltage

100 – 240 V ± 10%, 50/60 Hz AC

Power Consumption

243 W, 4 W standby

Fan Noise

High Light Output Mode: 39 dB

Low Light Output Mode: 30 dB

Security

Kensington-style lock provision

DIMENSIONS (W x D x H)

Including feet: 11.2" x 7.9" x 2.8"

Excluding feet: 11.2" x 7.9" x 2.6"

Weight: 3.74 lb/1.7 kg

REMOTE CONTROL

Features

Power, source search selection, computer, S-video, video, A/V mute, freeze, user ID, auto, aspect, color mode, num, page up and down, E-zoom, volume, help, menu, enter, esc and pointer functions

Operating Angle

Right/left:

Front: ± 60 degrees

Rear: ± 30 degrees

Upper/lower:

Front: -30 to +45 degrees

Rear: ± 30 degrees

Operating Distance

19.7 ft (6 m)

SUPPORT — THE EPSON CONNECTIONSM

Pre-sales support

U.S. and Canada 800-463-7766

Internet website www.epson.com

Service Programs

Two-year limited warranty, Epson Road

Service program, Epson PrivateLine[®]

dedicated toll-free support (U.S. and

Canada only) and 90-day limited lamp

warranty

Contents

Power cable, computer cable (VGA), projector remote control with batteries, USB cable, audio adapter, soft carrying case, user manual CD, Quick Setup Sheet, PrivateLine support card, registration card and password protection sticker

ACCESSORY PART NUMBERS

Distribution amplifier ELPDA01

Image presentation camera (ELPDC05)

V12H162020

Component to VGA video cable ELPKC19

S-video cable ELPSP01

SwissGear[®] backpack ELPKS63

Wheeled soft case ELPKS62

Soft shoulder case for ELPKS61

projector and laptop

Molded hardshell case ELPKS58

50" portable screen ELPSC06

60" portable pop-up screen ELPSC07

80" portable pop-up screen ELPSC08

Duet[™] screen ELPSC80

Epson DC-10s document camera ELPDC10S

Kensington security lock ELPPL01

Universal ceiling mount ELPMBPJF

PACKAGING SPECIFICATIONS

PowerLite 1720

Dimensions 19.4" x 14.2" x 7.6" (W x D x H)

Weight 10.12 lb

Replacement Lamp

Dimensions 5.1" x 5.5" x 5.6" (W x D x H)

Weight 0.24 lb

Master Carton

Dimensions 11.5" x 26.0" x 6.8" (W x D x H)

Weight 3.96 lb

Units Per Master Carton 10

Replacement Air Filter

Dimensions 3.5" x 4.8" x 1.9" (W x D x H)

Weight 0.08 lb

Master Carton

Dimensions 7.3" x 10.1" x 5.7" (W x D x H)

Weight 1.3 lb

Units Per Master Carton 10

* Light output varies depending upon modes (color and white light output). White light output measured using ISO 21118 standard.

** Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time.

Epson America, Inc.

3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.

3771 Victoria Park Avenue, Toronto, Ontario M1W 3Z5