# HP 90W Smart AC Adapter

Provide optimal power and help offset power fluctuations to your HP notebook with a HP 90W Smart AC Adapter. Now available with a new right-angled (90°) connector that reduces cable stress and an optional 4.5mm to 7.4mm conversion dongle. As a replacement or back-up adapter, be prepared with the right connection.



\*Product image may differ from actual product

### Operate with confidence

Operate with confidence with optimal performance using smart-pin technology and reduce the risk of power surges, while drawing only minimal power as needed.

#### **Connection versatility**

Connection versatility with a specially designed dongle allowing for simple conversion from the new standard 4.5mm connector to HP predecessor notebooks with 7.4mm connectors.

### Tight access made convenient

Tight access made convenient – the new right-angled (90°) 4.5mm connector allows for connecting in limited spaces and reduces cord bending providing better cable management and longevity.



# HP 90W Smart AC Adapter

## Specifications

| Product number                            | H6Y90AA   |
|---|---|
| Supported platforms                       | HP Notebooks with 4.5mm, 7.4mm connectors   |
| UPC number                                | 887758607725  |
| Connection type                           | 4.5 mm barrel port  |
| Input frequency                           | 47-63 Hz  |
| Input operating current                   | 1.5 A at 90 VAC max   |
| Input efficiency                          | 89% min at 115 VAC/230 VAC at 20V/3.25A   |
| Output power                              | 90 W  |
| Output voltages                           | 19V   |
| Hold-up time                              | 5 ms at 115 VAC input   |
| Output current limit                      | 11 A max  |
| Technical notes                           | Small dongle much be used to attach to HP Tablet PCs.   |
| Connector description                     | 4.5mm(F)-7.4mm(M) dongle  |
| Cable length                              | 70.87 in (power cable); 39.37 in (4.5 mm connector cable);  |
| System Requirements, Minimum              | 4.5 mm AC jack  |
| Warranty                                  | One-year, worldwide parts-and-labor limited warranty  |
| Certifications and compliances            | CE Mark; IEC 60950-1; EN 60950-1; UL 60950-1; UL 62368-1; SELV; C-UL-US; DENAN; EN 55022 Class B; FCC Class B; CISPR 32 Class B; CCC; NOM-1 NYCE; NORDICS; MTBF |
| What's in the box                         | 90W AC Adapter, power cable, warranty booklet   |
| Country of origin                         | China   |
| Package dimensions (W x D x H)            | 6.14 x 8.27 x 3.03 in;  |
| Package weight                            | 1.54 lb;  |
| Operating temperature range               | 0 to 35°C; 32 to 95°F   |
| Storage temperature range (Celsius)       | -20 to 85°C   |
| Storage temperature range<br>(Fahrenheit) | -4 to 185°F   |
| Operating humidity range                  | 20 to 95% RH (non-condensing)   |
|   |   |



## HP 90W Smart AC Adapter

### Footnotes

**Messaging Footnotes** 



