



BUSINESS PRODUCTIVITY MONITOR

PRO MP251 E2

SLIM, SLEEK, SMOOTH



SPECIFICATIONS

PANEL SIZE	24.5"
PANEL RESOLUTION	1920 x 1080 (FHD)
REFRESH RATE	120Hz
RESPONSE TIME	1ms (MPRT) / 4ms (GTG)
PANEL TYPE	IPS
VIEWING ANGLE	178°(H) / 178°(V)
ASPECT RATIO	16:9
CONTRAST RATIO	1500:1
PIXEL PITCH (H X V)	0.2832(H) x 0.2802(V)
HDR SUPPORT	HDR Ready
sRGB	99%
ACTIVE DISPLAY AREA (MM)	543.744(H) x 302.616(V)
SURFACE TREATMENT	Anti-glare
DISPLAY COLORS	16.7M
COLOR BIT	8 bits (6 bits + FRC)
VIDEO PORTS	1x HDMI™ 2.0 (FHD@120Hz) 1x DisplayPort (1.4a) 1x D-Sub (VGA)
AUDIO PORTS	1x Headphone-out 1x Line-in
KENSINGTON LOCK	Yes
SPEAKER	2x 2W
BRIGHTNESS (NITS)	300 cd/m2
VESA MOUNTING	100 x 100 mm
POWER TYPE	External Adaptor 12V 2.5A
DYNAMIC REFRESH RATE TECHNOLOGY	Adaptive-Sync
POWER INPUT	100~240V, 50~60Hz
ADJUSTMENT (TILT)	-5° ~ 20°
DIMENSION (W X H X D)	556.89 x 413.91 x 188.2 mm (21.92 x 16.30 x 7.40 inch)
CARTON DIMENSION (W X H X D)	630 x 411 x 142 mm (24.8 x 16.18 x 5.59 inch)
WEIGHT (NW / GW)	2.7 kg (5.95 lbs) / 4.9 kg (10.8 lbs)
CERTIFICATES	CB/CE Energy Star

FEATURES

Compatibility

PC, Mac, PS5™, PS4™, Xbox, Mobile, Notebook

* All trademarks and the registered trademarks are the property of their respective owners.

NOTE

HDMI™: 1920 x 1080 (Up to 120Hz)

DisplayPort: 1920 x 1080 (Up to 120Hz)

D-Sub (VGA): 1920 x 1080 (Up to 60Hz)

HDMI™ CEC Support

*sRGB follow CIE1976 Standard

CONNECTIONS



1. 1x DC-in
2. 1x DisplayPort 1.4a
3. 1x HDMI 2.0 (FHD@120Hz)
4. 1x D-Sub (VGA)
5. 1x Line-in
6. 1x Headphone-out
7. 1x Kensington Lock
8. 1x 5-way navigator